

Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

STRAPPING SOLUTIONS

In the appropriate applications, plastic strapping has consistently proven to reduce the amount of packaging at the source over alternative packaging methods. Source reduction means using less material to hold or package a product. This means less packaging to discard at the destination and less material to recycle. In addition, when you can apply plastic strapping with a machine or friction weld tool you further reduce the packaging by eliminating a mechanical seal, plastic is also light and flexible, making it the safest alternative for many applications.



Polypropylene Hand Grade Strapping- for applications ranging from lightweight hand-applied strapping to heavy duty strapping for use with power tools.

| Grainger Item Number | | Environmentally Responsible | Safety Enhanced | Productivity Levels |
|-------------------------|--|--------------------------------|--------------------|------------------------|
| 8DXA8 | Hand Grade Polypropylene, 16 mil, 6,600 ft./coil, BK | ✓ | ✓ | Medium |
| 2CXG9 | Hand Grade Polypropylene, 17.7 mil, 4,500 ft./coil, BK | V | ✓ | Medium |
| 2CXH1 | Hand Grade Polypropylene, 17.7 mil, 9,000 ft./coil, BK | V | ✓ | Medium |
| 41P039 | Hand Grade Polypropylene, 18 mil, 9,000 ft./coil, BK | ✓ | ✓ | Medium |
| 41P046 | Hand Grade Polypropylene, 18 mil, 9,000 ft./coil, BK | ✓ | ✓ | Medium |
| 6LFZ5 | Hand Grade Polypropylene, 22 mil, 300 ft./L, Smooth | V | ✓ | Medium |
| 41P045 | Hand Grade Polypropylene, 22 mil, 9,000 ft./coil, 8"W x 8"D, E | 3K ✔ | ✓ | Medium |
| 41P044 | Hand Grade Polypropylene, 22 mil, 9,000 ft./coil, 16"W x 6"D, | BK ✔ | ✓ | Medium |
| 6LFZ8 | Hand Grade Polypropylene, 22 mil, 9,000 ft./coil, 8"W x 8"D, E | 3K ✔ | ✓ | Medium |
| 6LFZ7 | Hand Grade Polypropylene, 22 mil, 9,000 ft./coil, 16"W x 6"D, | BK ✔ | ✓ | Medium |
| 6LFZ4 | Hand Grade Polypropylene, 23 mil, 300 ft./L, Smooth | ✓ | ✓ | Medium |
| 6LFZ9 | Hand Grade Polypropylene, 22 mil, 4,500 ft./coil, BK | V | ✓ | Medium |
| 2CXH6 | Hand Grade Polypropylene, 25 mil, 3,000 ft./coil | V | ✓ | Medium |
| 2CXH7 | Hand Grade Polypropylene, 25 mil, 6,000 ft./coil | V | V | Medium |
| 6LFZ6 | Hand Grade Polypropylene, 26 mil, 300 ft./coil, BK | V | V | Medium |
| 2CXH2 | Hand Grade Polypropylene, 26 mil, 3,600 ft./coil, BK | V | V | Medium |
| 41P042 | Hand Grade Polypropylene, 26 mil, 6,000 ft./coil, BK | ✓ | V | Medium |
| 41P043 | Hand Grade Polypropylene, 26 mil, 7,000 ft./coil, BK | V | V | Medium |
| 2CXH3 | Hand Grade Polypropylene, 26 mil, 7,200 ft./coil, BK | V | V | Medium |
| 41P047 | Hand Grade Polypropylene, 26 mil, 7,200 ft./coil, BK | ✓ | V | Medium |
| 41P040 | Hand Grade Polypropylene, 26 mil, 7,200 ft./coil, 500lb., BK | V | V | Medium |
| 41P041 | Hand Grade Polypropylene, 26 mil, 7,200 ft./coil, 600lb., BK | ✓ | ✓ | Medium |
| 2CXH4 | Hand Grade Polypropylene, 30 mil, 3,600 ft./coil, BK | ✓ | ✓ | Medium |
| 41P062 | Hand Grade Polypropylene, 30 mil, 6,000 ft./coil, BK | V | V | Medium |
| 2CXH5 | Hand Grade Polypropylene, 30 mil, 7,200 ft./coil, BK | ✓ | ✓ | Medium |
| 41P048 | Hand Grade Polypropylene, 30 mil, 7,200 ft./coil, BK | ✓ | V | Medium |
| 16P049 | Hand Grade Polypropylene, 32 mil, 2,200 ft./coil, BK | ✓ | ✓ | Medium |
| 16P048 | Hand Grade Polypropylene, 32 mil, 3,500 ft./coil, BK | ✓ | ✓ | Medium |
| 41P038 | Hand Grade Polypropylene, 32 mil, 3,500 ft./coil,BK | ✓ | V | Medium |
| 41P051 | Hand Grade Polypropylene, 33 mil, 4,500 ft./coil, 8"W x 8"D, | BK ✔ | V | Medium |
| 41P050 | Hand Grade Polypropylene, 33 mil, 4,500 ft./coil,16"W x 6"D, I | BK 🗸 | ✓ | Medium |
| 41P049 | Hand Grade Polypropylene, 37 mil, 5,000 ft./coil, BK | V | V | Medium |







Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping



Polyester Hand Grade Strapping- for applications ranging from lightweight hand-applied strapping to heavy duty strapping for use with power tools.

| Grainger Item Number | Item Description | Environmentally Responsible | Safety Enhanced | Productivity Levels |
|-------------------------|--|-----------------------------|--------------------|------------------------|
| 9UDG4 | Hand Grade Polyester, 20 mil, 2,850 ft./coil, BK | ✓ | ✓ | High |
| 2CXK5 | Hand Grade Polyester, 20 mil, 3,600 ft./coil, BK | ~ | ✓ | High |
| 16P052 | Hand Grade Polyester, 25 mil, 4,400 ft./coil, BK | ~ | V | High |
| 2CXK8 | Hand Grade Polyester, 25 mil, 2,500 ft./coil, BK | ~ | ✓ | High |
| 41P036 | Hand Grade Polyester, 25 mil, 4,400 ft./coil, BK | ~ | ✓ | High |
| 2CXL1 | Hand Grade Polyester, 30 mil, 1,800 ft./coil, BK | ~ | V | High |
| 16P057 | Hand Grade Polyester, 40 mil, 4,200 ft./coil, BK | ~ | ✓ | High |
| 16P053 | Hand Grade Polyester, 25 mil, 4,400 ft./coil, GN | ~ | ✓ | High |
| 141P037 | Hand Grade Polyester, 25 mil, 4,400 ft./coil, GN | ~ | V | High |
| 41P087 | Hand Grade Polyester, 30 mil, 3,600 ft./coil, GN | ~ | V | High |
| 9NMC0 | Hand Grade Polyester, 30 mil, 3,600 ft./coil, GN | <i>V</i> | V | High |
| 16P054 | Hand Grade Polyester, 35 mil, 4,000 ft./coil, GN | V | V | High |
| 16P056 | Hand Grade Polyester, 40 mil, 4,200 ft./coil, GN | ~ | V | High |



41P089

Strapping with Bonded Finish- for inside or outside applications.

| Grainger Item Number | Item Description | Environmentally Responsible | Safety Enhanced | Productivity Levels |
|-------------------------|---|-----------------------------|--------------------|------------------------|
| 41P089 | Hand Grade Polyester, 20 mil, 7,200 ft./coil, BK | ✓ | ✓ | High |
| 41P092 | Hand Grade Polyester, 25 mil, 5,800 ft./coil, BK | ✓ | ✓ | High |
| 41P093 | Hand Grade Polyester, 30 mil, 3,600 ft./coil, BK | V | ✓ | High |
| 41P103 | Hand Grade Polyester, 35 mil, 4,000 ft./coil, BK | V | V | High |
| 41P105 | Hand Grade Polyester, 40 mil, 4,000 ft./coil, BK | V | V | High |
| 16P057 | Hand Grade Polyester, 40 mil, 4,200 ft./coil, BK | V | ✓ | High |
| 41P090 | Hand Grade Polyester, 20 mil, 7,200 ft./coil, GN | V | V | High |
| 41P091 | Hand Grade Polyester, 25 mil, 5,800 ft./coil, GN | V | V | High |
| 41P102 | Hand Grade Polyester, 35 mil, 4,000 ft./coil, GN | V | V | High |
| 41P104 | Hand Grade Polyester, 40 mil, 4,000 ft./coil, GN | V | V | High |
| 16P065 | Hand Grade Polyester Cord, 25 mil, 2,100 ft./coil, WT | V | V | High |
| 16P064 | Hand Grade Polyester Cord, 25 mil, 3,000 ft./coil, WT | V | V | High |
| 16P063 | Hand Grade Polyester Cord, 25 mil, 3,900 ft./coil, WT | V | V | High |
| 16P061 | Hand Grade Polyester Cord, 25 mil, 7,800 ft./coil, WT | V | V | High |
| 16P073 | Hand Grade Polyester, HD Cord, 48 mil, 1,960 ft./coil, WT | V | V | High |
| 16P074 | Hand Grade Polyester, HD Cord, 60 mil, 1,640 ft./coil, WT | ✓ | ✓ | High |



Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping



Polypropylene Machine Grade Strapping- for applications ranging from semi-automatic and automatic machine applications.

| Grainger Item Number | | Environmentally Responsible | Safety Enhanced | Productivity Levels |
|-------------------------|--|--------------------------------|--------------------|------------------------|
| 2CXK4 | Machine Grade Polypropylene, 20 mil, 7,200 ft./coil, BK | ✓ | ✓ | Medium |
| 8AVA5 | Machine Grade Polypropylene, 23 mil, 12,900 ft./coil, BK | V | ✓ | Medium |
| 2CXK7 | Machine Grade Polypropylene, 25 mil, 5,800 ft./coil, BK | V | V | Medium |
| 8NCR1 | Machine Grade Polypropylene, 28 mil, 6,600 ft./coil, BK | V | V | Medium |
| 2CXK9 | Machine Grade Polypropylene, 30 mil, 3,600 ft./coil, BK | V | V | Medium |
| 40TP66 | Machine Grade Polypropylene, 30 mil, 6,000 ft./coil, BK | V | V | Medium |
| 41P085 | Machine Grade Polypropylene, 30 mil, 6,000 ft./coil, BK | ✓ | ✓ | Medium |
| 6LGC9 | Machine Grade Polypropylene, 30 mil, 6,000 ft./coil, BK | V | ✓ | Medium |
| 8AUU9 | Machine Grade Polypropylene, 30 mil, 6,000 ft./coil, BK | ✓ | ✓ | Medium |
| 6LGD0 | Machine Grade Polypropylene, 33 mil, 6,000 ft./coil, BK | ✓ | ✓ | Medium |
| 41P086 | Machine Grade Polypropylene, 33 mil, 7,200 ft./coil, BK | V | ✓ | Medium |
| 36T406 | Machine Grade Polypropylene, (Pallet/28), BK | ✓ | ✓ | Medium |
| 41P083 | Machine Grade Polypropylene, 24 mil, 18,000 ft./coil, CLR | ✓ | ✓ | Medium |
| 6LGC7 | Machine Grade Polypropylene, 24 mil, 18,000 ft./coil, CLR | ✓ | ✓ | Medium |
| 2CXK3 | Machine Grade Polypropylene, 20 mil, 7,200 ft./coil, GN | ✓ | ✓ | Medium |
| 2CXK6 | Machine Grade Polypropylene, 25 mil, 5,800 ft./coil, GN | ✓ | ✓ | Medium |
| 40TP44 | Machine Grade Polypropylene, 21 mil, 12,900 ft./coil, WT | ✓ | ✓ | Medium |
| 2CXH8 | Machine Grade Polypropylene, 22 mil, 12,900 ft./coil, 8" x 8", \ | NT 🗸 | ✓ | Medium |
| 2CXH9 | Machine Grade Polypropylene, 22 mil, 12,900 ft./coil, 8" x 9", \ | NT 🗸 | ✓ | Medium |
| 41P063 | Machine Grade Polypropylene, 22 mil, 12,900 ft./coil, 8" x 8", \ | NT 🗸 | ✓ | Medium |
| 41P064 | Machine Grade Polypropylene, 22 mil, 12,900 ft./coil, 9" x 8", \ | NT 🗸 | ✓ | Medium |
| 41P065 | Machine Grade Polypropylene, 24 mil, 9,900 ft./coil, WT | ✓ | ✓ | Medium |
| 41P066 | Machine Grade Polypropylene, 24 mil, 9,900 ft./coil, WT | V | ✓ | Medium |
| 2CXJ1 | Machine Grade Polypropylene, 24 mil, 9,900 ft./coil, 8" x 8", W | /T 🗸 | ✓ | Medium |
| 2CXJ2 | Machine Grade Polypropylene, 24 mil, 9,900 ft./coil, 8" x 9", W | /T 🗸 | ✓ | Medium |
| 41P084 | Machine Grade Polypropylene, 24 mil, 18,000 ft./coil, WT | V | ✓ | Medium |
| 6LGC8 | Machine Grade Polypropylene, 24 mil, 18,000 ft./coil, WT | ✓ | ✓ | Medium |
| 2CXJ3 | Machine Grade Polypropylene, 28 mil, 7,200 ft./coil, WT | ✓ | ✓ | Medium |
| 41P067 | Machine Grade Polypropylene, 28 mil, 7,200 ft./coil, WT | ✓ | V | Medium |
| 8DV01 | Machine Grade Polypropylene, 9,000 ft./coil, 8"W, WT | V | V | Medium |



MACHINE GRADE POLYPROPYLENE - METRIC SIZES

Machine grad low elongation- available in skid quantities only. 36T403 5MM, 24,000ft./coil, 110lbs. break, 8x8, WT



Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

POLYPROPYLENE HAND AND MACHINE GRADE STRAPPING

Plastic strapping has consistently proven to reduce the amount of packaging at the source over alternative packaging methods. Source reduction means using less material to hold or package a product. This means less packaging to discard at the destination and less material to recycle. In addition, when you can apply plastic strapping with a machine or friction weld tool you further reduce the packaging by eliminating a mechanical seal. Plastic is also light and flexible, making it the safest alternative for many applications.



Polypropylene Machine Grade Strap- for machines and tools.

| Grainger Item Number | Item Description | Environmentally Responsible | Safety Enhanced | Productivity Levels |
|-------------------------|---|-----------------------------|--------------------|------------------------|
| 40TP49 | Machine Grade Polypropylene, 14 mil, 12,000 ft./coil, BK | ✓ | ✓ | Medium |
| 6LGC1 | Machine Grade Polypropylene, 14 mil, 16,000 ft./coil, BK | ✓ | V | Medium |
| 33RZ02 | Machine Grade Polypropylene, 16 mil, 12,000 ft./coil, BK | ✓ | V | Medium |
| 41P076 | Machine Grade Polypropylene, 16 mil, 12,000 ft./plt., BK | ✓ | V | Medium |
| 41P077 | Machine Grade Polypropylene, 16 mil, 16,000 ft./plt.,BK | V | V | Medium |
| 6LGC0 | Machine Grade Polypropylene, 16 mil, 12,000 ft./coil, BK | V | V | Medium |
| 2CXJ5 | Machine Grade Polypropylene, 20 mil, 10,500 ft./coil, BK | ✓ | V | Medium |
| 41P069 | Machine Grade Polypropylene, 20 mil, 10,500 ft./plt., BK | V | V | Medium |
| 33RZ21 | Machine Grade Polypropylene, 22 mil, 8,000 ft./coil, BK | V | V | Medium |
| 41P073 | Machine Grade Polypropylene, 22 mil, 8,000 ft./plt., BK | V | V | Medium |
| 2CXJ8 | Machine Grade Polypropylene, 23 mil, 5,000 ft./coil, BK | V | V | Medium |
| 2CXK1 | Machine Grade Polypropylene, 23 mil, 7,500 ft./coil, BK | V | V | Medium |
| 41P072 | Machine Grade Polypropylene, 23 mil, 9,000 ft./plt., BK | V | V | Medium |
| 41P074 | Machine Grade Polypropylene, 23 mil, 7,500 ft./plt., BK | V | V | Medium |
| 41P111 | Machine Grade Polypropylene, 23 mil, 7,700 ft./plt., BK | V | V | Medium |
| 2CXJ6 | Machine Grade Polypropylene, 25 mil, 8,000 ft./coil, BK | V | V | Medium |
| 41P070 | Machine Grade Polypropylene, 25 mil, 8,000 ft./plt., BK | V | V | Medium |
| 33RZ03 | Machine Grade Polypropylene, 26 mil, 7,000 ft./coil, BK | ✓ | V | Medium |
| 41P043 | Machine Grade Polypropylene, 26 mil, 7,000 ft./plt, BK | ✓ | ✓ | Medium |
| 2CXJ7 | Machine Grade Polypropylene, 30 mil, 7,000 ft./coil, BK | ✓ | ✓ | Medium |
| 41P071 | Machine Grade Polypropylene, 30 mil, 7,000 ft./plt., BK | ✓ | V | Medium |
| 40TP47 | Machine Grade Polypropylene, 13 mil, 30,000 ft./coil, CLR | ✓ | ✓ | Medium |
| 6LGC2 | Machine Grade Polypropylene, 14 mil, 16,000 ft./coil, CLR | ✓ | ✓ | Medium |
| 40TP68 | Machine Grade Polypropylene, 14 mil, 25,000 ft./coil, CLR | ✓ | ✓ | Medium |
| 2CXK2 | Machine Grade Polypropylene, 16 mil, 12,000 ft./coil, CLR | ✓ | ✓ | Medium |
| 41P075 | Machine Grade Polypropylene, 16 mil, 12,000 ft./plt., CLR | ✓ | ✓ | Medium |
| 41P078 | Machine Grade Polypropylene, 16 mil, 16,000 ft./plt., CLR | ✓ | ✓ | Medium |
| 2CXJ4 | Machine Grade Polypropylene, 16 mil, 18,000 ft./coil, CLR | ✓ | ✓ | Medium |
| 41P068 | Machine Grade Polypropylene, 16 mil, 18,000 ft./plt., CLR | ✓ | ✓ | Medium |
| 6LGC3 | Machine Grade Polypropylene, 19 mil, 12,000 ft./coil, CLR | V | V | Medium |
| 41P079 | Machine Grade Polypropylene, 19 mil, 12,000 ft./plt., CLR | ✓ | V | Medium |
| 6LGC5 | Machine Grade Polypropylene, 23 mil, 7,500 ft./coil, CLR | V | V | Medium |
| 41P081 | Machine Grade Polypropylene, 23 mil, 7,500 ft./plt., CLR | ✓ | ✓ | Medium |
| 6LGC6 | Machine Grade Polypropylene, 23 mil, 9,000 ft./coil, CLR | ✓ | ✓ | Medium |
| 41P082 | Machine Grade Polypropylene, 23 mil, 9,000 ft./plt., CLR | ✓ | ✓ | Medium |



Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

POLYESTER CORD STRAPPING SOLUTIONS

Polyester Cord is available in a range of sizes and types to handle your toughest cord applications. In addition to standard bonded products, can supply you with woven material in both regular duty and heavy duty, along with a broad range of composite polyester cord strapping.

Polyester Cord Strapping- for regular duty standard applications.

| Grainger Item Number | Item Description | Environmentally Responsible | Safety Enhanced | Productivity Levels |
|-------------------------|--|-----------------------------|--------------------|------------------------|
| 16P055 | 5/8" Strap Width, Polyester, 35 mil, 4,000 ft./coil, BK | ✓ | ✓ | High |
| 36T405 | 5/8" Strap Width, Polyester, 25 mil, 4,200 ft., 28/pkg., BK | V | V | High |
| 40TP59 | 3/8" Strap Width, Polyester, 20 mil, 9,600 ft./coil, GN | V | V | High |
| 40TP45 | 3/8" Strap Width, Polyester, 20 mil, 12,500 ft./coil, GN | V | ✓ | High |
| 41P034 | 1/2" Strap Width, Polyester, 21 mil, 9,000 ft., 28/pkg., GN | ✓ | ✓ | High |
| 33RZ08 | 1/2" Strap Width, Polyester, 28 mil, 300 ft./coil, GN | ✓ | ✓ | High |
| 33RZ01 | 1/2" Strap Width, Polyester, 28 mil, 6,500 ft./coil, GN | ✓ | ✓ | High |
| 41P035 | 1/2" Strap Width, Polyester, 28 mil, 6,500 ft., 28/pkg., GN | ✓ | ✓ | High |
| 41P055 | 3/8" Strap Width, Polyester, 19 mil, 5,250 ft./coil, WT | ✓ | V | High |
| 41P061 | 3/4" Strap Width, Polyester, 21 mil, 2,100 ft./coil, WT | ✓ | V | High |
| 41P059 | 5/8" Strap Width, Polyester, 25 mil, 3,000 ft./coil, WT | ✓ | ✓ | High |
| 41P057 | 1/2" Strap Width, Polyester, 44 mil, 3,900 ft./coil, WT | ✓ | ✓ | High |
| Polyester Cord | d Strapping- for regular duty woven applications. | | | |
| 40TP73 | 1/4" Polyester Crosswoven, 7.27 mil, 7,800 ft./coil, WT | ✓ | ✓ | High |
| 16P067 | 1/2" Polyester Crosswoven, 25 mil, 1,500 ft./coil, WT | ✓ | ✓ | High |
| 16P070 | 3/4" Polyester Crosswoven, 25 mil, 2,100 ft./coil, WT | ✓ | ✓ | High |
| 16P069 | 5/8" Polyester Crosswoven, 25 mil, 3,000 ft./coil, WT | ✓ | ✓ | High |
| 16P068 | 1/2" Polyester Crosswoven, 25 mil, 3,900 ft./coil, WT | ✓ | <i>V</i> | High |
| 16P062 | 3/8" Polyester Crosswoven Bonded, 25 mil, 5,250 ft./coil, WT | · / | <i>V</i> | High |
| 16P066 | 3/8" Polyester Crosswoven, 25 mil, 5,250 ft./coil, WT | ✓ | <i>V</i> | High |
| 41P054 | 3/8" Polyester Crosswoven, 45 mil, 5,250 ft./plt., WT | ✓ | <i>V</i> | High |
| 41P060 | 3/4" Polyester Crosswoven, 50 mil, 2,100 ft./plt., WT | ✓ | <i>V</i> | High |
| 41P058 | 5/8" Polyester Crosswoven, 50 mil, 3,000 ft./plt., WT | ✓ | <i>V</i> | High |
| 41P056 | 1/2" Polyester Crosswoven, 50 mil, 3,900 ft./plt., WT | ✓ | ~ | High |
| Polyester Cord | d Strapping- for heavy duty woven applications. | | | |
| 16P072 | 1-1/4" HD Woven Polyester Cord, 26 mil, 600 ft./coil, NAT | ✓ | ✓ | High |
| 52CC65 | 3/4" HD Woven Polyester Cord, 25 mil, 1,320 ft./coil, WT | ✓ | ✓ | High |
| 2CXP8 | 3/4" HD Woven Polyester Cord, 30 mil, 1,320 ft./coil, WT | ✓ | <i>V</i> | High |
| 2CXP9 | 1-1/4" HD Woven Polyester Cord, 38 mil, 330 ft./coil, WT | ✓ | V | High |
| 16P071 | 3/4" HD Woven Polyester Cord, 50 mil, 250 ft./coil, WT | ✓ | <i>V</i> | High |
| 41P052 | 1-1/4" HD Woven Polyester Cord, 52 mil, 600 ft./plt., WT | ✓ | V | High |
| 41P053 | 3/4" HD Woven Polyester Cord, 60 mil, 1,320 ft./plt., WT | • | ✓ | High |
| Polyester Grad | de Strap- for machines and tools. | | | |
| 33RZ07 | Multi Grade Polyester, 20 mil, 300 ft./coil, GN | ✓ | ✓ | High |
| 33RZ18 | Multi Grade Polyester, 20 mil, 11,550 ft./coil, GN | V | ✓ | High |
| 9UDG5 | Multi Grade Polyester, 21 mil, 10,500 ft./coil, GN | ✓ | ✓ | High |
| 41P032 | Multi Grade Polyester, 21 mil, 10,500 ft./plt., GN | V | ✓ | High |
| 8VU81 | Multi Grade Polyester, 24 mil, 9,000 ft./coil, GN | V | ✓ | High |
| 41P033 | Multi Grade Polyester, 24 mil, 9,000 ft./plt., GN | ✓ | ✓ | High |
| 6LGA7 | Multi Grade Polyester, 28 mil, 300 ft./coil, GN | V | ✓ | High |
| 6LGA9 | Multi Grade Polyester, 30 mil, 300 ft./coil, GN | ✓ | ✓ | High |



High

PLASTIC STRAPPING SOLUTIONS

Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

Multi Grade Embossed Polyester, 40 mil, 4,000 ft., 28/pkg., GN

Polyester Strapping- for most friction weld applications.

5JPR5

| Item Number | Item Description | Environmentally Responsible | Safety Enhanced | Productivity Levels |
|--|--|--|--------------------|--|
| 41P113 | Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., BK | ✓ | ✓ | High |
| 3HJZ5 | Waxed Polyester, 40 mil, 3,000 ft./coil, BK | V | V | High |
| 41P108 | Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., BK | V | V | High |
| 419109 | Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., BK | V | V | High |
| 41P115 | Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., BK | ✓ | ✓ | High |
| 40TP78 | Waxed Polyester, 50 mil, 1,800 ft.,/coil, BK | ✓ | ✓ | High |
| 33RZ20 | Waxed Polyester, 18 mil, 10,500 ft./coil, GN | ✓ | ✓ | High |
| 16P050 | Waxed Polyester, 21 mil, 9,000 ft./coil, GN | ✓ | ✓ | High |
| 41P034 | Waxed Polyester, 21 mil, 9,000 ft., 28/pkg., GN | ✓ | ✓ | High |
| 41P035 | Waxed Polyester, 28 mil, 6,500 ft., 28/pkg., GN | ✓ | ✓ | High |
| 33RZ09 | Waxed Polyester, 35 mil, 300 ft., 28/pkg., GN | ✓ | ✓ | High |
| CXL2 | Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN | V | ✓ | High |
| 3RZ12 | Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN | ✓ | ✓ | High |
| 3RZ13 | Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN | ✓ | ✓ | High |
| 1P097 | Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN | ✓ | ✓ | High |
| 1P112 | Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN | V | V | High |
| 1P110 | Waxed Polyester, 40 mil, 2,200 ft., 28/pkg., GN | V | V | High |
| 0TP74 | Waxed Polyester, 40 mil, 4,000 ft.,/coil, GN | ✓ | ✓ | High |
| 1P114 | Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN | V | ✓ | High |
| 3RZ10 | Waxed Polyester, 50 mil, 200 ft., 28/pkg., GN | ✓ | ✓ | High |
| 0TP62 | Waxed Polyester, 50 mil, 1,800 ft./coil, GN | V | V | High |
| 6P060 | Waxed Polyester, 50 mil, 2,200 ft., 28/pkg., GN | V | V | High |
| 33RZ04 | Waxed Polyester, 50 mil, 2,400 ft., 28/pkg., GN | V | V | High |
| 11P106 | Waxed Polyester, 50 mil, 2,400 ft., 28/pkg., GN | V | V | High |
| | | | | |
| assure the stra | ter Strapping- polyester strapping is made using the high p meets the rigid specifications required by the American ed with an AAR approval number to designate the quality | Association of Railroa | | |
| ssure the stra straps are print | p meets the rigid specifications required by the American | Association of Railroa of the strapping. | | High |
| ssure the stra traps are print 6T408 | p meets the rigid specifications required by the American ed with an AAR approval number to designate the quality | Association of Railroa of the strapping. K ✓ | ids. These | High High |
| ssure the stra traps are print 6T408 3RZ19 | p meets the rigid specifications required by the American ed with an AAR approval number to designate the quality AAR Approved Waxed Polyester, 40 mil, 11,000 ft., 28/pkg., B | Association of Railroa of the strapping. K V | ds. These ✓ | |
| ssure the stra traps are print 6T408 3RZ19 1P096 | p meets the rigid specifications required by the American ed with an AAR approval number to designate the quality AAR Approved Waxed Polyester, 40 mil, 11,000 ft., 28/pkg., B AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN | Association of Railroa of the strapping. K V N V | nds. These | High |
| ssure the stra traps are print 6T408 3RZ19 1P096 1P094 | p meets the rigid specifications required by the American ed with an AAR approval number to designate the quality AAR Approved Waxed Polyester, 40 mil, 11,000 ft., 28/pkg., B AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN | Association of Railroa of the strapping. K V N V | nds. These | High High |
| assure the stra straps are print 67408 38Z19 1P096 1P094 JPR2 | p meets the rigid specifications required by the American ed with an AAR approval number to designate the quality AAR Approved Waxed Polyester, 40 mil, 11,000 ft., 28/pkg., B AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN | Association of Railroa of the strapping. K V N V N V | ds. These | High High High |
| assure the stra | p meets the rigid specifications required by the American ed with an AAR approval number to designate the quality AAR Approved Waxed Polyester, 40 mil, 11,000 ft., 28/pkg., B AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN | Association of Railroa of the strapping. K V V V V V V V V V V V V | ds. These | High High High High |
| assure the stra straps are print 66T408 63RZ19 61P096 61P094 6JPR2 61P099 6JPR1 | p meets the rigid specifications required by the American ed with an AAR approval number to designate the quality AAR Approved Waxed Polyester, 40 mil, 11,000 ft., 28/pkg., B AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN | Association of Railroa of the strapping. K V V V V V V V V V V V V | ds. These | High High High High High |
| assure the stra straps are print 36T408 33RZ19 11P096 11P094 5JPR2 11P099 | p meets the rigid specifications required by the American ed with an AAR approval number to designate the quality AAR Approved Waxed Polyester, 40 mil, 11,000 ft., 28/pkg., B AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN | Association of Railroa of the strapping. K V V V V V V V V V V V V | ds. These | High High High High High High |
| assure the stra atraps are print 667408 63RZ19 61P096 61P094 6JPR2 61P099 6JPR1 61P107 60TP62 | p meets the rigid specifications required by the American ed with an AAR approval number to designate the quality AAR Approved Waxed Polyester, 40 mil, 11,000 ft., 28/pkg., B AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 2,400 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 2,400 ft., 28/pkg., GN | Association of Railroa of the strapping. K V V V V V V V V V V V V | ds. These | High High High High High High High |
| assure the stra atraps are print 667408 63RZ19 61P096 61P094 6JPR2 61P099 6JPR1 61P107 60TP62 | p meets the rigid specifications required by the American ed with an AAR approval number to designate the quality AAR Approved Waxed Polyester, 40 mil, 11,000 ft., 28/pkg., B AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 2,400 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 3,000 ft., 28/pkg., GN | Association of Railroa of the strapping. K V N V N V N V N V N V N V N V N V N | ds. These | High High High High High High High |
| ssure the stra traps are print 6T408 3RZ19 1P096 1P094 JPR2 1P099 JPR1 1P107 0TP62 Embossed Po | p meets the rigid specifications required by the American ed with an AAR approval number to designate the quality AAR Approved Waxed Polyester, 40 mil, 11,000 ft., 28/pkg., B AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 2,400 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 2,400 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 3,000 ft., 3,000 ft., 3,000 ft., 3,000 ft., 3,000 ft., 3,000 ft. | Association of Railroa of the strapping. K V V V V V V V V V V V V V V V V V V | nds. These | High High High High High High High |
| ssure the stra traps are print 6T408 3RZ19 1P096 1P094 JPR2 1P099 JPR1 1P107 0TP62 Embossed Po 1P088 JPR3 | p meets the rigid specifications required by the American ed with an AAR approval number to designate the quality AAR Approved Waxed Polyester, 40 mil, 11,000 ft., 28/pkg., B AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 2,400 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,400 ft., 28/pkg., GN ARR Approved Waxed Polyester, 50 mil, 4,4 | Association of Railroa of the strapping. K V N V N V N V N V N V N V N V N V N | nds. These | High High High High High High High High |
| ssure the stra traps are print 6T408 3RZ19 1P096 1P094 JPR2 1P099 JPR1 1P107 0TP62 Embossed Po 1P088 JPR3 1P095 | p meets the rigid specifications required by the American ed with an AAR approval number to designate the quality AAR Approved Waxed Polyester, 40 mil, 11,000 ft., 28/pkg., B AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 2,400 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN AR Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN AR Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN AR Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN AR Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN AR Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN AR Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN AR Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN AR Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg., GN Approved Waxed Polyester, 25 mil, 4,400 ft., 28/pkg. | Association of Railroa of the strapping. K V N N | ds. These | High High High High High High High High |
| assure the stra atraps are print 66T408 33RZ19 11P096 11P094 5JPR2 11P099 5JPR1 11P107 10TP62 | p meets the rigid specifications required by the American ed with an AAR approval number to designate the quality AAR Approved Waxed Polyester, 40 mil, 11,000 ft., 28/pkg., B AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 2,400 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 3,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 25 mil, 4,400 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN M | Association of Railroa of the strapping. K V N V | ds. These | High High High High High High High High |
| assure the stra atraps are print 167408 137219 117096 117094 117099 117099 11707 11707 11707 11707 11708 117088 117088 117095 117095 117095 | p meets the rigid specifications required by the American ed with an AAR approval number to designate the quality AAR Approved Waxed Polyester, 40 mil, 11,000 ft., 28/pkg., B AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 2,400 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 3,000 ft., 28/pkg., GN AAR Approved Waxed Polyester, 50 mil, 3,000 ft., 28/pkg., GN Multi Grade Embossed Polyester, 25 mil, 4,400 ft., 28/pkg., GN Multi Grade Embossed Polyester, 25 mil, 7,200 ft., 28/pkg., GN Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN | Association of Railroa of the strapping. K V N V | ds. These | High High High High High High High High |



Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

STOCK STEEL STRAPPING

Steel strapping is consistent in width, gauge, and finish. Published break strengths are average and meet or exceed industry standards.

Regular Duty Steel Strapping

Regular duty steel strapping is manufactured from cold rolled steel. All regular duty steel can be used in manual and pneumatic tools, as well as automatic steel strapping heads.

High Tensile Steel Strapping

High tensile steel strapping is manufactured from cold rolled steel and heat treated to maximize break strength and ductility. High tensile steel provides additional break strength and shock resistance for your toughest applications.



Oscillated Wound- for regular duty steel applications.

| Grainger Item Number | | Environmentally Responsible | Safety Enhanced | Productivity Levels |
|-------------------------|---|--------------------------------|--------------------|------------------------|
| 52YU46 | 1/2" Stock Steel, Oscillated Wound, 17 mil, 5,300 ft./coil, BK | ✓ | ✓ | High |
| 52YU49 | 3/4" Stock Steel, Oscillated Wound, 17 mil, 5,300 ft./coil, BK | V | ✓ | High |
| 52YU51 | 5/8" Stock Steel, Oscillated Wound, 17 mil, 5,300 ft./coil, BK | V | V | High |
| 3CTU2 | 1/2" Stock Steel, Oscillated Wound, 20 mil, 2,942 ft./coil, BK | ✓ | ✓ | High |
| 3CTU3 | 5/8" Stock Steel, Oscillated Wound, 20 mil, 2,353 ft./coil, BK | ✓ | ✓ | High |
| 3CTU4 | 3/4" Stock Steel, Oscillated Wound, 20 mil, 1,961 ft./coil, BK | V | V | High |
| 32TL79 | 3/4" Stock Steel, Oscillated Wound, 20 mil, 1,961 ft., 12/plt., E | K 🗸 | ✓ | High |
| 32TL77 | 5/8" Stock Steel, Oscillated Wound, 20 mil, 2,353 ft., 12/plt., E | BK ✓ | ✓ | High |
| 32TL75 | 1/2" Stock Steel, Oscillated Wound, 20 mil, 2,942 ft., 12/plt., E | BK ✓ | ✓ | High |
| 6LGD4 | 3/4" Stock Steel, Oscillated Wound, 23 mil, 1,705 ft./coil, BK | ✓ | ✓ | High |
| 16P035 | 3/4" Stock Steel, Oscillated Wound, 23 mil, 1,705 ft./coil, BK | ✓ | ✓ | High |
| 32TL80 | 3/4" Stock Steel, Oscillated Wound, 23 mil, 1,705 ft., 12/plt., B | K 🗸 | ✓ | High |
| 16P034 | 5/8" Stock Steel, Oscillated Wound, 23 mil, 2,046 ft./coil, BK | ✓ | V | High |
| 32TL78 | 5/8" Stock Steel, Oscillated Wound, 23 mil, 2,046 ft., 12/plt., E | BK ✓ | ✓ | High |
| 16P033 | 1/2" Stock Steel, Oscillated Wound, 23 mil, 2,558 ft./coil, BK | ✓ | ✓ | High |
| 32TL76 | 1/2" Stock Steel, Oscillated Wound, 23 mil, 2,558 ft., 12/plt., E | BK 🗸 | V | High |



Ribbon Wound, High Tensile Steel- Ribbon wound strapping is wound onto itself to form a coil that is the same width as the strapping. Individual coil weight will vary with strapping width.

Ribbon Wound- for general packaging, palletizing and unitizing.

3CTU7 1-1/4" Stk Steel, Ribbon Wnd, Hi-Tensile, 29 mil, 811 ft./coil, BK

V

High



Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

SEALS FOR STEEL STRAPPING

Steel Strapping seals are made from precision tested galvanized steel. Engineered for high joint efficiency with regular duty and heavy duty steel, all seal meet federal government standards, along with ASTM Standard D3953.

Open Seals- for regular duty applications.

| Grainger Item Number | Item Description | Environmentally Responsible | Safety Enhanced | Productivity Levels |
|-------------------------|---|--------------------------------|--------------------|------------------------|
| 6LGD5 | 3/8", 20 mil, 1-1/4" L, Open Strapping Seal, Galvanized, 10 | 00/pkg. ✓ | ✓ | High |
| 3CTV4 | 1/2", 20 mil, 1-1/8" L, Open Strapping Seal, Galvanized, 20 | 0/pkg. ✓ | ✓ | Medium |
| 36T380 | 1/2", 20 mil, 1-1/4" L, Open Strapping Seal, Galvanized, 20 | 0/pkg. ✓ | V | Medium |
| 8E297 | 1/2", 20 mil, 1-1/4" L, Open Strapping Seal, Galvanized, 10 | 00/pkg. ✓ | V | High |
| 3CTV5 | 5/8", 20 mil, 1-1/4" L, Open Strapping Seal, Galvanized, 20 | 0/pkg. ✓ | V | Medium |
| 52YU57 | 5/8", 20 mil, 1-1/4" L, Open Strapping Seal, Galvanized, 20 | 0/pkg. ✓ | ~ | Medium |
| 3CTV6 | 3/4", 20 mil, 1-1/4" L, Open Strapping Seal, Galvanized, 20 | 0/pkg. ✓ | V | Medium |
| 9GDN4 | 3/4", 20 mil, 1-1/4" L, Open Strapping Seal, Galvanized, 10 | 00/pkg. ✓ | ✓ | High |
| Open Seals- fo | r heavy duty applications. | | | |
| 3CTV7 | 3/4", 1-3/4" L, Open Seal, 500/pkg. | ✓ | ✓ | Medium |
| 3CTV8 | 1-1/4", 2-1/4" L, Open Seal, 500/pkg. | V | ✓ | Medium |
| | (Push Type)- for use with round bundles, and with pushlications. These seals must be threaded prior to applic 3/8", Crimp Strapping Seal, Galvanized, 2500/pkg. | | V | High |
| 52YU62 | 3/8", 1" L, Push Strapping Seal, Galvanized, 5000/pkg. | | | High |
| 3CTV9 | 1/2", 7/8" L, Push Strapping Seal, 200/pkg. | <u> </u> | | Medium |
| 52YU63 | 1/2", 1" L, Push Strapping Seal, Galvanized, 2500/pkg. | | | High |
| 3CTW1 | 5/8", 7/8" L. Push Strapping Seal, 200/pkg. | | | 1 11911 |
| Medium | or or, more extrapping odds, 200, phg. | · | · | |
| 52YU64 | 5/8", 1" L, Push Strapping Seal, Galvanized, 5000/pkg. | V | ✓ | High |
| 3CTW2 | 3/4", 7/8" L, Push Strapping Seal, 200/pkg. | V | V | Medium |
| 52YU65 | 3/4", 1" L, Push Strapping Seal, Galvanized, 2500/pkg. | ✓ | V | High |
| Overlap Seals | (Push Type)- for heavy-duty applications. | | | |
| 3CTW3 | 3/4", 1-3/4" L, Push Strapping Seal, 500/pkg. | ✓ | ✓ | Medium |
| 3CTW4 | 1-1/4", 2-1/4" L, Push Strapping Seal, 500/pkg. | ✓ | ✓ | Medium |

SEALS FOR PLASTIC STRAPPING

Seals are manufactured from the finest raw materials under carefully controlled conditions. They are known throughout the industry for quality, consistency, and reliability. All standard open and closed seals are made to ASTM Standard D3950.

| 36T384 | 3/8", Open Strapping Seal, 2500/pkg. | ✓ | ✓ | High |
|--------|--------------------------------------|----------|----------|--------|
| 2CXP3 | 1/2", Open Strapping Seal, 1000/pkg. | V | ✓ | High |
| 2CXP4 | 5/8", Open Strapping Seal, 1000/pkg. | V | V | High |
| 16P030 | 3/4", Open Strapping Seal, 250/pkg. | V | V | Medium |

SEALS FOR COMBINATION TOOLS

For use in specific tools. When ordering, please specify tool or comparable competitive seals. In addition to the stock sizes listed below, we carry a full line of seals for competitor's tools.

Serrated Strapping Seals- the most common plastic seal, open seals allow you to place the seal on after tensioning has occurred.

| 2CXP5 | 1/2", Serrated Strapping Seal, 1000/pkg. | <i>V</i> | ✓ | High |
|--------|--|----------|----------|--------|
| 2CXP6 | 5/8", Serrated Strapping Seal, 1000/pkg. | ✓ | ✓ | High |
| 16P031 | 3/4", Serrated Strapping Seal, 250/pkg. | ✓ | V | Medium |
| 40TP76 | 3/4", Serrated Strapping Seal, 1000/pkg. | V | V | High |
| | | | | |



Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

BUCKLES

Designed for light duty applications where corrosion resistance and/or non-scratch product is important, offering a range of plastic buckles to fit your demanding applications. For superior holding power and convenience, the patented "Bucklelok" design "locks" each leg into postion to allow for pre-threading.



Plastic Buckles- for regular duty applications.

| Grainger Item Number | Item Description | Environmentally Responsible | Safety Enhanced | Productivity Levels |
|-------------------------|--|-----------------------------|--------------------|------------------------|
| 16P029 | 1/2" to 5/8" Plastic Buckle, 250/pkg. | ✓ | ✓ | Medium |
| Strapping with | Plastic Buckles- for regular duty applications. | | | |
| 43NE44 | 1/2" x 15' Plastic Strapping, Plastic Buckle, WT., 17ft., 500/ | pkg. 🗸 | ✓ | Medium |
| 16P026 | 1/2" x 17' Plastic Strapping, Plastic Buckle, WT., 17ft., 25/p | kg. 🗸 | V | Medium |
| 43NE45 | 1/2" x 17' Plastic Strapping, Plastic Buckle, WT., 17ft., 500/ | pkg. 🗸 | V | Medium |
| 43NE46 | 1/2" x 22' Plastic Strapping, Plastic Buckle, WT., 17ft., 250/ | pkg. 🗸 | V | Medium |
| 43NE47 | 1/2" x 25' Plastic Strapping, Plastic Buckle, WT., 17ft., 250/ | pkg. 🗸 | V | Medium |

Wire Buckles- for use with polypropylene, polyester strapping, and polyester cord strapping. No hand tools required.



160007

| oora orrapp | mig. No hana toolo roquirou. | | | |
|-------------|---|----------|----------|--------|
| 2JFF2 | 3/8" Metal Strapping Buckle, 1000/pkg. | ✓ | ✓ | High |
| 2CXP1 | 1/2" Metal Strapping Buckle, 1000/pkg. | V | V | High |
| 2CXP2 | 1/2" Heavy Duty Metal Strapping Buckle, 1000/pkg. | V | V | High |
| 16P027 | 5/8" Metal Strapping Buckle, 250/pkg. | ✓ | ✓ | Medium |
| 16P028 | 3/4" Metal Strapping Buckle, 250/pkg. | V | ✓ | Medium |

Strapping with Wire Buckles- for regular duty applications.

16P025 1/2" x 17' Plastic Strapping, Plastic Buckle, BK., 17ft., 25/pkg.

Phosphate Heavy Duty Buckles- for use with polyester cord and rayon cord heavy duty applications. The phosphate coating affords some additional protection against corrosion, and also significantly improves joint efficiency when properly applied.



| 2CXR1 | 3/4" Strapping Buckle, 1000/pkg. | 4 | 4 | High |
|-------|------------------------------------|---|---|------|
| 2CXR2 | 1-1/4" Strapping Buckle, 1000/pkg. | 4 | 4 | Hiah |

EDGE PROTECTORS

For use with both steel and plastic strapping, corners cushion your product and allow the strap to be tightened to its maximum tension without damaging the package. Each plastic corner is constructed from a specially formulated resin and is ribbed to hold the strapping firmly in place. Steel corners meet all Federal and GSA specifications.

| 2CXP7 | 1-3/8"W, 1"L, Plastic, 2000/pkg., Max. 3/4" Strap, WT | ✓ | ✓ | High |
|---------|--|----------|----------|--------|
| 5JPP6 | 2"W, 24"L, Polyethelyene, Max. 1/8" Strap, 50/pkg., BK | ✓ | ✓ | Medium |
| 5JPP7 | 2"W, 34"L, Polyethelyene, Max 1/8" Strap, 50/pkg., BK | ✓ | ✓ | Medium |
| 5JPP8 | 2"W, 42"L, Polyethelyene, Max 1/8" Strap, 50/pkg., BK | ✓ | ✓ | Medium |
| 4FET8 | 2-1/2"W, 1-3/4"L, Plastic, 1000/pkg. Max. 1-1/4" Strap, BK | V | ✓ | High |
| 4FET7 | 2-1/2"W, 2"L, Plastic, 1000/pkg. Max. 1-1/4" Strap, WT | V | ✓ | High |
| 4FEU2 | 2-1/2"W, 6"L, Plastic, 500/pkg. Max. 2" Strap, WT | ✓ | ✓ | Medium |
| 4FEU3** | 3"W, 2"L, Steel, 500/pkg. Max. 1-1/4" Strap | V | ✓ | Medium |
| 4FET9* | 5-1/4"W, 2"L, Plastic, 200/pkg. Max. 1-1/4" Strap, BK | V | ✓ | Medium |
| 4FEU1 | 5-1/4"W. 2"L, Plastic, 250/pkg, Max, 1-1/4" Strap, BK | V | V | Medium |

^{*} Corners have four inside points which penetrate the outside layer of your carton to hold the corner in place

^{**}Steel corner protector



Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

STRAPPING KITS

The strapping kits offers wholesalers of both plastic and steel strapping an excellent opportunity to increase sales and profits by efficiently servicing those markets that need a complete strapping set up. With the family of kits, there is no need to inventory separate components, do any packaging, or send a sales rep out to do a demo. These kits are available in both steel and plastic, and come in several sizes and varieties for a wide range of applications.



2CXL5

Replacement Kit- Kits for first time user and multi-location buyers that include everything in one kit.

| Grainger Item Number | Item Environmer Description Responsible | | Safety Enhanced | Productivit Levels |
|--|--|---------------------------------------|--------------------|--|
| 16P047 | 7200ft. 1/2", 500lb., strap, 500 Seals | 4 | 4 | High |
| 2CXL4 | 7200ft. 1/2" HD strap, 1000 1/2" open seals, HD tensioner, sealer | 4 | 4 | High |
| 16P044 | 9000ft. 1/2" 4 Lt. duty strap, 1000 1/2" open seals, tensioner & sealer | 4 | 4 | High |
| 16P046 | 9000ft. 1/2", 300lb., strap, 500 Seals | 4 | 4 | High |
| 16P045 | 9000ft. 1/2", 400lb., strap, 1000 wire buckles, hand pull tensioner | 4 | 4 | High |
| ALL PAC- Kits | for the customer who wants a premium strapping system. | | | |
| 2CXL5 | 3600ft. 1/2", 500lb.,1 coil HD strap, 500 seals, tensioner, sealer, dispenser | 4 | 4 | High |
| 2CXL6 | 5800ft. 1/2", 775lb., HD strap, 500 seals, tensioner, sealer, dispenser | 4 | 4 | High |
| -0/1-0 | | | | 112.1 |
| 2CXL7 | 4000ft. 5/8", 1400lb., strap, 500 seals, tensioner, sealer, dispenser | 4 | 4 | High |
| 2CXL7 Portable Steel | l Kits- Kits for flat loads. | | | Š |
| 2CXL7 Portable Steel 2CXL3 | Kits- Kits for flat loads. 3000ft. 1/2", 18mil strap, tensioner, 300 buckles, carton dispenser | 4 | | High High Medium |
| Portable Steel 2CXL3 3CTW8 | l Kits- Kits for flat loads. | V | V | High |
| Portable Steel 2CXL3 3CTW8 6LGE0 | Kits- Kits for flat loads. 3000ft. 1/2", 18mil strap, tensioner, 300 buckles, carton dispenser 400ft. 1/2", 20mil strap, tensioner, sealer, cutter, seals, tool box | <i>V</i> | V | High Medium |
| 2CXL7 | I Kits- Kits for flat loads. 3000ft. 1/2", 18mil strap, tensioner, 300 buckles, carton dispenser 400ft. 1/2", 20mil strap, tensioner, sealer, cutter, seals, tool box 400ft. 5/8", 20mil strap, tensioner, sealer, seal dispenser, cutting tool | <i>V V</i> | <i>V V</i> | High Medium Medium |
| Portable Steel 2CXL3 3CTW8 6LGE0 8UZ35 3CTW9 | I Kits- Kits for flat loads. 3000ft. 1/2", 18mil strap, tensioner, 300 buckles, carton dispenser 400ft. 1/2", 20mil strap, tensioner, sealer, cutter, seals, tool box 400ft. 5/8", 20mil strap, tensioner, sealer, seal dispenser, cutting tool 3000ft. 5/8", 20mil strap, 300 buckles, 1 hand pull tensioner | <i>V V V V</i> | У У У | High Medium Medium Medium |
| Portable Steel 2CXL3 3CTW8 6LGE0 BUZ35 3CTW9 Jumbo Steel Kall packaged in | I Kits- Kits for flat loads. 3000ft. 1/2", 18mil strap, tensioner, 300 buckles, carton dispenser 400ft. 1/2", 20mil strap, tensioner, sealer, cutter, seals, tool box 400ft. 5/8", 20mil strap, tensioner, sealer, seal dispenser, cutting tool 3000ft. 5/8", 20mil strap, 300 buckles, 1 hand pull tensioner 400ft. 3/4", 20mil strap, tensioner, sealer, cutter, seals, tool box Kits- Kits contain everything needed to begin steel strapping operation one heavy duty carton and packaged on a special skid. | \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ | | High Medium Medium Medium Medium |
| Portable Steel 2CXL3 3CTW8 6LGE0 BUZ35 3CTW9 | I Kits- Kits for flat loads. 3000ft. 1/2", 18mil strap, tensioner, 300 buckles, carton dispenser 400ft. 1/2", 20mil strap, tensioner, sealer, cutter, seals, tool box 400ft. 5/8", 20mil strap, tensioner, sealer, seal dispenser, cutting tool 3000ft. 5/8", 20mil strap, 300 buckles, 1 hand pull tensioner 400ft. 3/4", 20mil strap, tensioner, sealer, cutter, seals, tool box | v v v | У У У | High Medium Medium Medium |

Jumbo Steel Kits for Round Bundles- kits that are designed for round bundles and hard-to-reach places.

| 6LGD7 | 2942ft. 1/2", 20mil oscillated strap, tensioner, sealer, seals, dispenser, cutter | ✓ | ✓ | High |
|-------|---|----------|----------|------|
| 6LGD6 | 2353ft. 5/8", 20mil oscillated strap, tensioner, sealer, seals, dispenser, cutter | ~ | ✓ | High |
| 6LGD8 | 2353ft. 5/8", 20mil oscillated strap, tensioner, sealer, seals, dispenser, cutter | ~ | ✓ | High |
| 6LGD9 | 1961ft, 3/4", 20mil oscillated strap, tensioner, sealer, seals, dispenser, cutter | ~ | ~ | Hiah |



Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

MANUAL TOOLS FOR STEEL STRAPPING

These tools are designed to withstand tough steel strapping applications. Priced very competitively and covering a broad range of applications, they are backed by a large inventory of parts and our own service department. In addition to the stock tools listed, we can also supply you with specialty steel strapping tools for unique applications from a wide range of sources.

to 1-1/4" x .035 Steel, HD Feed Wheel, Push Bar tensioner



Medium

Sealers- for steel and flat surfaces.

52YU59

| Grainger Item Number | Item Description | Environmentally Responsible | Safety Enhanced | Productivity Levels |
|-------------------------|--|-----------------------------|--------------------|------------------------|
| 52YU53 | 3/8" to .020, Steel Strap, Heavy Duty, Double Down Notch | ✓ | ✓ | Medium |
| 36T402 | 3/8" to .030, Streel Strap, Double Down Notch | ✓ | ✓ | Medium |
| 52YU66 | 1/2" to .023, Steel Strap, Single Up Notch | ✓ | ✓ | Medium |
| 3CUN9 | 1/2" to .030, Steel Strap, Double Down Notch | ✓ | V | Medium |
| 52YU67 | 5/8" to .023, Steel Strap, Single Up Notch | ✓ | ✓ | Medium |
| 3CUP1 | 5/8" to .030, Steel Strap, Double Down Notch | ✓ | ✓ | Medium |
| 52YU68 | 3/4" to .023, Steel Strap, Single Up Notch | ✓ | V | Medium |
| 52YU71 | 3/4" x .025 to .035 Heavy Duty, Single Notch | ✓ | ✓ | Medium |
| 3CUP2 | 3/4" to .030, Steel Strap, Double Down Notch | V | V | Medium |
| 52YU70 | 1-1/4" x .031 to .035 Heavy Duty, Single Down Notch | V | ✓ | Medium |
| 52YU69 | 1-1/4" x .031 to .035 Heavy Duty, Double Up Notch | V | V | Medium |
| Sealless Comi | pination Tools- for steel and also regular duty and high to | ensile steel. | | |
| 49LX43 | 1/2" x .015, Regular Duty, Hi-Tensile, Steel, Sealless | ✓ | ✓ | Medium |
| 52YU73 | 1/2" x .017, Regular Duty Steel, Sealless | V | V | Medium |
| 52YU75 | 5/8" x .035, Regular Duty Steel, Sealless | V | V | Medium |
| 40TP60 | 3/4" x .025, Heavy Duty, Hi-Tensile Steel, Sealless | V | V | Medium |
| 40TP52 | 3/4" x .025 to .03, Hi-Tensile, Heavy Duty Steel, Sealless | V | V | Medium |
| 52YU74 | 3/4" x .035, Regular Duty Steel, Sealless | ✓ | V | Medium |
| Strap Cutters- | for steel and flat or round surfaces. | | | |
| 3CTX3 | 3/4" to .035, Steel Strap, Regular Duty, 9" | ✓ | V | Medium |
| 52YU76 | 1-1/4" x .035", 12" Alloy Steel, Cushion Grip Strapping Cutter | V | V | Medium |
| 3CTX4 | 1-1/4" to .035, Steel Strap, High Tensile, 11" | V | V | Medium |
| 52YU72 | to 2 x .050", Heavy Duty Cushion Grip Strapping Cutter | V | V | Medium |
| Tensioners- fo | r steel and at least 6" flat working surface. | | | |
| 3CUN7 | 1/2" x .015" - 3/4" x .023 Steel, Feed Wheel tensioner | v | ✓ | Medium |
| 52YU77 | 1/2" x .020 to 3/4" x .035 Hi-Tensile Steel, Feed Wheel tension | ner 🗸 | ✓ | Medium |
| 52YU60 | 3/4" x .023" Steel, Feed Wheel/Push Bar tensioner | ✓ | ✓ | Medium |
| 9ADJ8 | 3/4" x .0312 to 1-1/4" x .035 Steel, Feed Wheel tensioner | ✓ | ✓ | Medium |
| | | | | |



Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

MANUAL TOOLS FOR PLASTIC STRAPPING

The symmetrical series of sealing tools work with serrated seals crimped from either side. Crimping the seal is foolproof as operators no longer have to match the correct side of the sealer with the seal.



| Grainger Item Number | Item | Environmentally | Safety | Productivity |
|-------------------------|---|------------------------|---------------------------------------|--------------|
| item Number | Description | Responsible | Enhanced | Levels |
| 2CXN7* | 1/2" All Plastic, Single Feed High Joint Strength | ✓ | ✓ | Medium |
| 52YU58 | 1/2" up to .035", All Plastic, Double Down, Heavy Duty | ✓ | ✓ | Medium |
| 2CXN8* | 5/8" All Plastic, Single Feed High Joint Strength | ✓ | ✓ | Medium |
| 36T387 | Up to 5/8", All Plastic Strap, Extreme Tension, Heavy Duty | ✓ | · · · · · · · · · · · · · · · · · · · | Medium |
| Manual Sealer | s with 13" Handles- for plastic and regular duty applica | ations. | | |
| 2CXN3 | 1/2" All Plastic Strap, General Use | ✓ | ✓ | Medium |
| 2CXN4 | 5/8" All Plastic Strap, General Use | V | V | Medium |
| Manual Sealer | s with 17" Handles - for plastic and regular duty or hea | vy duty applications. | | |
| 2CXN5* | 1/2" Poly Strap .030", Heavy Duty, Serrated Seals | ✓ | ✓ | Medium |
| BAVA8 | 1/2" All Plastic Strap .031, Regular Duty | ✓ | ✓ | Medium |
| 52YU55 | 1/2" All Plastic Strap .031, Heavy Duty | V | V | Medium |
| 9GF35 | 5/8" All Plastic Strap .015 to .028, Heavy Duty, 18" Handles | ✓ | V | Medium |
| 16P077* | 5/8" Poly Strap .030" to .040", Heavy Duty, Serrated Seals | ✓ | ✓ | Medium |
| 2CXN6* | 5/8" Poly Strap .030" to .040", Heavy Duty, Serrated Seals | V | V | Medium |
| 52YU56 | 5/8" All Plastic Strap .031, Heavy Duty | V | ✓ | Medium |
| 40TP50 | 5/8" Poly Strap up to .047", Crimp, Flat Surface | V | ~ | Medium |
| Manual Symm | etrical Sealers with 17" Handles- for polyester strappi | ng and serrated seal a | pplications. | |
| 40TP72* | 1/2" x up to .030" Poly Strap with Serrated Seals | ✓ | ✓ | Medium |
| 40TP69* | 3/4" x up to .050" Poly Strap with Serrated Seals | V | V | Medium |
| 40TP77 | 3/4" x up to .050" Poly Strap with Serrated Seals, 20" Handl | es 🗸 | ~ | Medium |
| Tensioners- fo | or plastic and also general use applications. | | | |
| 36T411 | Up to 5/8", All Plastic Strap, Safety Hand Tensioner | ✓ | ✓ | Medium |
| 2CXN2 | Up to 3/4", All Plastic Strap on Flat Surfaces | V | V | Medium |
| 52YU54 | Up to 3/4", All Plastic Strap, Buckle Tensioner | V | V | Medium |
| 9ADJ5 | Up to 3/4", All Plastic Strap, Heavy Duty Tensioner | V | V | Medium |
| 36T357 | Up to 3/4", All Plastic Strap, Extreme Tension, Heavy Duty | <i>V</i> | V | Medium |
| 001001 | op to 0/4; / till I lastic Ottap, Extreme Tension, Heavy Baty | • | * | |

^{*}Designed for use with HSS-4, HSS-5, and HSS-6 seals with the appropriately sized tool.

Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

PLASTIC & STEEL STRAPPING DISPENSERS & PORTABLE COILS

All strapping dispensers are quality manufactured utilizing the highest quality material and workmanship. High yield structural tubing, heavy load bearing wheels, and solidly constructed brake assemblies result in dispensers that will give you years of dependable performance.



| Grainger Item Number | Item Description | Environmentally Responsible | Safety Enhanced | Productivity Levels |
|-------------------------|---|--------------------------------|--------------------|------------------------|
| 16P036 | 3/8" x .015, Average Break 665 ft./lb., Regular Duty | ✓ | ✓ | Medium |
| 16P037 | 1/2" x .015, Average Break 890 ft./lb., Regular Duty | V | V | Medium |
| 52YU47 | 1/2" x .017, Average Break 1275 ft./lb., Regular Duty | V | V | High |
| 52YU48 | 1/2" x .020, Average Break 1180 ft./lb., Regular Duty | V | V | High |
| 16P038 | 1/2" x .023, Average Break 1350 ft./lb., Regular Duty | ~ | V | High |
| 52YU52 | 5/8" x .017, Average Break 1550 ft./lb., Regular Duty | V | ✓ | High |
| 16P039 | 5/8" x .023, Average Break 1690 ft./lb., Regular Duty | ✓ | ✓ | High |
| 43VN02 | 5/8" x .025, Average Break 1765 ft./lb., Regular Duty | ~ | V | High |
| 52YU50 | 3/4" x .017, Average Break 1900 ft./lb., Regular Duty | V | V | High |
| 3CTV1 | 3/4" x .020, Average Break 1765 ft./lb., Regular Duty | V | V | High |
| 3CTV2 | 3/4" x .020, Average Break 1765 ft./lb., Regular Duty | V | V | High |
| 43VN03 | 3/4" x .020, Average Break 1765 ft./lb., Regular Duty | V | ✓ | High |
| 16P040 | 3/4" x .023, Average Break 2025 ft./lb., Regular Duty | V | V | High |

High Tensile Portable Coils- Steel strapping is manufactured from cold rolled steel and heat treated to maximize break strength and ductility. High tensile steel provides additional break strength and shock resistance for your toughest applications.

| 16P041 | 1/2" Stock Steel, Oscillated, High Tensile, 29 mil, 200 ft./coil | ✓ | ✓ | Medium |
|-----------------------------|---|-----------------|----------|--------|
| 16P042 | 5/8" Stock Steel, Oscillated, High Tensile, 20 mil, 200 ft./coil | V | ✓ | Medium |
| 3CTU5 | 3/4" Stock Steel, Oscillated, High Tensile, 25 mil, 1,569 ft./coil | V | V | High |
| 16P043 | 3/4" Stock Steel, Oscillated, High Tensile, 29 mil, 200 ft./coil | V | V | Medium |
| 3CTU6 | 3/4" Stock Steel, Oscillated, High Tensile, 29 mil, 1,330 ft./coil | ~ | ✓ | High |
| | | | | |
| Heavy Duty | Dispenser - These dispensers are shipped knocked down and | can ship via UF | S. | |
| Heavy Duty 48UY02 | Dispenser - These dispensers are shipped knocked down and 16x6, 16x3 Core Size, Mill Wound, Heavy Duty Steel/Plastic | can ship via UF | PS. ✔ | High |

Strapping Machinery - Steel portable coils are used in a variety of applications where a full coil of steel is not needed or is not practical. All portable coils are ribbon wound in a self-dispensing carton.

52DN28 Banding Chopper, Steel, Polypropylene and Polyester

High

Call or visit your local branch or go to **grainger.com/graingerchoice** for complete product line information.

