

Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

Environmentally

Safety

STRAPPING SOLUTIONS

Item

Grainger

In the appropriate applications, plastic strapping has consistently proven to reduce the amount of packaging at the source over alternative packaging methods. Source reduction means using less material to hold or package a product. This means less packaging to discard at the destination and less material to recycle. In addition, when you can apply plastic strapping with a machine or friction weld tool you further reduce the packaging by eliminating a mechanical seal. plastic is also light and flexible, making it the safest alternative for many applications.



Productivity

Item Number		Environmentally Responsible	Enhanced	Levels
Polypropylene use with power	Hand Grade Strapping- for applications ranging from lig tools.	htweight hand-applie	ed strapping to heavy	duty strapping for
8DXA8	Hand Grade Polypropylene, 16 mil, 6,600 ft./coil, BK	✓	✓	Medium
2CXG9	Hand Grade Polypropylene, 17.7 mil, 4,500 ft./coil, BK	✓	✓	Medium
2CXH1	Hand Grade Polypropylene, 17.7 mil, 9,000 ft./coil, BK	✓	✓	Medium
41P039	Hand Grade Polypropylene, 18 mil, 9,000 ft./coil, BK	✓	✓	Medium
41P046	Hand Grade Polypropylene, 18 mil, 9,000 ft./coil, BK	V	✓	Medium
6LFZ5	Hand Grade Polypropylene, 22 mil, 300 ft./L, Smooth	V	V	Medium
41P045	Hand Grade Polypropylene, 22 mil, 9,000 ft./coil, 8"W x 8"D, B	K 🗸	✓	Medium
41P044	Hand Grade Polypropylene, 22 mil, 9,000 ft./coil, 16"W x 6"D,	BK ✔	V	Medium
6LFZ8	Hand Grade Polypropylene, 22 mil, 9,000 ft./coil, 8"W x 8"D, B	K 🗸	V	Medium
6LFZ7	Hand Grade Polypropylene, 22 mil, 9,000 ft./coil, 16"W x 6"D,	BK ✔	V	Medium
6LFZ4	Hand Grade Polypropylene, 23 mil, 300 ft./L, Smooth	✓	V	Medium
6LFZ9	Hand Grade Polypropylene, 22 mil, 4,500 ft./coil, BK	✓	V	Medium
2CXH6	Hand Grade Polypropylene, 25 mil, 3,000 ft./coil	✓	V	Medium
2CXH7	Hand Grade Polypropylene, 25 mil, 6,000 ft./coil	✓	V	Medium
6LFZ6	Hand Grade Polypropylene, 26 mil, 300 ft./coil, BK	V	V	Medium
2CXH2	Hand Grade Polypropylene, 26 mil, 3,600 ft./coil, BK	✓	V	Medium
41P042	Hand Grade Polypropylene, 26 mil, 6,000 ft./coil, BK	✓	V	Medium
41P043	Hand Grade Polypropylene, 26 mil, 7,000 ft./coil, BK	V	V	Medium
2CXH3	Hand Grade Polypropylene, 26 mil, 7,200 ft./coil, BK	✓	V	Medium
41P047	Hand Grade Polypropylene, 26 mil, 7,200 ft./coil, BK	✓	V	Medium
41P040	Hand Grade Polypropylene, 26 mil, 7,200 ft./coil, 500lb., BK	✓	V	Medium
41P041	Hand Grade Polypropylene, 26 mil, 7,200 ft./coil, 600lb., BK	✓	V	Medium
2CXH4	Hand Grade Polypropylene, 30 mil, 3,600 ft./coil, BK	V	V	Medium
41P062	Hand Grade Polypropylene, 30 mil, 6,000 ft./coil, BK	✓	V	Medium
2CXH5	Hand Grade Polypropylene, 30 mil, 7,200 ft./coil, BK	✓	V	Medium
41P048	Hand Grade Polypropylene, 30 mil, 7,200 ft./coil, BK	✓	✓	Medium
16P049	Hand Grade Polypropylene, 32 mil, 2,200 ft./coil, BK	✓	V	Medium
16P048	Hand Grade Polypropylene, 32 mil, 3,500 ft./coil, BK	✓	V	Medium
41P038	Hand Grade Polypropylene, 32 mil, 3,500 ft./coil,BK	✓	V	Medium
41P051	Hand Grade Polypropylene, 33 mil, 4,500 ft./coil, 8"W x 8"D, E	BK ✔	V	Medium
41P050	Hand Grade Polypropylene, 33 mil, 4,500 ft./coil,16"W x 6"D, E	SK 🗸	V	Medium
41P049	Hand Grade Polypropylene, 37 mil, 5,000 ft./coil, BK	V	V	Medium

Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping



Grainger Item Number	Item Description	Environmentally Responsible	Safety Enhanced	Productivity Levels
Polyester Hand with power tool	d Grade Strapping- for applications ranging from list.	ghtweight hand-applied str	apping to heavy duty	strapping for use
9UDG4	Hand Grade Polyester, 20 mil, 2,850 ft./coil, BK	✓	✓	High
2CXK5	Hand Grade Polyester, 20 mil, 3,600 ft./coil, BK	✓	✓	High
16P052	Hand Grade Polyester, 25 mil, 4,400 ft./coil, BK	✓	✓	High
2CXK8	Hand Grade Polyester, 25 mil, 2,500 ft./coil, BK	✓	✓	High
41P036	Hand Grade Polyester, 25 mil, 4,400 ft./coil, BK	V	✓	High
2CXL1	Hand Grade Polyester, 30 mil, 1,800 ft./coil, BK	✓	✓	High
16P057	Hand Grade Polyester, 40 mil, 4,200 ft./coil, BK	~	✓	High
16P053	Hand Grade Polyester, 25 mil, 4,400 ft./coil, GN	V	✓	High
41P037	Hand Grade Polyester, 25 mil, 4,400 ft./coil, GN	V	✓	High
41P087	Hand Grade Polyester, 30 mil, 3,600 ft./coil, GN	✓	✓	High
9NMC0	Hand Grade Polyester, 30 mil, 3,600 ft./coil, GN	V	✓	High
16P054	Hand Grade Polyester, 35 mil, 4,000 ft./coil, GN	V	✓	High
16P056	Hand Grade Polyester, 40 mil, 4,200 ft./coil, GN	V	V	High



41P089

Grainger Item Number Strapping with	Item Description Bonded Finish- for inside or outside applications.	Environmentally Responsible	Safety Enhanced	Productivity Levels
41P089	Hand Grade Polyester, 20 mil, 7,200 ft./coil, BK	✓	✓	High
41P092	Hand Grade Polyester, 25 mil, 5,800 ft./coil, BK	✓	✓	High
41P093	Hand Grade Polyester, 30 mil, 3,600 ft./coil, BK	✓	✓	High
41P103	Hand Grade Polyester, 35 mil, 4,000 ft./coil, BK	✓	✓	High
41P105	Hand Grade Polyester, 40 mil, 4,000 ft./coil, BK	✓	✓	High
41P090	Hand Grade Polyester, 20 mil, 7,200 ft./coil, GN	✓	✓	High
41P091	Hand Grade Polyester, 25 mil, 5,800 ft./coil, GN	✓	V	High
41P102	Hand Grade Polyester, 35 mil, 4,000 ft./coil, GN	V	V	High
41P104	Hand Grade Polyester, 40 mil, 4,000 ft./coil, GN	✓	✓	High
16P065	Hand Grade Polyester Cord, 25 mil, 2,100 ft./coil, WT	V	V	High
16P064	Hand Grade Polyester Cord, 25 mil, 3,000 ft./coil, WT	V	V	High
16P063	Hand Grade Polyester Cord, 25 mil, 3,900 ft./coil, WT	V	V	High
16P061	Hand Grade Polyester Cord, 25 mil, 7,800 ft./coil, WT	V	✓	High
16P073	Hand Grade Polyester, HD Cord, 48 mil, 1,960 ft./coil, WT	V	V	High
16P074	Hand Grade Polyester, HD Cord, 60 mil, 1,640 ft./coil, WT	✓	✓	High

Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping



Grainger Item Number		Environmentally Responsible	Safety Enhanced	Productivity Levels
Polypropylene	Machine Grade Strapping- for applications ranging from	n semi-automatic and	d automatic machine a	applications.
2CXK4	Machine Grade Polypropylene, 20 mil, 7,200 ft./coil, BK	✓	✓	Medium
8AVA5	Machine Grade Polypropylene, 23 mil, 12,900 ft./coil, BK	V	V	Medium
2CXK7	Machine Grade Polypropylene, 25 mil, 5,800 ft./coil, BK	✓	V	Medium
8NCR1	Machine Grade Polypropylene, 28 mil, 6,600 ft./coil, BK	✓	V	Medium
2CXK9	Machine Grade Polypropylene, 30 mil, 3,600 ft./coil, BK	✓	✓	Medium
40TP66	Machine Grade Polypropylene, 30 mil, 6,000 ft./coil, BK	V	V	Medium
41P085	Machine Grade Polypropylene, 30 mil, 6,000 ft./coil, BK	✓	✓	Medium
6LGC9	Machine Grade Polypropylene, 30 mil, 6,000 ft./coil, BK	✓	✓	Medium
8AUU9	Machine Grade Polypropylene, 30 mil, 6,000 ft./coil, BK	✓	✓	Medium
6LGD0	Machine Grade Polypropylene, 33 mil, 6,000 ft./coil, BK	V	V	Medium
41P086	Machine Grade Polypropylene, 33 mil, 7,200 ft./coil, BK	✓	V	Medium
36T406	Machine Grade Polypropylene, (Pallet/28), BK	V	V	Medium
41P083	Machine Grade Polypropylene, 24 mil, 18,000 ft./coil, CLR	V	V	Medium
6LGC7	Machine Grade Polypropylene, 24 mil, 18,000 ft./coil, CLR	V	V	Medium
2CXK3	Machine Grade Polypropylene, 20 mil, 7,200 ft./coil, GN	V	✓	Medium
2CXK6	Machine Grade Polypropylene, 25 mil, 5,800 ft./coil, GN	V	✓	Medium
40TP44	Machine Grade Polypropylene, 21 mil, 12,900 ft./coil, WT	V	✓	Medium
2CXH8	Machine Grade Polypropylene, 22 mil, 12,900 ft./coil, 8" x 8", V	VT 🗸	V	Medium
2CXH9	Machine Grade Polypropylene, 22 mil, 12,900 ft./coil, 8" x 9", V	VT 🗸	✓	Medium
41P063	Machine Grade Polypropylene, 22 mil, 12,900 ft./coil, 8" x 8", V	VT 🗸	✓	Medium
41P064	Machine Grade Polypropylene, 22 mil, 12,900 ft./coil, 9" x 8", V	VT 🗸	✓	Medium
41P065	Machine Grade Polypropylene, 24 mil, 9,900 ft./coil, WT	V	✓	Medium
41P066	Machine Grade Polypropylene, 24 mil, 9,900 ft./coil, WT	✓	✓	Medium
2CXJ1	Machine Grade Polypropylene, 24 mil, 9,900 ft./coil, 8" x 8", W	T 🗸	✓	Medium
2CXJ2	Machine Grade Polypropylene, 24 mil, 9,900 ft./coil, 8" x 9", W	T 🗸	✓	Medium
41P084	Machine Grade Polypropylene, 24 mil, 18,000 ft./coil, WT	V	✓	Medium
6LGC8	Machine Grade Polypropylene, 24 mil, 18,000 ft./coil, WT	✓	✓	Medium
2CXJ3	Machine Grade Polypropylene, 28 mil, 7,200 ft./coil, WT	✓	✓	Medium
41P067	Machine Grade Polypropylene, 28 mil, 7,200 ft./coil, WT	✓	✓	Medium
8DV01	Machine Grade Polypropylene, 9,000 ft./coil, 8"W, WT	✓	V	Medium

36T403

MACHINE GRADE POLYPROPYLENE - METRIC SIZES

Grainger Item Description Environmentally Responsible Safety Enhanced Levels

Machine grad low elongation- available in skid quantities only.

36T403 5MM, 24,000ft./coil, 110lbs. break, 8x8, WT ✓ Medium

Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

POLYPROPYLENE HAND AND MACHINE GRADE STRAPPING

Plastic strapping has consistently proven to reduce the amount of packaging at the source over alternative packaging methods. Source reduction means using less material to hold or package a product. This means less packaging to discard at the destination and less material to recycle. In addition, when you can apply plastic strapping with a machine or friction weld tool you further reduce the packaging by eliminating a mechanical seal. Plastic is also light and flexible, making it the safest alternative for many applications.



Grainger Item Number	Item Description	Environmentally Responsible	Safety Enhanced	Productivity Levels
Polypropylene	Machine Grade Strap- for machines and tools.			
40TP49	Machine Grade Polypropylene, 14 mil, 12,000 ft./coil, BK	✓	✓	Medium
6LGC1	Machine Grade Polypropylene, 14 mil, 16,000 ft./coil, BK	✓	✓	Medium
33RZ02	Machine Grade Polypropylene, 16 mil, 12,000 ft./coil, BK	✓	✓	Medium
41P076	Machine Grade Polypropylene, 16 mil, 12,000 ft./plt., BK	✓	✓	Medium
41P077	Machine Grade Polypropylene, 16 mil, 16,000 ft./plt.,BK	✓	V	Medium
6LGC0	Machine Grade Polypropylene, 16 mil, 12,000 ft./coil, BK	V	V	Medium
2CXJ5	Machine Grade Polypropylene, 20 mil, 10,500 ft./coil, BK	✓	V	Medium
41P069	Machine Grade Polypropylene, 20 mil, 10,500 ft./plt., BK	V	V	Medium
33RZ21	Machine Grade Polypropylene, 22 mil, 8,000 ft./coil, BK	V	V	Medium
41P073	Machine Grade Polypropylene, 22 mil, 8,000 ft./plt., BK	✓	✓	Medium
2CXJ8	Machine Grade Polypropylene, 23 mil, 5,000 ft./coil, BK	V	V	Medium
2CXK1	Machine Grade Polypropylene, 23 mil, 7,500 ft./coil, BK	V	V	Medium
41P072	Machine Grade Polypropylene, 23 mil, 9,000 ft./plt., BK	V	V	Medium
41P074	Machine Grade Polypropylene, 23 mil, 7,500 ft./plt., BK	V	V	Medium
41P111	Machine Grade Polypropylene, 23 mil, 7,700 ft./plt., BK	V	V	Medium
2CXJ6	Machine Grade Polypropylene, 25 mil, 8,000 ft./coil, BK	V	V	Medium
41P070	Machine Grade Polypropylene, 25 mil, 8,000 ft./plt., BK	V	V	Medium
33RZ03	Machine Grade Polypropylene, 26 mil, 7,000 ft./coil, BK	V	V	Medium
2CXJ7	Machine Grade Polypropylene, 30 mil, 7,000 ft./coil, BK	V	V	Medium
41P071	Machine Grade Polypropylene, 30 mil, 7,000 ft./plt., BK	V	V	Medium
40TP47	Machine Grade Polypropylene, 13 mil, 30,000 ft./coil, CLR	V	V	Medium
6LGC2	Machine Grade Polypropylene, 14 mil, 16,000 ft./coil, CLR	✓	V	Medium
40TP68	Machine Grade Polypropylene, 14 mil, 25,000 ft./coil, CLR	V	V	Medium
2CXK2	Machine Grade Polypropylene, 16 mil, 12,000 ft./coil, CLR	V	V	Medium
41P075	Machine Grade Polypropylene, 16 mil, 12,000 ft./plt., CLR	V	V	Medium
41P078	Machine Grade Polypropylene, 16 mil, 16,000 ft./plt., CLR	V	V	Medium
2CXJ4	Machine Grade Polypropylene, 16 mil, 18,000 ft./coil, CLR	V	V	Medium
41P068	Machine Grade Polypropylene, 16 mil, 18,000 ft./plt., CLR	✓	V	Medium
6LGC3	Machine Grade Polypropylene, 19 mil, 12,000 ft./coil, CLR	✓	V	Medium
41P079	Machine Grade Polypropylene, 19 mil, 12,000 ft./plt., CLR	V	V	Medium
6LGC5	Machine Grade Polypropylene, 23 mil, 7,500 ft./coil, CLR	✓	V	Medium
41P081	Machine Grade Polypropylene, 23 mil, 7,500 ft./plt., CLR	V	V	Medium
6LGC6	Machine Grade Polypropylene, 23 mil, 9,000 ft./coil, CLR	V	V	Medium
41P082	Machine Grade Polypropylene, 23 mil, 9,000 ft./plt., CLR	V	✓	Medium

Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

POLYESTER CORD STRAPPING SOLUTIONS

Polyester Cord is available in a range of sizes and types to handle your toughest cord applications. In addition to standard bonded products, can supply you with woven material in both regular duty and heavy duty, along with a broad range of composite polyester cord strapping.

Grainger Item Number	Item	Environmentally	Safety	Productivity
	Description	Responsible	Enhanced	Levels
-	d Strapping- for regular duty standard applications.			
16P055	5/8" Strap Width, Polyester, 35 mil, 4,000 ft./coil, BK	· ·	<u> </u>	High
36T405	5/8" Strap Width, Polyester, 25 mil, 4,200 ft., 28/pkg., BK	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	High
40TP59	3/8" Strap Width, Polyester, 20 mil, 9,600 ft./coil, GN	· · · · · · · · · · · · · · · · · · ·	· ·	High
40TP45	3/8" Strap Width, Polyester, 20 mil, 12,500 ft./coil, GN	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	High
33RZ08	1/2" Strap Width, Polyester, 28 mil, 300 ft./coil, GN	✓	<u> </u>	High
33RZ01	1/2" Strap Width, Polyester, 28 mil, 6,500 ft./coil, GN	✓	<i>V</i>	High
41P055	3/8" Strap Width, Polyester, 19 mil, 5,250 ft./coil, WT	✓	<u> </u>	High
41P061	3/4" Strap Width, Polyester, 21 mil, 2,100 ft./coil, WT	✓	· ·	High
41P059	5/8" Strap Width, Polyester, 25 mil, 3,000 ft./coil, WT	✓	✓	High
41P057	1/2" Strap Width, Polyester, 44 mil, 3,900 ft./coil, WT	✓	✓	High
Polyester Cord 40TP73	d Strapping- for regular duty woven applications. 1/4" Polyester Crosswoven, 7.27 mil, 7,800 ft./coil, WT	✓	V	High
16P067	1/2" Polyester Crosswoven, 25 mil, 1,500 ft./coil, WT	V	V	High
16P070	3/4" Polyester Crosswoven, 25 mil, 2,100 ft./coil, WT	V	<i>V</i>	High
16P069	5/8" Polyester Crosswoven, 25 mil, 3,000 ft./coil, WT		<i>V</i>	High
16P068	1/2" Polyester Crosswoven, 25 mil, 3,900 ft./coil, WT	<i>V</i>		High
16P062	3/8" Polyester Crosswoven Bonded, 25 mil, 5,250 ft./coil, WT		<u> </u>	High
16P066	3/8" Polyester Crosswoven, 25 mil, 5,250 ft./coil, WT			High
41P054	3/8" Polyester Crosswoven, 45 mil, 5,250 ft./coii, WT		<u> </u>	High
	• • • • • • • • • • • • • • • • • • • •			
41P060	3/4" Polyester Crosswoven, 50 mil, 2,100 ft./plt., WT			High
41P058	5/8" Polyester Crosswoven, 50 mil, 3,000 ft./plt., WT	<u> </u>	<u> </u>	High
41P056	1/2" Polyester Crosswoven, 50 mil, 3,900 ft./plt., WT	✓	✓	High
_	Strapping- for heavy duty woven applications.			
16P072	1-1/4" HD Woven Polyester Cord, 26 mil, 600 ft./coil, NAT	<u> </u>	✓	High
52CC65	3/4" HD Woven Polyester Cord, 25 mil, 1,320 ft./coil, WT	<u> </u>	✓	High
2CXP8	3/4" HD Woven Polyester Cord, 30 mil, 1,320 ft./coil, WT	✓	✓	High
2CXP9	1-1/4" HD Woven Polyester Cord, 38 mil, 330 ft./coil, WT	✓	V	Hig
16P071	3/4" HD Woven Polyester Cord, 50 mil, 250 ft./coil, WT	✓	✓	High
41P052	1-1/4" HD Woven Polyester Cord, 52 mil, 600 ft./plt., WT	✓	✓	High
41P053	3/4" HD Woven Polyester Cord, 60 mil, 1,320 ft./plt., WT	✓	V	High
Polyester Grad	de Strap- for machines and tools.			
33RZ07	Multi Grade Polyester, 20 mil, 300 ft./coil, GN	✓	V	High
33RZ18	Multi Grade Polyester, 20 mil, 11,550 ft./coil, GN	V	V	High
9UDG5	Multi Grade Polyester, 21 mil, 10,500 ft./coil, GN	✓	✓	High
41P032	Multi Grade Polyester, 21 mil, 10,500 ft./plt., GN	V	V	High
8VU81	Multi Grade Polyester, 24 mil, 9,000 ft./coil, GN	✓	✓	High
41P033	Multi Grade Polyester, 24 mil, 9,000 ft./plt., GN	V	V	High
6LGA7	Multi Grade Polyester, 28 mil, 300 ft./coil, GN	V	V	High
6LGA9	Multi Grade Polyester, 30 mil, 300 ft./coil, GN	V	V	High

Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

Grainger Item Number	Item Description	Environmentally Responsible	Safety Enhanced	Productivity Levels
Polyester Stra	pping- for most friction weld applications.			
41P113	Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., BK	✓	✓	High
3HJZ5	Waxed Polyester, 40 mil, 3,000 ft./coil, BK	✓	✓	High
41P108	Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., BK	✓	✓	High
41P109	Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., BK	✓	✓	High
41P115	Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., BK	✓	✓	High
40TP78	Waxed Polyester, 50 mil, 1,800 ft.,/coil, BK	✓	✓	High
33RZ20	Waxed Polyester, 18 mil, 10,500 ft./coil, GN	✓	✓	High
16P050	Waxed Polyester, 21 mil, 9,000 ft./coil, GN	✓	✓	High
41P034	Waxed Polyester, 21 mil, 9,000 ft., 28/pkg., GN	✓	✓	High
41P035	Waxed Polyester, 28 mil, 6,500 ft., 28/pkg., GN	<i>V</i>	V	High
33RZ09	Waxed Polyester, 35 mil, 300 ft., 28/pkg., GN	✓	✓	High
2CXL2	Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN	✓	✓	High
33RZ12	Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN	V	✓	High
33RZ13	Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN	✓	V	High
41P097	Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN	✓	✓	High
41P112	Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN	V	V	High
41P110	Waxed Polyester, 40 mil, 2,200 ft., 28/pkg., GN	✓	V	High
40TP74	Waxed Polyester, 40 mil, 4,000 ft.,/coil, GN	V	V	High
41P114	Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN	✓	V	High
33RZ10	Waxed Polyester, 50 mil, 200 ft., 28/pkg., GN	V	V	High
40TP62	Waxed Polyester, 50 mil, 1,800 ft./coil, GN	V	V	High
16P060	Waxed Polyester, 50 mil, 2,200 ft., 28/pkg., GN	✓	✓	High
33RZ04	Waxed Polyester, 50 mil, 2,400 ft., 28/pkg., GN	·	V	High
41P106	Waxed Polyester, 50 mil, 2,400 ft., 28/pkg., GN	V	✓	High

Waxed Polyester Strapping- polyester strapping is made using the highest grade resins available to assure the strap meets the rigid specifications required by the American Association of Railroads. These straps are printed with an AAR approval number to designate the quality of the strapping.

36T408	AAR Approved Waxed Polyester, 40 mil, 11,000 ft., 28/pkg., BK	✓	✓	High
33RZ19	AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN	V	V	High
41P096	AAR Approved Waxed Polyester, 35 mil, 4,000 ft., 28/pkg., GN	V	✓	High
41P094	AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN	~	✓	High
5JPR2	AAR Approved Waxed Polyester, 40 mil, 3,000 ft., 28/pkg., GN	~	~	High
41P099	AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN	~	V	High
5JPR1	AAR Approved Waxed Polyester, 40 mil, 4,000 ft., 28/pkg., GN	~	V	High
41P107	AAR Approved Waxed Polyester, 50 mil, 2,400 ft., 28/pkg., GN	V	V	High
40TP62	AAR Approved Waxed Polyester, 50 mil, 3,000 ft., 28/pkg., GN	~	~	High

Embossed Polyester Cord Strapping- for multi duty applications.

	7 11			
41P088	Multi Grade Embossed Polyester, 25 mil, 4,400 ft., 28/pkg., BK	V	✓	High
5JPR3	Multi Grade Embossed Polyester, 25 mil, 7,200 ft., 28/pkg., GN	V	✓	High
41P095	Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN	V	✓	High
5JPR4	Multi Grade Embossed Polyester, 35 mil, 4,000 ft., 28/pkg., GN	V	V	High
41P101	Multi Grade Embossed Polyester, 40 mil, 3,000 ft., 28/pkg., GN	V	✓	High
5JPR6	Multi Grade Embossed Polyester, 40 mil, 3,000 ft., 28/pkg., GN	V	V	High
41P098	Multi Grade Embossed Polyester, 40 mil, 4,000 ft., 28/pkg., GN	V	V	High
5JPR5	Multi Grade Embossed Polyester, 40 mil, 4,000 ft., 28/pkg., GN	~	✓	High

Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

STOCK STEEL STRAPPING

Steel strapping is consistent in width, gauge, and finish. Published break strengths are average and meet or exceed industry standards.

Regular Duty Steel Strapping

Regular duty steel strapping is manufactured from cold rolled steel. All regular duty steel can be used in manual and pneumatic tools, as well as automatic steel strapping heads.

High Tensile Steel Strapping

High tensile steel strapping is manufactured from cold rolled steel and heat treated to maximize break strength and ductility. High tensile steel provides additional break strength and shock resistance for your toughest applications.



Grainger Item Number	Item Description	Environmentally Responsible	Safety Enhanced	Productivity Levels
Oscillated Wo	und- for regular duty steel applications.			
52YU46	1/2" Stock Steel, Oscillated Wound, 17 mil, 5,300 ft./coil, BK	✓	✓	High
52YU49	3/4" Stock Steel, Oscillated Wound, 17 mil, 5,300 ft./coil, BK	✓	✓	High
52YU51	5/8" Stock Steel, Oscillated Wound, 17 mil, 5,300 ft./coil, BK	✓	✓	High
3CTU2	1/2" Stock Steel, Oscillated Wound, 20 mil, 2,942 ft./coil, BK	✓	✓	High
3CTU3	5/8" Stock Steel, Oscillated Wound, 20 mil, 2,353 ft./coil, BK	V	✓	High
3CTU4	3/4" Stock Steel, Oscillated Wound, 20 mil, 1,961 ft./coil, BK	V	✓	High
32TL79	3/4" Stock Steel, Oscillated Wound, 20 mil, 1,961 ft., 12/plt., E	BK ✔	✓	High
32TL77	5/8" Stock Steel, Oscillated Wound, 20 mil, 2,353 ft., 12/plt., E	BK ✔	✓	High
32TL75	1/2" Stock Steel, Oscillated Wound, 20 mil, 2,942 ft., 12/plt., E	3K ✔	✓	High
6LGD4	3/4" Stock Steel, Oscillated Wound, 23 mil, 1,705 ft./coil, BK	V	✓	High
16P035	3/4" Stock Steel, Oscillated Wound, 23 mil, 1,705 ft./coil, BK	✓	✓	High
32TL80	3/4" Stock Steel, Oscillated Wound, 23 mil, 1,705 ft., 12/plt., E	BK ✔	✓	High
16P034	5/8" Stock Steel, Oscillated Wound, 23 mil, 2,046 ft./coil, BK	✓	✓	High
32TL78	5/8" Stock Steel, Oscillated Wound, 23 mil, 2,046 ft., 12/plt., E	3K ✔	✓	High
16P033	1/2" Stock Steel, Oscillated Wound, 23 mil, 2,558 ft./coil, BK	V	V	High
32TL76	1/2" Stock Steel, Oscillated Wound, 23 mil, 2,558 ft., 12/plt., E	3K ✔	✓	High



Ribbon Wound, High Tensile Steel

Ribbon wound strapping is wound onto itself to form a coil that is the same width as the strapping. Individual coil weight will vary with strapping width.

Grainger	Item Description	Environmentally	Safety	Productivity
Item Number		Responsible	Enhanced	Levels
3CTU7	1-1/4" Stk Steel, Ribbon Wnd, Hi-Tensile, 29 mil, 811 ft./coil,	BK 🗸	✓	High

Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

SEALS FOR STEEL STRAPPING

Steel Strapping seals are made from precision tested galvanized steel. Engineered for high joint efficiency with regular duty and heavy duty steel, all seal meet federal government standards, along with ASTM Standard D3953.

Grainger Item Number	Item Environm Description Respons		Safety Enhanced	Productivity Levels
Open Seals- fo	or regular duty applications.			
6LGD5	3/8", 20 mil, 1-1/4" L, Open Strapping Seal, Galvanized, 1000/pkg.	✓	✓	High
3CTV4	1/2", 20 mil, 1-1/8" L, Open Strapping Seal, Galvanized, 200/pkg.	V	✓	Medium
36T380	1/2", 20 mil, 1-1/4" L, Open Strapping Seal, Galvanized, 200/pkg.	V	✓	Medium
8E297	1/2", 20 mil, 1-1/4" L, Open Strapping Seal, Galvanized, 1000/pkg.	✓	✓	High
3CTV5	5/8", 20 mil, 1-1/4" L, Open Strapping Seal, Galvanized, 200/pkg.	~	✓	Medium
52YU57	5/8", 20 mil, 1-1/4" L, Open Strapping Seal, Galvanized, 200/pkg.	~	✓	Medium
3CTV6	3/4", 20 mil, 1-1/4" L, Open Strapping Seal, Galvanized, 200/pkg.	V	V	Medium
9GDN4	3/4", 20 mil, 1-1/4" L, Open Strapping Seal, Galvanized, 1000/pkg.	~	✓	High
•	or heavy duty applications. 3/4", 1-3/4" L, Open Seal, 500/pkg.	~	✓	Medium
3CTV7 3CTV8	1-1/4", 2-1/4" L, Open Seal, 500/pkg.	~	V	Medium
3CTV8	1-1/4", 2-1/4" L, Open Seal, 500/pkg. (Push Type)- for use with round bundles, and with pusher tools in	V	·	Medium
3CTV8 Overlap Seals	1-1/4", 2-1/4" L, Open Seal, 500/pkg. (Push Type)- for use with round bundles, and with pusher tools in to application.	V	·	Medium
3CTV8 Overlap Seals threaded prior	1-1/4", 2-1/4" L, Open Seal, 500/pkg. (Push Type)- for use with round bundles, and with pusher tools in	heavy-duty a	applications. These sea	Medium Is must be
Overlap Seals threaded prior 16P032	1-1/4", 2-1/4" L, Open Seal, 500/pkg. (Push Type)- for use with round bundles, and with pusher tools in to application. 3/8", Crimp Strapping Seal, Galvanized, 2500/pkg.	heavy-duty a	applications. These sea	Medium Is must be High
Overlap Seals threaded prior 16P032 52YU62	1-1/4", 2-1/4" L, Open Seal, 500/pkg. (Push Type)- for use with round bundles, and with pusher tools in to application. 3/8", Crimp Strapping Seal, Galvanized, 2500/pkg. 3/8", 1" L, Push Strapping Seal, Galvanized, 5000/pkg.	heavy-duty a	applications. These sea	Medium Is must be High High
Overlap Seals threaded prior 16P032 52YU62 3CTV9	1-1/4", 2-1/4" L, Open Seal, 500/pkg. (Push Type)- for use with round bundles, and with pusher tools in to application. 3/8", Crimp Strapping Seal, Galvanized, 2500/pkg. 3/8", 1" L, Push Strapping Seal, Galvanized, 5000/pkg. 1/2", 7/8" L, Push Strapping Seal, 200/pkg.	heavy-duty a	applications. These sea	Medium Is must be High High Medium
3CTV8 Overlap Seals threaded prior 16P032 52YU62 3CTV9 52YU63	1-1/4", 2-1/4" L, Open Seal, 500/pkg. (Push Type)- for use with round bundles, and with pusher tools in to application. 3/8", Crimp Strapping Seal, Galvanized, 2500/pkg. 3/8", 1" L, Push Strapping Seal, Galvanized, 5000/pkg. 1/2", 7/8" L, Push Strapping Seal, 200/pkg. 1/2", 1" L, Push Strapping Seal, Galvanized, 2500/pkg.	heavy-duty a	applications. These sea	Medium Is must be High High Medium High
3CTV8 Overlap Seals threaded prior 16P032 52YU62 3CTV9 52YU63 3CTW1 52YU64	1-1/4", 2-1/4" L, Open Seal, 500/pkg. (Push Type)- for use with round bundles, and with pusher tools in to application. 3/8", Crimp Strapping Seal, Galvanized, 2500/pkg. 3/8", 1" L, Push Strapping Seal, Galvanized, 5000/pkg. 1/2", 7/8" L, Push Strapping Seal, 200/pkg. 1/2", 1" L, Push Strapping Seal, Galvanized, 2500/pkg. 5/8", 7/8" L, Push Strapping Seal, 200/pkg.	heavy-duty a	applications. These sea	Medium Is must be High High Medium High Medium High
3CTV8 Overlap Seals threaded prior 16P032 52YU62 3CTV9 52YU63 3CTW1	1-1/4", 2-1/4" L, Open Seal, 500/pkg. (Push Type)- for use with round bundles, and with pusher tools in to application. 3/8", Crimp Strapping Seal, Galvanized, 2500/pkg. 3/8", 1" L, Push Strapping Seal, Galvanized, 5000/pkg. 1/2", 7/8" L, Push Strapping Seal, 200/pkg. 1/2", 1" L, Push Strapping Seal, Galvanized, 2500/pkg. 5/8", 7/8" L, Push Strapping Seal, 200/pkg. 5/8", 1" L, Push Strapping Seal, Galvanized, 5000/pkg.	heavy-duty a	applications. These sea	Medium Is must be High High Medium High Medium High Medium High
Overlap Seals threaded prior 16P032 52YU62 3CTV9 52YU63 3CTW1 52YU64 3CTW2 52YU65	1-1/4", 2-1/4" L, Open Seal, 500/pkg. (Push Type)- for use with round bundles, and with pusher tools in to application. 3/8", Crimp Strapping Seal, Galvanized, 2500/pkg. 3/8", 1" L, Push Strapping Seal, Galvanized, 5000/pkg. 1/2", 7/8" L, Push Strapping Seal, 200/pkg. 1/2", 1" L, Push Strapping Seal, Galvanized, 2500/pkg. 5/8", 7/8" L, Push Strapping Seal, 200/pkg. 5/8", 1" L, Push Strapping Seal, Galvanized, 5000/pkg. 3/4", 7/8" L, Push Strapping Seal, 200/pkg. 3/4", 7/8" L, Push Strapping Seal, Galvanized, 2500/pkg.	heavy-duty a	applications. These sea	Medium Is must be High High Medium High Medium High Medium High Medium High
Overlap Seals threaded prior 16P032 52YU62 3CTV9 52YU63 3CTW1 52YU64 3CTW2 52YU65	1-1/4", 2-1/4" L, Open Seal, 500/pkg. (Push Type)- for use with round bundles, and with pusher tools in to application. 3/8", Crimp Strapping Seal, Galvanized, 2500/pkg. 3/8", 1" L, Push Strapping Seal, Galvanized, 5000/pkg. 1/2", 7/8" L, Push Strapping Seal, 200/pkg. 1/2", 1" L, Push Strapping Seal, Galvanized, 2500/pkg. 5/8", 7/8" L, Push Strapping Seal, 200/pkg. 5/8", 1" L, Push Strapping Seal, Galvanized, 5000/pkg. 3/4", 7/8" L, Push Strapping Seal, 200/pkg.	heavy-duty a	applications. These sea	Medium Is must be High High Medium High Medium High Medium High Medium High

SEALS FOR PLASTIC STRAPPING

Seals are manufactured from the finest raw materials under carefully controlled conditions. They are known throughout the industry for quality, consistency, and reliability. All standard open and closed seals are made to ASTM Standard D3950.

36T384	3/8", Open Strapping Seal, 2500/pkg.	✓	✓	High
2CXP3	1/2", Open Strapping Seal, 1000/pkg.	✓	V	High
2CXP4	5/8", Open Strapping Seal, 1000/pkg.	V	V	High
16P030	3/4", Open Strapping Seal, 250/pkg.	V	~	Medium

SEALS FOR COMBINATION TOOLS

For use in specific tools. When ordering, please specify tool or comparable competitive seals. In addition to the stock sizes listed below, we carry a full line of seals for competitor's tools.

Serrated Strapping Seals- the most common plastic seal, open seals allow you to place the seal on after tensioning has occurred.

2CXP5	1/2", Serrated Strapping Seal, 1000/pkg.	✓	✓	High
2CXP6	5/8", Serrated Strapping Seal, 1000/pkg.	✓	✓	High
16P031	3/4", Serrated Strapping Seal, 250/pkg.	V	V	Medium
40TP76	3/4", Serrated Strapping Seal, 1000/pkg.	✓	V	High

Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

BUCKLES

Designed for light duty applications where corrosion resistance and/or non-scratch product is important, offering a range of plastic buckles to fit your demanding applications. For superior holding power and convenience, the patented "Bucklelok" design "locks" each leg into postion to allow for pre-threading.

16P029



Grainger Item Number	Item Description	Environmentally Responsible	Safety Enhanced	Productivity Levels
Plastic Buckle	s- for regular duty applications.			
16P029	1/2" to 5/8" Plastic Buckle, 250/pkg.	✓	✓	Medium
Strapping with	Plastic Buckles- for regular duty applications.			
43NE44	1/2" x 15' Plastic Strapping, Plastic Buckle, WT., 17ft., 500/p	okg. 🗸	✓	Medium
16P026	1/2" x 17' Plastic Strapping, Plastic Buckle, WT., 17ft., 25/pk	ĸg. ✔	V	Medium
43NE45	1/2" x 17' Plastic Strapping, Plastic Buckle, WT., 17ft., 500/p	okg. 🗸	✓	Medium
43NE46	1/2" x 22' Plastic Strapping, Plastic Buckle, WT., 17ft., 250/p	okg. 🗸	V	Medium
43NE47	1/2" x 25' Plastic Strapping, Plastic Buckle, WT., 17ft., 250/p	okg. 🗸	V	Medium

16P027



Wire Buckles- for use with polypropylene, polyester strapping, and polyester cord strapping. No hand tools required.

2JFF2	3/8" Metal Strapping Buckle, 1000/pkg.	✓	✓	High
2CXP1	1/2" Metal Strapping Buckle, 1000/pkg.	✓	✓	High
2CXP2	1/2" Heavy Duty Metal Strapping Buckle, 1000/pkg.	V	V	High
16P027	5/8" Metal Strapping Buckle, 250/pkg.	✓	~	Medium
16P028	3/4" Metal Strapping Buckle, 250/pkg.	✓	~	Medium

Strapping with Wire Buckles- for regular duty applications.

6P025 1/2" x 17' Plastic Strapping, Plastic Buckle, BK., 17ft., 25/pkg.

Medium

2CXR1



Phosphate Heavy Duty Buckles- for use with polyester cord and rayon cord heavy duty applications. The phosphate coating affords some additional protection against corrosion, and also significantly improves joint efficiency when properly applied.

2CXR1	3/4" Strapping Buckle, 1000/pkg.	4	4	High
2CXR2	1-1/4" Strapping Buckle, 1000/pkg.	4	4	High

EDGE PROTECTORS

For use with both steel and plastic strapping, corners cushion your product and allow the strap to be tightened to its maximum tension without damaging the package. Each plastic corner is constructed from a specially formulated resin and is ribbed to hold the strapping firmly in place. Steel corners meet all Federal and GSA specifications.

2CXP7	1-3/8"W, 1"L, Plastic, 2000/pkg., Max. 3/4" Strap, WT	✓	✓	High
5JPP6	2"W, 24"L, Polyethelyene, Max. 1/8" Strap, 50/pkg., BK	✓	~	Medium
5JPP7	2"W, 34"L, Polyethelyene, Max 1/8" Strap, 50/pkg., BK	✓	V	Medium
5JPP8	2"W, 42"L, Polyethelyene, Max 1/8" Strap, 50/pkg., BK	✓	V	Medium
4FET8	2-1/2"W, 1-3/4"L, Plastic, 1000/pkg. Max. 1-1/4" Strap, BK	V	V	High
4FET7	2-1/2"W, 2"L, Plastic, 1000/pkg. Max. 1-1/4" Strap, WT	V	V	High
4FEU2	2-1/2"W, 6"L, Plastic, 500/pkg. Max. 2" Strap, WT	V	V	Medium
4FEU3**	3"W, 2"L, Steel, 500/pkg. Max. 1-1/4" Strap	✓	V	Medium
4FET9*	5-1/4"W, 2"L, Plastic, 200/pkg. Max. 1-1/4" Strap, BK	V	V	Medium
4FEU1	5-1/4"W, 2"L, Plastic, 250/pkg. Max. 1-1/4" Strap, BK	V	V	Medium

^{*} Corners have four inside points which penetrate the outside layer of your carton to hold the corner in place

^{**}Steel corner protector

Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

STRAPPING KITS

The strapping kits offers wholesalers of both plastic and steel strapping an excellent opportunity to increase sales and profits by efficiently servicing those markets that need a complete strapping set up. With the family of kits, there is no need to inventory separate components, do any packaging, or send a sales rep out to do a demo.

These kits are available in both steel and plastic, and come in several sizes and varieties for a wide range of applications.



Grainger Item Number	Item Environ Description Respon	nmentally nsible	Safety Enhanced	Productivity Levels
Replacement	Kit- Kits for first time user and multi-location buyers that include ev	erything in one	kit.	
16P047	7200ft. 1/2", 500lb., strap, 500 Seals	4	4	High
2CXL4	7200ft. 1/2" HD strap, 1000 1/2" open seals, HD tensioner, sealer	4	4	High
6P044	9000ft. 1/2" 4 Lt. duty strap, 1000 1/2" open seals, tensioner & sealer	4	4	High
6P046	9000ft. 1/2", 300lb., strap, 500 Seals	4	4	High
6P045	9000ft. 1/2", 400lb., strap, 1000 wire buckles, hand pull tensioner	4	4	High
	for the customer who wants a premium strapping system.			
2CXL5	3600ft. 1/2", 500lb.,1 coil HD strap, 500 seals, tensioner, sealer, disper	nser 4	4	High
2CXL6	5800ft. 1/2", 775lb., HD strap, 500 seals, tensioner, sealer, dispenser	4	4	High
2CXL7	4000ft. 5/8", 1400lb., strap, 500 seals, tensioner, sealer, dispenser	4	4	High
Portable Stee	Kits- Kits for flat loads.			
CXL3	3000ft. 1/2", 18mil strap, tensioner, 300 buckles, carton dispenser	V	~	High
BCTW8	400ft. 1/2", 20mil strap, tensioner, sealer, cutter, seals, tool box			Medium
SLGE0	400ft. 5/8", 20mil strap, tensioner, sealer, seal dispenser, cutting tool			Medium
3UZ35	3000ft. 5/8", 20mil strap, 300 buckles, 1 hand pull tensioner			Medium
BCTW9	400ft. 3/4", 20mil strap, tensioner, sealer, cutter, seals, tool box	V	~	Medium
	(its- Kits contain everything needed to begin steel strapping oper special skid.	ations, all pac	kaged in one heavy du	ty carton and
oackaged on a	special skid.	•	kaged in one heavy du	
oackaged on a BCTX1	special skid. 2940ft. 1/2", 20mil strap, tensioner, sealer, cutter, 500 seals, mobile dis	spenser 🗸	kaged in one heavy du	ty carton and High High
packaged on a BCTX1 BCUN5	special skid.	spenser 🗸	V	High
oackaged on a BCTX1 BCUN5 BCUN6	special skid. 2940ft. 1/2", 20mil strap, tensioner, sealer, cutter, 500 seals, mobile di 1960ft. 3/4", 20mil strap, tensioner, sealer, cutter, 500 seals, mobile dis	spenser V spenser V	<i>V V</i>	High High
packaged on a BCTX1 BCUN5 BCUN6	special skid. 2940ft. 1/2", 20mil strap, tensioner, sealer, cutter, 500 seals, mobile dii 1960ft. 3/4", 20mil strap, tensioner, sealer, cutter, 500 seals, mobile dii 250ft. 3/4", 50mil strap, HD windlass, tensioner, 25 buckles, plastic ca	spenser spe	<i>V V</i>	High High
oackaged on a SCTX1 SCUN5 SCUN6 SUMBO Steel F	special skid. 2940ft. 1/2", 20mil strap, tensioner, sealer, cutter, 500 seals, mobile dia 1960ft. 3/4", 20mil strap, tensioner, sealer, cutter, 500 seals, mobile dia 250ft. 3/4", 50mil strap, HD windlass, tensioner, 25 buckles, plastic ca	spenser spe	reach places.	High High Medium
oackaged on a BCTX1 BCUN5 BCUN6	special skid. 2940ft. 1/2", 20mil strap, tensioner, sealer, cutter, 500 seals, mobile dis 1960ft. 3/4", 20mil strap, tensioner, sealer, cutter, 500 seals, mobile dis 250ft. 3/4", 50mil strap, HD windlass, tensioner, 25 buckles, plastic ca (its for Round Bundles- kits that are designed for round bundles 2942ft. 1/2", 20mil oscillated strap, tensioner, sealer, seals, dispenser,	spenser spenser spenser spenser spenser cutter c	reach places.	High High Medium High

Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

MANUAL TOOLS FOR STEEL STRAPPING

These tools are designed to withstand tough steel strapping applications. Priced very ompetitively and covering a broad range of applications, they are backed by a large inventory of parts and our own service department. In addition to the stock tools listed, we can also supply you with specialty steel strapping tools for unique applications from a wide range of sources.



Grainger Item Number	Item Description	Environmentally Responsible	Safety Enhanced	Productivity Levels
Sealers- for ste	eel and flat surfaces.			
52YU53	3/8" to .020, Steel Strap, Heavy Duty, Double Down Notch	✓	✓	Medium
36T402	3/8" to .030, Steel Strap, Double Down Notch	V	V	Medium
52YU66	1/2" to .023, Steel Strap, Single Up Notch	V	✓	Medium
3CUN9	1/2" to .030, Steel Strap, Double Down Notch	V	✓	Medium
52YU67	5/8" to .023, Steel Strap, Single Up Notch	V	✓	Medium
3CUP1	5/8" to .030, Steel Strap, Double Down Notch	✓	✓	Medium
52YU68	3/4" to .023, Steel Strap, Single Up Notch	✓	✓	Medium
52YU71	3/4" x .025 to .035 Heavy Duty, Single Notch	✓	✓	Medium
3CUP2	3/4" to .030, Steel Strap, Double Down Notch	✓	✓	Medium
52YU70	1-1/4" x .031 to .035 Heavy Duty, Single Down Notch	V	✓	Medium
52YU69	1-1/4" x .031 to .035 Heavy Duty, Double Up Notch	~	V	Medium
Sealless Comb	pination Tools- for steel and also regular duty and high	tensile steel.		
49LX43	1/2" x .015, Regular Duty, Hi-Tensile, Steel, Sealless	✓	V	Medium
52YU73	1/2" x .017, Regular Duty Steel, Sealless	✓	✓	Medium
52YU75	5/8" x .035, Regular Duty Steel, Sealless	✓	V	Medium
40TP60	3/4" x .025, Heavy Duty, Hi-Tensile Steel, Sealless	✓	V	Medium
40TP52	3/4" x .025 to .03, Hi-Tensile, Heavy Duty Steel, Sealless	✓	✓	Medium
52YU74	3/4" x .035, Regular Duty Steel, Sealless	V	✓	Medium
Strap Cutters- 3CTX3	for steel and flat or round surfaces. 3/4" to .035, Steel Strap, Regular Duty, 9"	✓	V	Medium
52YU76	1-1/4" x .035", 12" Alloy Steel, Cushion Grip Strapping Cutte		<u> </u>	Medium
BCTX4	1-1/4" to .035, Steel Strap, High Tensile, 11"	· · · · · · · · · · · · · · · · · · ·	<u> </u>	Medium
52YU72	to 2 x .050", Heavy Duty Cushion Grip Strapping Cutter	V	V	Medium
F				
	r steel and at least 6" flat working surface.			
3CUN7	1/2" x .015" - 3/4" x .023 Steel, Feed Wheel tensioner	<u> </u>	<u> </u>	Medium
52YU77	1/2" x .020 to 3/4" x .035 Hi-Tensile Steel, Feed Wheel tension		<u> </u>	Medium
52YU60	3/4" x .023" Steel, Feed Wheel/Push Bar tensioner	<u> </u>	<u> </u>	Medium
9ADJ8	3/4" x .0312 to 1-1/4" x .035 Steel, Feed Wheel tensioner	<i>V</i>	<u> </u>	Medium
52YU59	to 1-1/4" x .035 Steel, HD Feed Wheel, Push Bar tensioner	✓	✓	Medium

Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

MANUAL TOOLS FOR PLASTIC STRAPPING

The symmetrical series of sealing tools work with serrated seals crimped from either side. Crimping the seal is foolproof as operators no longer have to match the correct side of the sealer with the seal.

_				
Grainger tem Number	Item Description	Environmentally Responsible	Safety Enhanced	Productivit Levels
Manual Comb	ination Tools- for plastic applications.			
2CXN7*	1/2" All Plastic, Single Feed High Joint Strength	✓	✓	Medium
52YU58	1/2" up to .035", All Plastic, Double Down, Heavy Duty	V	V	Medium
2CXN8*	5/8" All Plastic, Single Feed High Joint Strength	V	✓	Medium
36T387	up to 5/8", All Plastic Strap, Extreme Tension, Heavy Duty	V	V	Medium
Manual Sealer	's with 13" Handles- for plastic and regular duty applic	ations.		
2CXN3	1/2" All Plastic Strap, General Use	✓	✓	Medium
2CXN4	5/8" All Plastic Strap, General Use	V	V	Medium
52YU55 9GF35 16P077* 2CXN6* 52YU56	1/2" All Plastic Strap .031, Heavy Duty 5/8" All Plastic Strap .015 to .028, Heavy Duty, 18" Handles 5/8" Poly Strap .030" to .040", Heavy Duty, Serrated Seals 5/8" Poly Strap .030" to .040", Heavy Duty, Serrated Seals 5/8" All Plastic Strap .031, Heavy Duty	<i>V V V V V V V V V V</i>	<i>V V V V V</i>	Medium Medium Medium Medium Medium
40TP50 Manual Symm 40TP72*	5/8" Poly Strap up to .047", Crimp, Flat Surface netrical Sealers with 17" Handles- for polyester strapp 1/2" x up to .030" Poly Strap with Serrated Seals	ing and serrated seal a	pplications.	Medium Medium
I0TP69*	3/4" x up to .050" Poly Strap with Serrated Seals	V	V	Medium
10TP77	3/4" x up to .050" Poly Strap with Serrated Seals, 20" Hand	les 🗸	V	Medium
Tensioners - fo	or plastic and also general use applications.			
36T411	Up to 5/8", All Plastic Strap, Safety Hand Tensioner	✓	✓	Medium
CXN2	Up to 3/4", All Plastic Strap on Flat Surfaces	V	V	Medium
52YU54	Up to 3/4", All Plastic Strap, Buckle Tensioner	✓	✓	Medium
ADJ5	Up to 3/4", All Plastic Strap, Heavy Duty Tensioner	V	V	Medium
36T357	Up to 3/4", All Plastic Strap, Extreme Tension, Heavy Duty	V	~	Medium

2CXN7

^{*}Designed for use with HSS-4, HSS-5, and HSS-6 seals with the appropriately sized tool.

Material Handling, Packaging and Shipping Strapping and Strapping Equipment, Plastic Strapping

PLASTIC & STEEL STRAPPING DISPENSERS & PORTABLE COILS

All strapping dispensers are quality manufactured utilizing the highest quality material and workmanship. High yield structural tubing, heavy load bearing wheels, and solidly constructed brake assemblies result in dispensers that will give you years of dependable performance.



High

48UY02

Grainger tem Number	Item Description	Environmentally Responsible	Safety Enhanced	Productivity Levels
Regular Duty I	Portable Coils - Steel portable coils are used in a variety	of applications where	a full coil of steel is r	ot needed or is not
oractical. All po	ortable coils are ribbon wound in a self-dispensing carton			
16P036	3/8" x .015, Average Break 665 ft./lb., Regular Duty	✓	✓	Medium
16P037	1/2" x .015, Average Break 890 ft./lb., Regular Duty	✓	✓	Medium
52YU47	1/2" x .017, Average Break 1275 ft./lb., Regular Duty	V	V	High
52YU48	1/2" x .020, Average Break 1180 ft./lb., Regular Duty	V	V	High
6P038	1/2" x .023, Average Break 1350 ft./lb., Regular Duty	✓	✓	High
52YU52	5/8" x .017, Average Break 1550 ft./lb., Regular Duty	V	✓	High
6P039	5/8" x .023, Average Break 1690 ft./lb., Regular Duty	V	✓	High
3VN02	5/8" x .025, Average Break 1765 ft./lb., Regular Duty	✓	✓	High
52YU50	3/4" x .017, Average Break 1900 ft./lb., Regular Duty	V	✓	High
CTV1	3/4" x .020, Average Break 1765 ft./lb., Regular Duty	✓	✓	High
CTV2	3/4" x .020, Average Break 1765 ft./lb., Regular Duty	V	✓	High
13VN03	3/4" x .020, Average Break 1765 ft./lb., Regular Duty	V	✓	High
6P040	3/4" x .023, Average Break 2025 ft./lb., Regular Duty	V	✓	High
•	ortable Coils- Steel strapping is manufactured from colornsile steel provides additional break strength and shock 1/2" Stock Steel, Oscillated, High Tensile, 29 mil, 200 ft./coil			oreak strength and Medium
01 041			•	
6P042		<u> </u>	V	
	5/8" Stock Steel, Oscillated, High Tensile, 20 mil, 200 ft./coil	<i>V</i>	V	Medium
6P042 8CTU5	5/8" Stock Steel, Oscillated, High Tensile, 20 mil, 200 ft./coil 3/4" Stock Steel, Oscillated, High Tensile, 25 mil, 1,569 ft./coi	· ·	V	Medium High
CTU5 6P043	5/8" Stock Steel, Oscillated, High Tensile, 20 mil, 200 ft./coil	· · · · · · · · · · · · · · · · · · ·		Medium
BCTU5 16P043 BCTU6	5/8" Stock Steel, Oscillated, High Tensile, 20 mil, 200 ft./coil 3/4" Stock Steel, Oscillated, High Tensile, 25 mil, 1,569 ft./coi 3/4" Stock Steel, Oscillated, High Tensile, 29 mil, 200 ft./coil 3/4" Stock Steel, Oscillated, High Tensile, 29 mil, 1,330 ft./coi spenser - These dispensers are shipped knocked down	l ✓ l ✓ and can ship via UPS.	<i>V V</i>	Medium High Medium High
CTU5 6P043 CTU6	5/8" Stock Steel, Oscillated, High Tensile, 20 mil, 200 ft./coil 3/4" Stock Steel, Oscillated, High Tensile, 25 mil, 1,569 ft./coil 3/4" Stock Steel, Oscillated, High Tensile, 29 mil, 200 ft./coil 3/4" Stock Steel, Oscillated, High Tensile, 29 mil, 1,330 ft./coil	V	<i>V V</i>	Medium High Medium

Strapping Machinery - Steel portable coils are used in a variety of applications where a full coil of steel is not needed or is not practical.

52DN28

All portable coils are ribbon wound in a self-dispensing carton.

Banding Chopper, Steel, Polypropylene and Polyester