



We would like to thank you for your decision to purchase a NoTrax® anti-fatigue floor mat with RedStop™ technology. Unique to NoTrax® floor mats, RedStop™ dramatically reduces mat slippage on smooth surfaces such as tiled or sealed/treated floors.

We're confident you will find the performance of this floor mat to be second to none. After all, when you see Red...you've made the right choice!

To ensure that you get the best possible performance from your mat and to maintain its appearance and integrity over the longest possible time, we suggest the following:

REMOVAL FROM PACKAGING

After removing the mat from the box, it should lay flat in a warm, dry environment for several hours to allow it to relax and uncurl before placing it into service.

CARE AND CLEANING

When placing a mat into service, be certain that the floor and the underside of the mat are completely free of dirt and debris. For best results, periodically clean the bottom of the mat using a damp cloth only, **NO** cleaning chemicals. Allow to air dry after cleaning. If using the mat on cleaned carpet, make sure that the carpet is completely dry before returning mat to use.

Superior Manufacturing Group will not be liable for any injuries resulting from failure to follow the recommended housekeeping procedures. Frequent cleaning under the mat is also required to maintain the warranty.

STORAGE & HANDLING

For proper storage, roll the mat with the top surface facing out and lay flat. Do not stack any materials or other mats on top of a rolled mat. Store mats in a dry environment with a moderate temperature.

(*Important note) Matting must never be stored on-end. This will cause the edges to curl and will void the warranty.



www.notrax.com