





Specialty



Ovation™ is made with a generously tufted Decalon® looped pile construction that serves as the finishing, drying and cleaning mat in the coordinated "Stages" series, or as zone 3 in the Opera™ 3-in-1 mat system. A heavyweight vinyl non-slip backing ensures minimum movement.

Test	Test Description	*Results
ASTM D6540	Accelerated Soiling Method	Based on Visual Inspection 4.8 - Vacuum Rating 5.0 - Rating After Extraction
ASTM D412	Breaking Load/Elongation	243.7 lbs/in <sup>2</sup>
ASTM 5252-98a	Accelerated Wear - 4,000 cycles (Hexapod Tumble Drum Tester)	Appearance: 2.5 Color: 3.0
ASTM D3936-05	Delamination	Exceeds Backing Strength
ASTM D2240-02	Durometer (Hardness)	75
ASTM D1335-05	Tuft Bind of Pile Yarn	16.3 = Superior
CPSC FF 1-70	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass

<sup>\*</sup>All testing of NoTrax\* floor matting has been performed by an independent testing laboratory.

07/2014

Appearance Rating Key		
5	No change	
4	Slight change	
3	Noticeable change	
2	Considerable change	
1	Severe change	

- Heavyweight vinyl non-slip backing
- Can be used as a stand-alone mat, or as the third section (Drying) of "Stages" entrance matting system
- Stock Sizes: 2' x 3', 3' x 4', 3' x 5', 3' x 6', 3' x 10', 4' x 6', 4' x 8'
- Roll Sizes: 3' x 60', 4' x 60', 6' x 60'
- Custom Sizes: In 3', 4', and 6' widths (up to 60')
- Recommended and approved product as part of the GreenTRAX™ program for "Green Cleaning" environments (When used as part of the "Stages"





