



Main

| | |
|--------------------------------|--------------------|
| Range | TeSys |
| Product name | TeSys CAK |
| Product or Component Type | Control relay |
| Device short name | CA2K |
| Contactor application | Control circuit |
| Utilisation category | AC-15 DC-13 |
| Pole contact composition | 3 NO + 1 NC |
| [Ue] rated operational voltage | <= 690 V <= 400 Hz |
| Control circuit type | AC 50/60 Hz |
| [Uc] control circuit voltage | 24 V AC 50/60 Hz |

Complementary

| | |
|---|--|
| [Ith] conventional free air thermal current | 10 A 122 °F (50 °C) |
| Irms rated making capacity | 110 A IEC 60947 |
| Associated fuse rating | 10 A gG IEC 60947 10 A gG VDE 0660 |
| [Ui] rated insulation voltage | 690 V IEC 60947 750 V VDE 0110 group C 690 V BS 5424 600 V CSA C22.2 No 14 |
| Mounting Support | Plate Rail |
| Connections - terminals | Screw clamp terminals 1 0.00...0.01 in ² (1.5...4 mm ²)solid Screw clamp terminals 2 0.00...0.01 in ² (1.5...4 mm ²)solid Screw clamp terminals 1 0.00...0.01 in ² (0.75...4 mm ²)flexible with cable end Screw clamp terminals 2 0.00...0.01 in ² (0.75...4 mm ²)flexible without cable end Screw clamp terminals 1 0.00...0.00 in ² (0.34...1.5 mm ²)flexible with cable end Screw clamp terminals 2 0.00...0.00 in ² (0.34...1.5 mm ²)flexible without cable end |
| Tightening torque | 11.51 Lbf.in (1.3 N.m) screw clamp terminals flat Ø 6 mm 11.51 lbf.in (1.3 N.m) screw clamp terminals Philips No 2 0.24 in (6 mm) |
| Control circuit voltage limits | Drop-out 0.2...0.75 U _c 122 °F (50 °C)) Operational 0.8...1.15 U _c 122 °F (50 °C)) |
| Operating time | 10...20 ms coil de-energisation and NO opening 10...20 ms coil energisation and NO closing 15...25 ms coil de-energisation and NC closing 5...15 ms coil energisation and NC opening |
| Mechanical durability | 10 Mcycles |
| Maximum operating rate | 10000 cyc/h |
| Immunity to microbreaks | 2 ms |
| Inrush power in VA | 30 VA 68 °F (20 °C)) |
| Hold-in power consumption in VA | 4.5 VA 68 °F (20 °C)) |
| Heat dissipation | 1.3 W |
| Minimum switching voltage | 17 V |
| Minimum switching current | 5 mA |
| Non overlap distance | 0.02 in (0.5 mm) |
| Insulation resistance | > 10 MOhm |
| Height | 2.28 in (58 mm) |

| | |
|------------|-----------------------|
| Width | 1.77 in (45 mm) |
| Depth | 2.24 in (57 mm) |
| Net Weight | 0.40 lb(US) (0.18 kg) |

Environment

| | |
|---------------------------------------|--|
| Standards | BS 5424 IEC 60947 NF C 63-140 VDE 0660 |
| Product Certifications | UL CSA |
| IP degree of protection | IP2x |
| Protective treatment | TC IEC 60068 |
| Ambient air temperature for operation | -13...122 °F (-25...50 °C) |
| Ambient Air Temperature for Storage | -58...176 °F (-50...80 °C) |
| Operating altitude | 6561.68 ft (2000 m) without derating |
| Flame retardance | V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102 |
| Mechanical robustness | Vibrations contactor open2 Gn, 5...300 Hz IEC 60068-2-6 Vibrations contactor closed4 Gn, 5...300 Hz IEC 60068-2-6 Shocks contactor open10 Gn for 11 ms IEC 60068-2-27 Shocks contactor closed15 Gn for 11 ms IEC 60068-2-27 |




Ordering and shipping details

| | |
|-----------------------|-------------------------|
| Category | 22371 - RELAYS, CONTROL |
| Discount Schedule | I12 |
| GTIN | 3389110500295 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 6.24 oz (177 g) |
| Returnability | Yes |
| Country of origin | ID |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 1.89 in (4.8 cm) |
| Package 1 width | 2.44 in (6.2 cm) |
| Package 1 Length | 2.60 in (6.6 cm) |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 50 |
| Package 2 Weight | 20.41 lb(US) (9.26 kg) |
| Package 2 Height | 5.91 in (15 cm) |
| Package 2 width | 11.81 in (30 cm) |
| Package 2 Length | 15.75 in (40 cm) |
| Package 3 Height | 30.31 in (77 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information |  Yes |

| | |
|--------------------------|--|
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|