

Edge Defender™ Cut Resistant Pad

The number one cause of synthetic sling failure is cutting. **Edge Defender** pads are our best synthetic product for protecting slings from being cut by load edges and protecting load edges from being marred due to lifting equipment.

Protect your loads and your slings now by using the new Lift-All **Edge Defender!**



Features:

- Three layers of webbing sewn together with Kevlar[®] thread
- A layer of orange vinyl is sandwiched between the first and second layer to aid inspection
- Synthetic material is flexible under load
- Velcro[®] straps help keep sling in position prior to lift

Benefits:

- Improves Safety – Thick pad sewn with Kevlar[®] thread gives excellent cut resistant protection to the sling
- Saves Time – Velcro[®] straps help to keep pad positioned on the sling to reduce rigging time
- Saves Money – This longer lasting pad protects slings better, extends sling life and reduces replacement purchases



Standard Pad Widths & Maximum Appropriate Sling Sizes

Pad Width (In.)	Max. Web Sling Width (In.)	Max. Tuflex Size	Max. KeyFlex Size	Part Numbers for Standard <i>Edge Defender</i> Lengths				
				12 In.	18 In.	24 In.	30 In.	36 In.
3	2	EN30	NA	ED3X12IN	ED3X18IN	ED3X24IN	ED3X30IN	ED3X36IN
4	3	EN60	NA	ED4X12IN	ED4X18IN	ED4X24IN	ED4X30IN	ED4X36IN
6	4	EN150	KEN20K	ED6X12IN	ED6X18IN	ED6X24IN	ED6X30IN	ED6X36IN
8	6	EN240	KEN50K	ED8X12IN	ED8X18IN	ED8X24IN	ED8X30IN	ED8X36IN
10	8	EN600	KEN90K	ED10X12IN	ED10X18IN	ED10X24IN	ED10X30IN	ED10X36IN

Velcro[®] is a registered trademark of Velcro Industries B.V.
 Kevlar[®] is a registered trademark of E.I. du Pont de Nemours and Company.