HOFALL DUCTTAPEIS CREATED EOUAL



DUCT TAPE IS NOT A ONE-SIZE FITS-ALL TOOL, PERFORMANCE IS DEPENDENT ON THE APPLICATION AND ENVIRONMENT IN WHICH THE TAPE IS USED, AS WELL AS HOW THE TAPE IS MADE. KNOWING HOW EACH MANUFACTURING PROCESS - CO-EXTRUSION AND **LAMINATION** – IMPACTS PERFORMANCE WILL HELP YOU CHOOSE

THE BEST DUCT TAPE FOR THE JOB AT HAND.



CO-EXTRUDED VS. LAMINATED DUCT TAPE:

WHICH ONE'S BEST FOR THE JOB?

	Location		Surface		Duration	
	Indoor	Outdoor	Even	Irregular	Short	Long
Co-Extruded	Best	Best	Best	Good	Best	Best
Laminated	Best	Good	Best	Best	Best	Good




BREAKING DOWN 3 KEY FACTORS FOR CONSIDERATION



LOCATION

Tape used outside may encounter exposure to sun and unfavorable weather conditions. **Co-extruded** duct tape has an airtight construction which prevents delamination, making it a better choice for outdoor use.





SURFACE

Laminated duct tape is a better choice for uneven or curved surfaces because it is more flexible. Co-extruded duct tape has a stiffer, less-conformable backing.





DURATION

Because co-extruded duct tape is less susceptible to delamination it delivers strong performance for long-term projects that may encounter repeated stress and impact.



WHAT IS **DELAMINATION?**

Delamination occurs when tape layers separate and weaken from a failure of composite materials, typically caused by air or water penetration and repeated stress from exposure to weather elements. The co-extrusion manufacturing process creates airtight construction, eliminating the possibility of delamination.

HOW TO TELL A TAPE IS CO-EXTRUDED:



has a recognizable, dotted appearance

You can also check for a notation on the manufacturer's website or technical literature