

## SHOWA 890

Forged with fluoroelastomer rubber, SHOWA 890 provides superior resistance to highly corrosive acids and is designed for handling aliphatic and aromatic hydrocarbons, such as Benzene, Toulene, and Xylene.

#### **FEATURES** ſ

- Unlined Viton<sup>®</sup> over Butyl
- 28-mil thick
- 14" long
- Smooth grip

### BENEFITS

- Protection against aromatics such as benzene, toluene, xylene
- Excellent barrier to most chlorinated solvents and aliphatic hydrocarbons

#### 

Chemical

Janitorial



#### **Municipal Services**

#### **IDEAL APPLICATIONS** Chemical spray and treatment

- Coating preparation
- Laboratory, pharma & analysis
- Painting & spray workshops
- Washing & cleaning
- Fracking
- Pipe Fitters



#### **TAA PRODUCTS**

#### MATERIAL

Unsupported


#### COATING

- chemical resistant
- Viton
- Water resistant


#### GRIP

• Smooth


#### **STANDARDS**













# CHEMICA



#### USER INSTRUCTIONS

Protection against mechanical risks, with electrostatic properties. Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light. All clothing and shoes worn with the glove with electrostatic dissipation properties must also be designed taking the electrostatic risk into account.

### DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch SHOWA USA | 579 Edison Street - Menlo, GA 30731, USA USA@SHOWAgroup.com © SHOWA Group 2018 | All rights reserved