

# SHOWA 892

Forged with fluoroelastomer rubber, SHOWA 892 provides superior resistance to highly corrosive acids and is designed for handling aliphatic and aromatic hydrocarbons, such as Benzene, Toulene, and Xylene.

## [ FEATURES

- Unlined Viton® over Butyl
- 12-mil thick
- 12" long
- Smooth grip

## [ BENEFITS

- Protection against aromatics such as benzene, toluene, xylene
- Excellent barrier to most chlorinated solvents and aliphatic hydrocarbons

## [ INDUSTRY



Chemical



Laboratory



Manufacturing



Oil and Gas

## [ IDEAL APPLICATIONS

- Chemical spray and treatment
- Coating preparation
- Laboratory, pharma & analysis
- Painting & spray workshops
- Drilling
- Fracking



## TAA PRODUCTS

### MATERIAL

- Unsupported

### COATING

- chemical resistant
- Viton
- Water resistant

### GRIP

- Smooth

### STANDARDS

Cat. III



0299

EN ISO 374-1:2016/Type B



DFL

EN 388:2016



1010X

EN ISO 374-5:2016



VIRUS

# SHOWA 892

**PACKAGING**  
● 1 Pair per polybag

**COLOUR**  
● Black

**SIZES**  
● S  
● M  
● L  
● XL  
● XXL

**THICKNESS**  
● 12 mil



## [ YOU MIGHT ALSO BE INTERESTED IN

SHOWA  
**890**



**MATERIAL**  
Unsupported  
**COATING**  
chemical resistant

SHOWA  
**878**



**MATERIAL**  
Unsupported  
**COATING**  
Butyl

SHOWA  
**874**



**MATERIAL**  
Unsupported  
**COATING**  
Butyl

## [ USER INSTRUCTIONS

## [ DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

**Get in touch**

**SHOWA USA** | 579 Edison Street - Menlo, GA 30731, USA

**USA@SHOWAgroup.com**

© SHOWA Group 2018 | All rights reserved