GOJO PRO[™] TDX[™] 2000 & PRO TDX 5000 DISPENSER INSTALLATION INSTRUCTIONS

These instructions apply to GOJO[®] brand PRO TDX 2000 and PRO TDX 5000 dispensers.

Please carefully read all instructions before installing and using the dispenser.

Screw Mount (Preferred Method) | Recommended for dry wall and stud wall surfaces.



Tape Method

1.

> 4" MINIMUM CLEABANCE

Determine Mounting Position Locate desired position on wall. Allow 4" at bottom and 1" at top of dispenser for proper dearance.



Prepare Tape. Carefully remove paper backing from tape on back of dispenser.



Mount Dispenser. Firmly press closed dispenser on pre-determined location on wall.



Unlatch Cover. Press firmly against back plate to ensure maximum contact of tape with wall surface. Close dispenser.



Wait 24 hours before loading refill.



Place carton into dispenser, slide nozzle into both slots, and close cover.

Adjustable Output

Recommended for cement and concrete block, ceramic tile, steel and other smooth surfaces.



Use flat head screw driver to adjust output as shown.



Call or write GOJO Industries, Inc. for information regarding the adapter kit for mounting dispenser on wash fountains.



GOJO Industries, Inc. One GOJO Plaza, Suite 500 P.O. Box 991 • Akron, OH 44309-0991 Tel: 1-330-255-6000 • Toll-free: 1-800-321-9647 Fax: 1-800-FAX-GOJO