



**F1SUPERIOR** 

MANUFACTURING GROUP, INC.

A step above the commodity entrance mat, Sabre<sup>™</sup> is designed for use in light to medium foot traffic areas. Sabre's<sup>™</sup> durable Decalon<sup>®</sup> fibers provide moisture and dirt retention at entrances, lobbies, and passageways; reducing slip hazards and floor care maintenance. A vinyl non-slip backing helps to minimize mat movement.

Test	Test Description	*Results
ASTM D3884-01	Abrasion Resistance	-1.17 grams (3.7%)
ASTM D6540-00	Accelerated Soiling	Based on Visual Inspection 4.0 - Vacuum Rating 5.0 - Rating After Extraction
ASTM D5252-98a	Accelerated Wear	Based on visual inspection @ 4,000 cycles Considerable change in appearance and color
CPSC FF 1-70 (ASTM D-2859)	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass
-	Water Retention	Weight Gain = .415 gals./yd <sup>2</sup>
		12/2014

\*All testing of NoTrax  $\ensuremath{^\circ}$  floor matting has been performed by an independent testing laboratory.

12/2014

Appearance Rating Key		
5	No change	
4	Slight change	
3	Noticeable change	
2	Considerable change	
1	Severe change	
	1	





- 19 oz. face weight
- Thickness: 5/16"
- Stain resistant, tufted cut-pile Decalon<sup>®</sup> fibers
- Vinyl backing to reduce mat movement
- Stock Sizes: 2' x 3', 3' x 4', 3' x 5', 3' x 6', 3' x 10', 4' x 6', 4' x 8'
- Roll Sizes: 3' x 60', 4' x 60', 6' x 60'
- Custom Sizes: In 3', 4', and 6' widths (up to 60')