## **131** Dante<sup>™</sup> Decalon<sup>®</sup>

Entrance Floor Mat



SUPER

MANUFACTURING GROUP, INC

5



Dante<sup>™</sup> is made with a densely tufted cut-pile Decalon<sup>®</sup> construction that is a step above the look-alikes and provides much greater moisture retention. 24 ounces of tufted yarn per square yard make it the perfect product for all medium traffic areas including entrances and lobbies. A vinyl non-slip backing helps to minimize mat movement.

Test	Test Description	*Results
ASTM D6540	Accelerated Soiling Method	Based on Visual Inspection 4.0 - Vacuum Rating 4.7 - Rating After Extraction
ASTM D412	Breaking Load/Elongation	248.2 lbs/in <sup>2</sup>
ASTM 5252-98a	Accelerated Wear - 4,000 cycles (Hexapod Tumble Drum Tester)	Appearance: 3.3 Color: 3.5
ASTM D3936-05	Delamination	Construction does not allow for Delamination
ASTM D2240-02	Durometer (Hardness)	50
CPSC FF 1-70	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass

\*All testing of NoTrax<sup>®</sup> floor matting has been performed by an independent testing laboratory.

07/2014

Appearance Rating Key		
5	No change	
4	Slight change	
3	Noticeable change	
2	Considerable change	
1	Severe change	

- 24 oz. face weight
- Thickness: 3/8"
- Heavyweight vinyl non-slip backing
- Stock Sizes: 2' x 3', 3' x 4', 3' x 5', 3' x 6', 3' x 10', 4' x 6', 4' x 8'
- Roll Sizes: 3' x 60', 4' x 60', 6' x 60'
- Custom Sizes: In 3', 4', and 6' widths (up to 60')



