











DRM1065 For 55 gal. Steel Drums, FM-Approved, Bolt-Ring

The only latching lid that meets NFPA 30 venting requirements helps you safely contain and lock flammable materials in a 55-gallon steel drum.

- The only latching lid that satisfies NFPA 30 venting requirements
- In a fire, 2" and 3/4" FM Approved nylon plugs melt to vent pressure and prevent drum bursting
- Ideal for safe storage of flammable or combustible solids such as used rags and absorbents
- Latching handle easily opens and closes with one hand
- Nitrile gasket and locking mechanism seal lid to help reduce vapor emissions
- Easy-access lid closes securely to help you meet haz-waste regs
- Hinge stops keep funnel lid upright when open
- Durable, chemical-resistant powder coat helps ensure long service life
- Lockable latch helps prevent unauthorized access
- Hinge pin is made for easy lid removal without loosening band around drum





Item#	Description	Dimensions	Weight
DRM1065-YW	Yellow,	23.25" W x 26.75" L x 4.375" H	25 lbs.
DRM1065-RD	Red,	23.25" W x 26.75" L x 4.375" H	25 lbs.
DRM1065-BK	Black,	23.25" W x 26.75" L x 4.375" H	25 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM1065-YW	Yellow,	59.1cm W x 67.9cm L x	11.3 kg
		11.1cm H	
DRM1065-RD	Red,	59.1cm W x 67.9cm L x	11.3 kg

		11.1cm H
DRM1065-BK	Black,	59.1cm W x 67.9cm L x 11.3 kg
		11.1cm H

Specifications

Special Feature	FM-Approved
Style	Hinged Lid w/ One-Hand Latch
Use With	55 gal. Steel Drums
Dimensions	23.25" W x 26.75" L x 4.375" H
Drum Mounting	Bolt-Ring
Drum Size	55 gal.
Drum Type	Steel Drum
Sold as	1 per box
Weight	25 lbs.
NSN (National Stock Number)	DRM1065-BK-8110-01-595-7372
NSN (National Stock Number)	DRM1065-RD-8110-01-595-7372
NSN (National Stock Number)	DRM1065-YW-8110-01-595-7372
# per Pallet	23
Composition	Lid - Steel Gasket - Nitrile Bungs - Nylon
Padlockable	Padlockable w/ .25" Shackle
UNSPSC	24112112
Pigalog® Page Number	Page 304

Metric Equivalent

Dimensions	59.1cm W x 67.9cm L x 11.1cm H
Weight	11.3 kg

Technical Information

Certifications, Approvals and Ratings

NFPA Code 30

Technical Documents

Nitrile gasket for PIG® Drum lids and funnels

PIG Latching Drum Lid (Steel) Instructions

29 CFR 1910.106(e)(2)(i)

29 CFR 1910.22(a)

40 CFR 261.4

40 CFR 262.15

40 CFR 262.16(b)(2)(iii)

40 CFR 262.17(a)(1)(iv)

40 CFR 264.1086(c)(1)(ii)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com