



OMNIAIRE 600 Nitro

HEPA Air Filtration Machine

ORDERING INFO

OmniAire 600 Nitro	OA600N
OmniAire 600 Nitro GEO w/ MERV 14	OA600NG
Primary/Secondary Two-Stage Filters (box of 20)	OAPI616
HEPA Filter 99.99%, 0.3µ (plastic frame)	OAH15156P
Geo95 MERV 14 Filter	OAG15154
OdorGuard 600 Carbon Filter	OG1616
Quick Clamp, 8"-12" Dia.	QCW12
Flexible Duct, 10" Dia. x 25' L	OADI0
Flexible Duct, Wire & Fiber Reinforced	OADI0R

PART NUMBER



UL 507:1997/R:2017-01
CAN/CSA-C22.2 No. 113-15

The OmniAire Nitro 600 a portable HEPA air scrubber with a variable speed motorized impeller featuring high suction capacity and air flow. It is used for removal of toxic mold, asbestos and lead dust during renovation and abatement projects, and for purifying air in commercial, factory sites and medical facilities. The Nitro can be used with a variety of filters such as HEPA 99.99%, MERV 15, GEO95 high capacity dust filter or an activated carbon filter. Units are safely stackable up to 3 high during operation, transportation, and storage.

OmniAire 600 Nitro

Airflow*	200 - 600 CFM
Power Requirements	115VAC/60 Hz/2.4 Amp
Blower	motorized impeller with thermal overload
Recessed Controls	variable speed control; red power indicator light; amber change filter light; GFI protected outlet (8 Amp load max); 12 Amp breaker
Filtration	HEPA Filter 99.99% 0.3µ; MERV 9 primary/secondary filter Optional: OdorGuard 600 carbon web filter; MERV15 GEO95 filter
Housing	polyethylene; 10" inlet/outlet; soft rubber handle
Size/Weight	19"W x 19"H x 25"L; 36 lbs.

*Airflows based on blower manufacturer curves. Different filters may cause the flow to vary.