





SHOWA

Created with a 19" gauntlet, SHOWA 747 offers premium protection against a wide range of chemicals for various applications.

FEATURES

- Unsupported, unlined
- 100% nitrile
- 22 mil thick
- Bisque grip
- 9" length
- Chlorinated



- Provides chemical resistance against a broad range of solvents, oils, animal fats and other chemicals
- Mechanical resistance
- Bisque finish grip makes wet work easier and safer
- Ergonomic design maximizes comfort

INDUSTRY



Agriculture



Automotive



Chemical



Landscaping



Municipal Services

IDEAL APPLICATIONS

- Chemical spray and treatment
- Light chemical handling in agriculture, horticulture
- Light assembly of oil-coated pieces
- Painting and spray workshops
- Coating preparation
- Washing & cleaning



TAA PRODUCTS

MATERIAL

Unsupported

COATING

- chemical resistant
- Nitrile
- Water resistant

GRIP

Bisque

STANDARDS





EN ISO 374-1:2016/Type A EN ISO 374-5:2016







SHOWA





PACKAGING

- 6 Pair per polybag12 Polybags per case
- 72 Pair per case



SIZES

- h 5
 - M
 - XL



COLOUR

Light green





YOU MIGHT ALSO BE INTERESTED IN





MATERIAL
Coton flock
COATING
Biodegradable





MATERIAL
Unsupported
COATING
Biodegradable

SHOWA **772**



MATERIAL Cotton COATING chemical resistant

SHOWA **717**



MATERIAL
Unsupported
COATING
chemical
resistant

USER INSTRUCTIONS

Protection against mechanical risks, with electrostatic properties. Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light. All clothing and shoes worn with the glove with electrostatic dissipation properties must also be designed taking the electrostatic risk into account.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.