

AMERIC CONFINED SPACE VENTILATOR 2 SPEED
VAF3000A-2

Product Description

Industrial VAF3000A/B – On-demand performance. Ideal for use in confined spaces that require a powerhouse air ventilator, the VAF3000A/B can handle your most demanding industrial needs. With a forceful 1 hp motor, the VAF3000 can deliver both positive and negative airflow at an incredible maximum capacity of 2,796 CFM in the most difficult work environments.

Features

- Industry leading airflow in all sizes, rated from 750-10,000 cfm
- Dual wall polyethylene housing designed to withstand the harshest of conditions, providing years of durability and dependability
- Premium quality motors rated for over 100,000 hours of heavy duty, continuous use for unmatched return on investment
- Safety tested to UL, CSA and CE certifications, exceeding industry standards
- Provides positive and negative airflow (blows and extracts)
- Lightweight for easy portability
- Stackable to save storage space
- Three year warranty
- Made in the USA



Specifications

Blade Color	Black
Brand	Schaefer
Cfm (free Air)	2780
Drive	Direct
Housing Material	Polyethylene
Maximum Duct Length (feet)	125
Phase	1
Speeds	2
Cfm/watt (free Air)	3.6
Cord	Included - Wired
Diameter (inches)	12
Frequency (hz)	60
Guard Color	Black
Nameplate Amps	10/6.7

Number Of Wings	7
Power (hp)	1
Product Dimensions (L X W X H Inches)	21" x 17" x 14"
Product Net Weight (lbs)	33
Performance Test #	0789 / 0790
Switch	On product
Voltage	115
Blade Material	Polypropylene
Cfm (high)	2780
Cfm Calculation Standard	ANSI/AMCA Standard Z30-99
Product Color	Blue
Product Shipping Dimensions (in)	18 x 16 x 24
Able To Ship Small Parcel	Yes
Cfm (low)	1875

Cfm Range (free Air)	2501 - 5000
Cord Length (feet)	20
Distinguishing Feature	Suitable with Ducting
Fixed Or Portable	Portable
Guard Material	Powder Coated Steel
Oscillating	No
Product Certifications	cULus
Rpm 50 Hz Motor	2000-2600
Sound Level (dda @ 10')	82
Country Of Origin	US
Guard Spacing (inches)	1/2 OSHA
Housing Color	Blue
Maximum Static Pressure (in. H2o)	3