







ADVANCED LED TECHNOLOGY FOR THE BEST-IN-CLASS OPTIMAL VISION

- Modes: High Spot, Low Spot, High Flood, Low Flood
- Large push button switch
- Lightweight polymer housing
- Adjustable Mount tilts down to see ground or objects below
- Low profile design fits within most visors and shields
- Strap securely adheres to helmets, hardhats and heads.
- IPx4 rated water-resistant design









185 LUMENS ON HIGH WITH A 6.75 HR RUN TIME! RUNS 20 HRS ON LOW.

HIGH MODE

FL1 STANDARDS	
	
	
	

LOW MODE

FL1 STANDARDS	
	
	
	

SPECIFICATIONS

POWER SOURCE: 3 AA-cell Alkaline Batteries
LAMP: Advanced LED Technology
LIGHT OUTPUT: 185 Lumens on High Mode, 65 Lumens on Low Mode
PEAK BEAM INTENSITY: 7,000 candela
BEAM DISTANCE: 65 Meters on High Mode, 35 Meters on Low Mode
WEIGHT: 3.5 oz. with Batteries
LENGTH: 24 in. **WIDTH:** 1.4 in. **HEIGHT:** 1.8 in.
KBS MODEL: #200501 Hi-Vis Green
UPC#: 016731205010

SAFETY RATINGS

Intrinsically Safe
 UL Protection Methods
 UL 913 CSA C22.2
 Class I, II, III Div 1 C-G
 Class I, II, III Div 2 C-G
 T4



See it all.™

