

# CORTEGA® Second Look®

Tegular  
medium texture



**SUSTAIN®**  
High Performance  
Sustainable  
Ceiling Systems



▲ Cortega® Second Look® II panels with Suprafine® XL® 9/16" suspension system

Medium-texture panels; Economical solution with standard acoustical absorption.

## KEY SELECTION ATTRIBUTES


- Cortega® Second Look® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Economical
- Geometric Scored Visuals

## COLOR




White  
(WH)

## FACE VIEWS




Cortega® Second Look® I panels –  
Scoring creates nominal 12" x 12" squares



Cortega® Second Look® II panels –  
Scoring creates nominal 24" x 24" squares

## DETAIL



Cortega® Second Look®

# CORTEGA® Second Look®

Tegular  
medium texture



Declare

GREENGUARD Gold Certified (details below)

LEED® WELL™ LBC  
UP TO 55% RECYCLED CONTENT

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/excimer producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

Calculate sustainability with GreenGenie™ [armstrongceilings.com/greengenie](http://armstrongceilings.com/greengenie)

LOCATION DEPENDENT

## VISUAL SELECTION

## PERFORMANCE SELECTION

\$\$\$\$

armstrongceilings.com/catdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	
CORTEGA® Second Look® I	11	2765	24 x 48 x 3/4"	
15/16" Angled Tegular				

UL Classified Acoustics	Total Acoustics <sup>1</sup>	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
NRC + CAC =										
0.55 + 35 =	N/A	Class A	0.81	N/A	Std	•	Std	Std	•	1-Yr

CORTEGA® Second Look® II	11	2758	24 x 48 x 3/4"	
15/16" Angled Tegular				

0.55 + 40 =	N/A	Fire Guard	0.81	N/A	Std	•	Std	•	•	1-Yr
-------------	-----	------------	------	-----	-----	---	-----	---	---	------

2767	24 x 48 x 3/4"	
------	----------------	--

0.55 + 35 =	N/A	Class A	0.81	N/A	Std	•	Std	•	•	1-Yr
-------------	-----	---------	------	-----	-----	---	-----	---	---	------

9/16" Angled Tegular	27	2776	24 x 48 x 3/4"	

0.55 + 30 =	N/A	Class A	0.81	N/A	Std	•	Std	•	•	1-Yr
-------------	-----	---------	------	-----	-----	---	-----	---	---	------

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

## SUSPENSION SYSTEMS



## PHYSICAL DATA

Cortega®/Coretega Second Look®: wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

Fire Guard: A fire-resistant ceiling when used in applicable UL assemblies

**ASTM E1264 Classification**  
Type III, Form 2, Pattern C D K

**Humidity/Sag Resistance**  
Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

**VOC Emissions**  
(PB suffix items only)  
GREENGUARD Gold Certified  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Primary (Embodied) Energy**  
See all LCA information on our EPDs.

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS  
UL.COM/GG  
UL 2818



**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Insulation Value**  
2765, 2758, 2767, 2776 – R Factor – 1.5 (BTU units);  
R Factor – 0.28 (Watts units)

**Weight; Square Feet/Carton**  
2765, 2767 – 0.73 lbs/SF; 80 SF/ctn  
2758 – 1.26 lbs/SF; 64 SF/ctn  
2776 – 0.70 lbs/SF; 80 SF/ctn

**Minimum Order Quantity**  
1 carton

TechLine / 1 877 276-7876  
[armstrongceilings.com/cortega](http://armstrongceilings.com/cortega)  
BPCS-3022-722

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute®; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL and UL Certified are trademarks of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2022 AWI Licensing LLC



MINERAL FIBER – Standard

