

Technical Data Sheet

KLEENGUARD* A10 Light Duty Coveralls

Product Information

Zipper Front, Elastic Wrists	Code	Size	Quantity
	10468	L	25
P	10636	XL	25
$\omega \cup \omega$	10616	2XL	25
/ / \	10625	3XL	25
/ / \ \	10621	4XI	25

Zipper Front, Elastic Wrists, Attached Hood	Code	Size	Quantity
	12231	L	25
	12225	XL	25
	12226	2XL	25
010	12227	3XL	25
(/\)	12230	4XL	25

Zipper Front, Elastic Wrist, Hood & Boots	Code	Size	Quantity
	10601	L	25
	10608	XL	25
(T)	10631	2XL	25
Q İ Ø	10610	3XL	25
11/17	10615	4XL	25
)	•		•

Fabric Properties

Physical Properties	Results	Test Method
Tensile Strength – MD	24.6 lbs	STM 5668
Tensile Strength – CD	16.0 lbs.	STM 5668
Trapezoidal tear - MD	4.8 lbs.	
Trapezoidal tear - CD	9.2 lbs.	

Barrier Properties	Results	Test Method
Hydrohead	48cm	STM 4507

Comfort Properties	Results	Test Method
Air Permeability	43 cfm	STM 3801

Additional Attribites

- Breathable SMS polypropylene material
- Non-latex polyisoprene elastic
- No silicone, no BHT preservative

Meets ANSI/ISEA 101-1996 sizing standards
Serged Seams
No zipper flap; zipper teeth exposed

Workmanship Requirements

Coveralls shall be made in accordance with reasonable industry practice with respect to holes, tears, wrinkles, cleanliness, and foreign materials or dirt.

For additional information: 1-888-346-4652 or kimtech@kcc.com



