

Recycled Content: **Up to 51%**

armstrong.com/greengenie

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views
	✓	✓	✓	✓	

Location Dependent

LEED for Schools

Acoustics	Low Emitting or CHPS
	✓

CORTEGA® Second Look®

Scored Tegular
medium texture



\$\$\$\$\$

Key Selection Attributes

- Geometric scored visuals
- Economical

Typical Applications

- Many types of commercial interiors
- Discount stores/retail

Detail




CORTEGA
Second Look
Squares

Color



White (WH)

Face View Photos



Second Look I scoring creates nominal 12" x 12" squares



Second Look II scoring creates nominal 24" x 24" squares



Cortega Second Look II with Suprafine® 9/16" Exposed Tee grid (Pg. 220)

Visual Selection

Performance Selection Dots represent highest level of performance.

Edge Profile	Suspension Detail Dwg. Pgs. 226-228	Item No.	Dimensions	UL Classified		Light Reflect	Sag Resist	Anti-Microbial	Durable	Recycle Program	
				Acoustics NRC	Fire Rating						
CORTEGA Second Look I											
15/16" Angled Tegular	5	2765	2' x 4' x 3/4"	0.55	35	Class A	0.82	Standard	-	Standard	Yes
		2765M	600 x 1200 x 19mm								
CORTEGA Second Look II											
9/16" Angled Tegular	28	2776	2' x 4' x 3/4"	0.55	30	Class A	0.82	Standard	-	Standard	•
15/16" Angled Tegular	5	2758	2' x 4' x 3/4"	0.55	40	Fire Guard	0.82	Standard	-	Standard	•
15/16" Angled Tegular	5	2767	2' x 4' x 3/4"	0.55	35	Class A	0.82	Standard	-	Standard	•
		2767M	600 x 1200 x 19mm								

Suspension Systems



Physical Data

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled) Fire Guard™: A fire resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification
Type III, Form 2, Pattern C D K
Fire Class A

VOC/Formaldehyde Emissions
Meets CA Dept. of Health Services Standard Practice for the testing of VOC Emissions and is listed on CHPS High Performance Products Database for Low-Emitting Materials.

Insulation Value
R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

Warranty Information
See warranty details in the back of this catalog

Weight; Square Feet/Carton
2765, 2767, 2776 – 0.70 lbs/SF; 80 SF/ctn
2758 – 1.20 lbs/SF; 64 SF/ctn