

DEF DRUM PUMP 6GKR1

TECHNICAL data sheet

DEF PUMP PACKAGE

DEF pump packages are engineered to transfer AdBlue (AUS32) Diesel Exhaust Fluid (DEF) directly from barrels, drums and Intermediate Bulk Containers (IBC). Packages include sealless pump, variable speed motor, dispensing nozzle (manual or auto-shut off), compatible hose and barrel adapter.

APPLICATIONS

- Diesel Exhaust Fluid

TECHNICAL SPECIFICATIONS	
Package	Motor, Pump, Hose, Barrel Adapter & Hand Nozzle
Motor Type	Open Drip Proof (IP 44)
Wetted Parts	SS316, PTFE, Polypropylene, Carbon, EPDM
Pump Length	39" (1000 mm) (Drums)
Discharge Hose	CarboBlue, 8ft (2,4 m), 3/4" (19 mm) I.D
Hand Nozzle	Auto-Shut Off, SS316
Maximum Flow Rate	11 GPM (41 LPM)
Maximum Viscosity	1500 cps (mPas)
Maximum Temperature	130° F (55° C)
Shipping Weight	28 lbs. (12, 72 kg)
Package Number	6GKR1
Motor	1DLK6
Volts	110v
Pump Tube	6GKR1

