


# Hook-Face

# Random Orbital Sanding Pads

## With Dynabrade's Exclusive Single-Piece Hub Design!

- Exclusive single-piece hub design reduces pad vibration and ensures smooth performance.
- PREMIUM URETHANE Sanding Pads are perfectly weight-mated to Dynabrade tools, for achieving consistent **swirl-free finishes**.


Ask for the **ORANGE!**



### Hook-Face Pads


Short nap pads for use with reattachable discs.

Long nap pads for use with non-woven nylon discs.




### Non-Vacuum Pads

High quality backup pad. Weight-mated for smooth running and minimal tool vibration.



### Vacuum Pads

Holes are precisely located to achieve proper alignment with abrasive discs, for optimum vacuum capabilities.



### Channel Vacuum Pads

1/8" (3 mm) deep recessed channel. No need to align abrasive holes with pad holes!

## Non-Vacuum Pads

| Pad Diameter   | Part Number | Thickness    | Nap   | Density    |
|----------------|-------------|--------------|-------|------------|
| 3" (76 mm)     | 56087       | 5/8" (16 mm) | Short | Medium     |
|                | 56090       | 5/8" (16 mm) | Long  | Medium     |
|                | 56145       | 1/2" (13 mm) | Short | Medium     |
| 3-1/2" (89 mm) | 54311       | 5/8" (16 mm) | Short | Soft       |
|                | 54313       | 5/8" (16 mm) | Short | Hard       |
|                | 54314       | 5/8" (16 mm) | Long  | Medium     |
| 5" (127 mm)    | 54325       | 3/8" (10 mm) | Short | Medium     |
|                | 56157       | 3/8" (10 mm) | Short | Soft       |
|                | 56180       | 5/8" (16 mm) | Short | Medium     |
|                | 56195       | 5/8" (16 mm) | Short | Soft       |
| 6" (152 mm)    | 56271       | 1/2" (13 mm) | Short | Extra Soft |
|                | 54327       | 3/8" (10 mm) | Short | Medium     |
|                | 56103       | 3/8" (10 mm) | Short | Medium     |
|                | 56107       | 3/8" (10 mm) | Short | Soft       |
|                | 56158       | 3/8" (10 mm) | Short | Soft       |
| 8" (203 mm)    | 56177       | 5/8" (16 mm) | Short | Medium     |
|                | 56182       | 5/8" (16 mm) | Short | Medium     |
|                | 56187       | 5/8" (16 mm) | Short | Soft       |
|                | 56197       | 5/8" (16 mm) | Short | Soft       |
|                | 56236       | 3/8" (10 mm) | Short | Medium     |

All Pads: 13,000 RPM maximum operating speed; 5/16"-24 male thread.

## Channel Vacuum Pads

| Pad Diameter | Part Number | Holes | Thickness    | Nap   | Density |
|--------------|-------------|-------|--------------|-------|---------|
| 5" (127 mm)  | 56250       | 5     | 3/8" (10 mm) | Short | Medium  |
|              | 56253       | 5     | 3/8" (10 mm) | Short | Soft    |
|              | 56255       | 5     | 5/8" (16 mm) | Short | Medium  |
|              | 56257       | 5     | 5/8" (16 mm) | Short | Soft    |
| 6" (152 mm)  | 56260       | 6     | 3/8" (10 mm) | Short | Medium  |
|              | 56263       | 6     | 3/8" (10 mm) | Short | Soft    |
|              | 56265       | 6     | 5/8" (16 mm) | Short | Medium  |
|              | 56267       | 6     | 5/8" (16 mm) | Short | Soft    |

## Vacuum Pads

| Pad Diameter    | Part Number | Holes | Thickness    | Nap   | Density    |
|-----------------|-------------|-------|--------------|-------|------------|
| 3" (76 mm)*     | 56087       | 0     | 5/8" (16 mm) | Short | Medium     |
|                 | 56090       | 0     | 5/8" (16 mm) | Long  | Medium     |
|                 | 56142       | 6     | 1/2" (13 mm) | Short | Medium     |
| 3-1/2" (89 mm)* | 54311       | 0     | 5/8" (16 mm) | Short | Soft       |
|                 | 54313       | 0     | 5/8" (16 mm) | Short | Hard       |
|                 | 54314       | 0     | 5/8" (16 mm) | Long  | Medium     |
| 5" (127 mm)     | 54326       | 5     | 3/8" (10 mm) | Short | Medium     |
|                 | 56155       | 5     | 3/8" (10 mm) | Short | Soft       |
|                 | 56181       | 5     | 5/8" (16 mm) | Short | Medium     |
|                 | 56196       | 5     | 5/8" (16 mm) | Short | Soft       |
|                 | 56240       | 6     | 3/8" (10 mm) | Short | Medium     |
|                 | 56320       | 44    | 3/8" (10 mm) | Short | Medium     |
| 6" (152 mm)     | 56272       | 5     | 1/2" (13 mm) | Short | Extra Soft |
|                 | 54328       | 6     | 3/8" (10 mm) | Short | Medium     |
|                 | 56156       | 6     | 3/8" (10 mm) | Short | Soft       |
|                 | 56183       | 6     | 5/8" (16 mm) | Short | Medium     |
|                 | 56198       | 6     | 5/8" (16 mm) | Short | Soft       |
|                 | 56321       | 52    | 3/8" (10 mm) | Short | Medium     |
| 8" (203 mm)     | 56322       | 48    | 3/8" (10 mm) | Short | Medium     |
|                 | 56327       | 8     | 3/8" (10 mm) | Short | Medium     |

All Pads: 13,000 RPM maximum operating speed; 5/16"-24 male thread.

\*NOTE: Our 3" (76 mm) and 3-1/2" (89 mm) pads, without holes, can be used for vacuum sanding. Vacuum pick-up is around periphery of pad.

## 15-Hole Vacuum Pad\*

| Pad Diameter | Part Number | Holes | Thickness    | Nap   | Density |
|--------------|-------------|-------|--------------|-------|---------|
| 6" (152 mm)  | 54331       | 15    | 5/8" (16 mm) | Short | Medium  |
|              | 56297       | 15    | 3/8" (10 mm) | Short | Medium  |

\*NOTE: This pad has unique "8+6+1" hole pattern.

It accepts 6" (152 mm) diameter abrasive discs with these hole patterns:

- 6-Hole • 6+1 • 8+1 • 8+6+1 • 21-Hole • Mesh or Multi-Hole