

EYE/FACEWASH

PARTS

SERVICE

KNOWLEDGE

SELF-CONTAINED



QUALITY



INNOVATION

Encon[®]
SAFETY PRODUCTS

SHOWER, EYEWASH & FACEWASH PRODUCTS

Encon[®] — The Industry Leader in Emergency & Safety Irrigation Equipment

LEADERS

SOLUTIONS

EXCELLENCE



SAFETY



No. 1

PRODUCT INDEX

00014337	17	01045501	2	01052123	17	01090102	7
01030101	3	01045501PBC	3	01052129	17	01090103	7
01030302	3	01045501SBC	3	01052130	17	01103002	6
01030401	2	01045502	3	01052132	17	01103007	6
01030403	3	01045506PBC	3	01052133	17	01104002	6
01030415	3	01045507	3	01052149	16	01104050	5
01030410	3	01045509	3	01052185	17	01104055	5
01035402	3	01050207	12	01052189	17	01104070	5
01035410	3	01050208	12	01052197	17	01105003	17
01035501	2	01050210	14	01052207	17	01105005	17
01035503	3	01050216	12	01052208	17	01106001	6
01035509	3	01050217	12	01052212	17	01106002	6
01035510	3	01050228	14	01052382	12	01110096	17
01035511PBC	2	01050230	13	01052500	10	01110302	4
01035601	3	01050234	13	01052501	15	01110462	17
01038401	3	01050251	12	01052502	15	01110700	4
01038901	3	01050260	12	01052507	10	01110764	5
01040106	11	01050265	12	01052518	10	01110786S	5
01040112	11	01050266	12	01052520	10	01110786C	5
01040121	9	01050317	15	01054003	17	01110793S	5
01040123	9	01050357	15	01054005	17	01110793C	5
01040125	9	01050362	15	01055005	17	01110787	5
01040127	9	01050374	13	01055007	17	01112428	10
01040128	9	01050471	13	01060007	14	01112429	10
01040130	8	01050472	13	01060009	14	01112470	10
01040133	8	01052018	17	01060011	14	01112911	16
01040139	11	01052020	17	01060021	14	01112951	16
01040140	11	01052083	17	01060022	14	01112953	16
01040141	11	01052098	17	01060023	14	02111000	16
01040142	11	01052101	17	01060024	14	AQ 100	4
01045001	2	01052103	17	01080024	16	AQ 100H1	4
01045001PBC	3	01052111A	17	01090007	7	AQ 120	4
01045002	3	01052113	17	01090008	7	STU1	16
01045006	3	01052114	17	01090009	7	TF12B4777200	18
01045015	3	01052122	17	01090012	8	TF16B2300300	18

LIMITED WARRANTY STATEMENT

ENCON HEREBY DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT OF THIRD-PARTY RIGHTS, EXCEPT AS HEREINAFTER PROVIDED.

Encon warrants that for one year from the date of purchase of any Encon products, the product will be free of defects in materials and workmanship if properly used and cared for or cleaned under normal conditions in accordance with Encon's use and care instructions and properly installed, if applicable, in accordance with Encon's installation instructions. With respect to the product, Encon's only obligation and purchaser's exclusive remedy under this warranty is to repair or replace such product; provided that 1) Encon is notified of the defect within one year of shipment, and 2) the product is determined by Encon to be defective. Encon requires proof of original ownership as proof of warranty coverage, and Encon must receive any claim under this Limited Warranty within one year of purchase of the product.

NOTWITHSTANDING ANYTHING TO THE CONTRARY CONTAINED HEREIN, ENCON SHALL NOT BE LIABLE FOR LOSS, DAMAGE, OR EXPENSE ARISING DIRECTLY OR INDIRECTLY AS A CONSEQUENCE OF USE OF THE EQUIPMENT WITH OTHER PRODUCTS OR FROM ANY

OTHER CAUSE, INCLUDING ANY CONSEQUENTIAL, INCIDENTAL, SPECIAL OR EXEMPLARY DAMAGES, EXCEPT FOR ENCON'S OBLIGATION TO REPAIR OR REPLACE DEFECTIVE PRODUCTS AS EXPRESSLY PROVIDED IN THIS STATEMENT.

Replacement parts purchased from Encon are warranted for one year following the shipment of such replacement part or until the expiration of the warranty period for the product, whichever is less. No warranty is given in connection with products that are altered without Encon's express written consent. The same warranty limitations and the obligations of Encon as set out herein above shall apply to replacement parts.

Encon's total liability arising out of this warranty (including, but not limited to, warranty claims) regardless of forum and regardless of whether such action or claim is based on tort, contract or otherwise will not exceed the total purchase price of the product.

Contents

Eye/Facewashes	pg. 2
Self-Contained	
Aquarion®	pg. 4
Gravity Fed Units	pg. 5
Pressurized Units	pg. 6
Laboratory	
Hose Stations	pg. 7
Counter-Mounted Eyewashes	pg. 8
Recessed Showers & Combinations	pg. 10
Recessed Eyewashes	pg. 11
Combination Shower/Eyewashes	
Yello-Bowl® Models	pg. 12
Stainless Steel Bowl Models	pg. 13
PVC Models	pg. 14
Corrosion-Resistant Models	pg. 14
Freeze-Resistant Models	pg. 15
Showers	pg. 15
Shower Accessories	pg. 16
Parts	pg. 17
Therma-Flow® Freeze Protected Showers	pg. 18

Key

BCP	Brass Chrome-Plated	FTR	Foot Treadle
BF	Barrier Free	FW	Facewash
CP	Chrome-Plated	PBC	Plastic Bowl Cover
DH	Drench Hose	PT	P-trap
EFW	Eyewash & Facewash	SBC	SS Bowl Cover
EW	Eyewash	SS	Stainless Steel

EYE/FACEWASH

MOUNTING

Wall mounted, supply pipe mounted, and pedestal mounted

PIPING & VALVE

1/2" BCP piping; 1/2" CP bronze, stay-open ball valve with CP ball, SS valve stem and push plate with actuation graphic; pedestal option – SS or schedule 80 galvanized piping

HEADS

- ABS plastic heads, Wye and float off covers secured with SS bead chains (optional BCP Wye); self-adjusting regulators to flow at EW–3.2 gpm (12.1 lpm)* and FW–8.0 gpm (30.3 lpm)* for FW
- Acetal EW heads with hinged covers, BCP Wye; self-adjusting regulators to flow at 2.4 gpm (9.1 lpm)*

BOWL CHOICES

- High visibility ABS plastic Yello-Bowl®, 10.8" diameter
- 304 SS bowl, 10.6" diameter

BOWL COVER OPTION

High visibility yellow, corrosion-resistant ABS; push

NOTE All Encon facewashes also meet the ANSI Z358.1 requirements of an eyewash.

*Varying hydraulic conditions of 30 to 70 psi (206.8 to 482.6 kPa)

plate actuator opens cover; manually closing cover is independent of water flow actuator

304 SS; Push plate actuator opens cover; manually closing cover is independent of water flow actuator

Plastic bowl and stainless steel bowl covers are available on all models with BCP Wyes. Add "PBC" (Plastic Bowl Cover) or "SBC" (Stainless Steel Bowl Cover) to the suffix when ordering.

SUPPLY

1/2" NPT connection

BOWL WASTE CHOICES

- ABS Bowl: 1 1/4" x 6" (3.17 cm x 15.24 cm) slip joint tailpiece
- 304 SS bowl has 1-1/4" NPT connection
- P-trap — 1 1/4" slip tube connection

DRENCH HOSE OPTION

Provides partial body flushing

6' (182.9 cm) synthetic rubber hose assembly and mounting bracket

Yellow ABS plastic single-stream head and float off cover secured by SS bead chain; self-closing lock-open squeeze handle

APPROX. SHIP WEIGHT

6 lbs (2.72 kg) approx.
25 lbs (11.34 kg) w/pedestal

7"X11" SIGN INCLUDED

WALL-MOUNTED EYE/FACEWASH

Model: 01035501

- ABS Heads/Wye
- Yello-Bowl®
- Eyewash is Model 01030401



WALL MOUNTED EYEWASH

Model: 01045001

- Acetal Heads
- BCP Wye
- SS Bowl
- Eye/facewash is Model 01045501



PLASTIC BOWL COVERS

- High Visibility Yellow ABS
- Available with Yello-Bowl® & SS Bowl Models with BCP Wyes
- Model Shown 01035511PBC



STAINLESS STEEL BOWL COVERS

- 304 SS
- Available on All SS Bowl Models
- Model Shown 01045501SBC




U.S. Patent No. 5,008,963

EYE/FACEWASH

PEDESTAL MOUNTED EYEWASH

Model: 01030302

- ABS Heads/Wye
- Yello-Bowl®
- Eye/facewash is Model 01035402



Drench Hose Added

Model: 01035410



PEDESTAL MOUNTED EYE/FACEWASH

Model: 01045502

- ABS Heads
- BCP Wye
- SS Bowl
- Eyewash Model 01045002



Foot Treadle & Plastic Bowl Cover Added

Model: 01045506PBC



WALL-MOUNTED

MODEL	DESCRIPTION
01030401	EW, ABS Heads/Wye, Yello-Bowl®
01035501	FW, ABS Heads/Wye, Yello-Bowl® (shown)
01030101	EW, ABS Heads/Wye, Supply Pipe Mount, No Bowl
01035601	FW, ABS Heads/Wye, Supply Pipe Mount, No Bowl
01030403	EW, ABS Heads/Wye, ST, Yello-Bowl®
01035503	FW, ABS Heads/Wye, ST, Yello-Bowl®
01030415	EW, Acetal Heads, BCP Wye, Yello-Bowl®
01035509	FW, ABS Heads, BCP Wye, Yello-Bowl®
01030410	EW, ABS Heads/Wye, PT, Yello-Bowl®
01035510	FW, ABS Heads/Wye, PT, Yello-Bowl®
01038401	EW, ABS Heads/Wye, PVC Piping, Yello-Bowl®
01038901	FW, ABS Heads/Wye, PVC Piping, Yello-Bowl®
01045001	EW, Acetal Heads, BCP Wye, SS Bowl (shown)
01045001PBC	EW, Acetal Heads, BCP Wye and Plastic Bowl Cover, SS Bowl
01045015	EW, SS Heads, SS Wye, SS Piping & Valve, SS Bowl
01045501	FW, ABS Heads, BCP Wye, SS Piping & Valve, SS Bowl
01045501SBC	FW, ABS Heads, BCP Wye and SS Bowl Cover, SS Bowl (shown)
01045507	FW, ABS Heads, BCP Wye, SS Bowl

PEDESTAL MOUNTED

MODEL	DESCRIPTION
01030302	EW, ABS Heads/Wye, Yello-Bowl® (shown)
01035402	FW, ABS Heads/Wye, Yello-Bowl®
01035410	FW, ABS Heads/Wye, Yello-Bowl®, Drench Hose (shown)
01045002	EW, Acetal Heads, BCP Wye, SS Bowl
01045502	FW, ABS Heads/Wye, SS Bowl (shown)
01045506	FW, ABS Heads/Wye, SS Bowl, Foot Treadle
01045506PBC	FW, ABS Heads, BCP Wye, SS Bowl, Foot Treadle, PBC (shown)
01045509	FW, ABS Heads, BCP Wye, ST, SS Piping/Valve, SS Bowl
01045509	Foot Treadle assembly (if ordered separately)

NOTE Foot Treadles available on all models.



Every model in this section includes 7" x 11" sign (17.8 cm x 27.9 cm)

SELF-CONTAINED

COVER

Yellow ABS for protection of fluid bags and internal cavity of the station; Side windows for visual inspection of the fluid bags without removal of the cover

BACK PLATE

Polycarbonate to support the eyewash station with filled cartridges; Mounting slots spaced to screw to wall studs between 12 and 20 inches apart, a solid bearing frame or by using a retaining strap through molded slots around a support behind the plate formed to fit a 4 to 8 inch wide beam

TRAY & NOZZLES

Retracting tray to protect the nozzles from the environment; Single pull down motion pierces seals in the hoses allowing the fluid to flow immediately from the attached nozzles; Collects spent fluid and directs it to an integral drain port for future disposal; Usage indicator tie breaks upon actuation showing that the unit has been used. Enclosed ABS plastic heads connect to retracting tray; non-injurious, dual stream of water at 0.4 gpm (1.5 lpm)

BASE

Black ABS base slides onto the back plate positioned and held through four retaining hooks, fastened with supplied self threading bolts if desired; Base provides structure to the station and holds the nozzle tray in an upright, ready to use position

FLUID BAGS

Self-evacuating flexible bags keep the flushing fluid fresh and clean for reliable performance and maintenance free service ; Two hand slots allow for easy handling and mounting into the station by one person

SHIP WEIGHT

28 lbs (12.7 kg)
70 lbs (31.75 kg) fluid Bags

TRANSPORT CART

Weight—66 lbs (29.94 kg)
Height—60" (to top bar)
Height—38" (to handlebars)
Width—28½" (wheel to wheel)

MODEL

DESCRIPTION

AQ 100	Aquarion® Eyewash Station (shown)
AQ 100H1	Heated Aquarion® Eyewash Station
AQ 120	Aquarion® Fluid Bags
01110302	Transport Cart only
01110700	Transport Cart and Receptacle

AQUARION®

Model: AQ100

- Self-contained eyewash unit only

Fluid cartridges (ordered separately from eyewash unit):

- AQ120 Aquarion® Fluid Bags



Shown with optional cart and waste receptacle.



Heated Aquarion®



Shown with cover removed and tray down for visual inspection

U.S. Patent No. 7,254,848 , 7,082,627 and other patents pending

GRAVITY FED EYEWASH

Model: 01104050

- Gravity Fed Eyewash
- Transport Cart
- Waste Receptacle
- As shown with Cart is Model 01104055



One bottle of Hydrosep® included.

HYDROSEP®

Model: 01110764

- Water preservative
- 90-day service use
- One Bottle Included with each Encon Self-Contained Eye Wash Station
- Reorder includes 4, 8oz. Bottles



HEATED GRAVITY FED EYEWASH

Model: 01104070

- C1D2 Gp. BCD
- Voltage – 120 VAC
- Hertz – 60 Cycles
- Phase – Single
- Amps – 3.5 Max.
- Includes Insulation Jacket



One bottle of Hydrosep® included.



C1D2 Gp. BCD
LR83818

FIRSTSTEP® FIRSTFLUSH®

Model: 01110786S

- Single Station Unit
- 32oz. Isotonic Buffered Solution
- See Model 01110793S for Dual Station Unit



SELF-CONTAINED

GRAVITY FED EYEWASH

TANK

High visibility yellow polyethylene; two carrying handles; operation and maintenance instructions on front graphics
EW fill—15 min., 14 gal.;
Height—24"; Width—20";
Depth—9½"

EYEWASH

Enclosed ABS plastic heads integral to hinged drain tray; non-injurious, dual stream of water at 0.4 gpm (1.5 lpm)

FILL WEIGHT

138 lbs (62.6 kg), 15 min. fill
19 lbs (8.61 kg), empty

RECEPTACLE

Weight—1.4 lbs (6.35 kg)
Height—22½"
Width—21½"

TRANSPORT CART

Weight—66 lbs (29.94 kg)
Height—60" (to top bar)
Height—38" (to handle-bars)
Width—28½"
(wheel to wheel)

HEATED OPTION

INSULATION JACKET

Waterproof, highly visible PVC coated nylon Thinsulate®

ELECTRICAL CONNECTION

9 foot S.O.W. 16 gauge, 3-wire cord without plug; explosion-proof connection assembly required if applicable; Voltage—120 VAC; Hertz—60 cycles; Phase—single; Amps—3.5 maximum

SHIP WEIGHT

32 lbs (14.52 kg)

MODEL

DESCRIPTION

01104050	Gravity Fed Eyewash
01104055	Gravity Fed Eyewash with Cart & Receptacle (shown)
01110302	Transport Cart
01110700	Transport Cart with Waste Receptacle
01104070	Hazardous Area C1D2 Gp. BCD Heated Gravity Fed Eyewash (shown)
01110764	Hydrosep® reorder, – 4 ea., 8oz. Bottles

FIRSTSTEP® FIRSTFLUSH®

DETAILS

32oz. buffered isotonic saline solution preserved with Hydrosep®; single or dual bottle stations

Highly visible yellow ABS plastic holder with operational instructions; vibration and UV resistant

PACKAGING

HDPE, durable, non-resealable bottle; large, full flow opening for rapid irrigation

SHIP WEIGHT

Single stations (case of 6) – 20 lbs (9.07 kg)
Dual stations (case of 3) – 20 lbs (9.07 kg)
Replacement bottles (case of 12) – 27 lbs (12.25 kg)

MODEL

DESCRIPTION

01110786S	Single Wall Mounted Unit, Each (shown)
01110786C	Single Wall Mounted Unit, Case of 6
01110793S	Dual Wall Mounted Unit, Each
01110793C	Dual Wall Mounted Unit, Case of 3
01110787	Replacement Bottles, Case of 12

SELF-CONTAINED

13-GALLON PRESSURIZED

PIPING & VALVES

1/2" BCP piping; option with 8' coiled hose; 1/2" CP bronze stay-open ball valve with CP ball; SS valve stem; SS push plate with actuation graphic

RELIEF VALVE

Brass; automatically opens at 115 psi

GAUGE

Custom face gauge visually indicates tank pressure status

EYEWASH

ABS plastic heads and BCP Wye with SS bead chains securing covers; self-adjusting 0.4 gpm (1.5 lpm)

WATER TREATMENT ADDITIVE

Each bottle treats 5 to 20 gallons for up to 180 days

TANK

304 SS, ASME & CRN rated vessel with 13-gallon capacity

SHIP WEIGHT

32 lbs (14.52 kg)
34 lbs (15.42 kg) with drench hose

MODEL DESCRIPTION

01103002	Socket Style Mount with Hose
01103007	Fixed EW without Hose
01104002	EW with Drench Hose (<i>shown</i>)
01110764	Hydrosep®, 4 - 8oz. Bottles

NOTE Heated options available on 13-gallon Units

13-GALLON PRESSURIZED

Model: 01104002

- Eyewash with Drench Hose

Option

Model: 01104002

Model: 01103008 for Yellow Cart




One bottle of Hydrosep® included.

37-GALLON PRESSURIZED

PIPING & VALVES

1/2" BCP piping; 1/2" CP bronze stay-open ball valve with CP ball; SS valve stem; SS push plate with actuation graphic

WATER TREATMENT ADDITIVE

Two bottles of 8oz. Hydrosep®; each bottle treats 5 to 20 gallons for 180 days

EYEWASH

ABS plastic heads and BCP Wye with SS bead chains securing covers; self-adjusting 0.4 gpm (1.5 lpm)

DRENCH HOSE OPTION

Valve
3/8" BCP, self-closing, lock-open handle

Head
Solvent-resistant ABS single spray head; self-adjusting 5.0 gpm (18.75 lpm)

TANK

37-gallon is ASME.

RELIEF VALVE

Brass; automatically opens at 115 psi

CART OPTION WITH 37-GALLON MODEL

Tubular steel with retaining chains

GAUGE

Custom face gauge visually indicates tank pressure status

SHIP WEIGHT

160 lbs (72.6 kg)

MODEL DESCRIPTION

01106001	EW with Drench Hose, Cart (<i>shown</i>)
01106002	EW with Drench Hose, No Cart
01110764	Hydrosep®, 4 - 8oz. Bottles

37-GALLON PRESSURIZED

Model: 01106001

- Eyewash with Drench Hose
- Dolly Cart
- Model without Dolly Cart: 01106002




Two bottles of Hydrosep® included.

HYDROSEP®

Model: 01110764

- Water preservative
- Up to 180-day service use
- Reorder includes 4, 8oz. Bottles



EYE/FACEWASH HOSE STATION

Model: 01090102

- ABS Heads
- BCP Wye
- 6' Coiled Hose
- Eyewash is Model 01090103



DRENCH HOSE

Model: 01090008

- ABS Head
- Lock-open Squeeze Handle
- 6' Hose
- Wall Mounting with Bracket
- Counter Mounting with Flange, is 01090009



Push Plate Option

Model: 01090007



LABORATORY

HOSE STATION

VALVE

1/2" CP bronze stay-open ball valve and CP ball with SS valve stem and push plate with actuation graphic

HOSE

6' (182.9 cm) coiled hose, stores neatly when not in use, wall bracket included

EYEWASH OPTION

Acetal eyewash heads with hinged covers, BCP Wye; self-adjusting regulators to flow at 2.4 gpm (9.1 lpm)*; supply pipe mount

SUPPLY

1/2" NPT connection

SHIP WEIGHT

6 lbs (2.72 kg)

EYE/FACEWASH OPTION

ABS plastic heads and float off covers secured with SS bead chains, BCP Wye; self-adjusting regulator to flow at 8.0 gpm (30.3 lpm)*; wall mount

MODEL DESCRIPTION

01090102 FW Hose Station, Wall Mounting (shown)

01090103 EW Hose Station, Supply Pipe Mounting

NOTE All Encon® facewashes also meet the ANSI Z358.1 requirements of an eyewash.

DRENCH HOSES

VALVE

3/8" CP bronze, self-closing valve with lock-open squeeze handle actuator

BRACKET OPTION

Vinyl-coated wall mount bracket secures head when not in use

HOSE

6' (182.9 cm) synthetic rubber hose with brass fittings

SUPPLY

3/8" NPT connection (1/2" supply line recommended)

HEAD

ABS plastic, single-stream head and float off cover secured with SS bead chain

SHIP WEIGHT

5 lbs (2.26 kg)

MODEL DESCRIPTION

01090007 Drench Hose, Wall Mounting with Push Plate (shown)

01090008 Drench Hose, Wall Mounting with Bracket (shown)

01090009 Drench Hose, Counter Mounting with Flange



Every model in this section includes 7" x 11" sign (17.8 cm x 27.9 cm)

*Varying hydraulic conditions of 30 to 70 psi (206.8 to 482.6 kPa)

LABORATORY

EYEWASH WITH HOSE STATION

VALVE

3/8" CP bronze, self-closing squeeze valve with lock-open actuation

HOSE

8' (243.8 cm) synthetic rubber hose; sink/counter-top mounting

EYEWASH

Acetal heads with hinged covers; self-adjusting regulators to flow at 2.4 gpm (9.1 lpm)*

SUPPLY

3/8" NPT connection (1/2" supply line recommended)

SHIP WEIGHT

7 lbs (3.17 kg)

MODEL

DESCRIPTION

01090012 Eyewash/Drench Hose Station

EYEWASH WITH HOSE STATION

Model: **01090012**

- Acetal Heads
- 8' Hose



PULL-DOWN EYEWASH

INSTALLATION CHOICES

- Behind sink mounting, either left or right side; connection through countertop up to 2" thick; height of 14" from counter to eyewash heads in stored position (shown)
- Side of sink mounting, either left or right side; connection through countertop up to 2" thick; height of 13 5/8" from counter to eyewash heads in stored position (not shown)

ARM ASSEMBLY

BCP, right hand counter-mounted actuator; can be mounted as is on left side for left-hand actuation

EYEWASH

Acetal heads with hinged covers; self-adjusting regulators to flow at 2.4 gpm (9.1 lpm)*

SUPPLY

1/2" NPT connection

SHIP WEIGHT

Behind sink—5 lbs (2.27 kg)

Side of sink—4 lbs (1.81 kg)

VALVES

1/2" CP, stay-open valve provides quick operation with positive stop

MODEL

DESCRIPTION

01040130 Pull Down Eyewash, Behind Sink Mounting (shown)

01040133 Pull Down Eyewash, Side of Sink Mounting

PULL DOWN EYEWASH

Model: **01040130** (shown)

- Acetal Heads
- Behind Sink Mounting
- Side of Sink Mounting is Model 01040133



Every model in this section includes 7" x 11" sign (17.8 cm x 27.9 cm)

*Varying hydraulic conditions of 30 to 70 psi (206.8 to 482.6 kPa)

LABORATORY

SWING-AWAY™ EYEWASH

Model: 01040128

- Acetal Heads
- Right Hand Actuation
- 10-1/2" Arm
- 12-1/2" Arm is Model 01040127



EYEWASH WITH SAF-T-LOK®

Model: 01040123

- Acetal Heads
- Right Hand Actuation
- Vertical Valve
- Horizontal Valve is Model 01040121
- Left Hand Models Available



SWING-AWAY™ EYEWASH

VALVE

1/2" CP, stay-open valve provides quick operation with positive stop

ARM ASSEMBLY CHOICES

BCP, right-hand countertop mounted actuator with actuation graphic (reversible for left-hand mount)

12 1/2" or 10 1/2" SWING-AWAY™ arm assembly to swivel EW over sink

EYEWASH

Acetal heads with hinged covers; self-adjusting regulators to flow at 2.4 gpm (9.1 lpm)*

SUPPLY

1/2" NPT connection through countertop up to 2" thick

HEIGHT

4" above counter (stored position)

SHIP WEIGHT

4 lbs (1.84 kg)

MODEL DESCRIPTION

- | | |
|-----------------|----------------------------------|
| 01040127 | Eyewash with 12 1/2" Arm |
| 01040128 | Eyewash with 10 1/2" Arm (shown) |

SAF-T-LOK®

PIPING & VALVE CHOICES

3/8" BCP piping, fitting and swivel

Choose horizontal or vertical valve, 3/8" CP bronze ball valve and CP ball with SS push plate and actuation graphic

ASSEMBLY

Choose right hand or left hand model.

Saf-T-Lok's® CP swivel allows EW head to swivel over sink and lock into place

To store — top portion of Saf-T-Lok® lifts to free piping movement

EYEWASH

Acetal heads with hinged covers; self-adjusting regulators to flow at 2.4 gpm (9.1 lpm)*

SUPPLY

3/8" NPT connection

SHIP WEIGHT

8 lbs (3.63 kg)

MODEL DESCRIPTION

- | | |
|-----------------|--|
| 01040121 | Eyewash with Saf-T-Lok® with Horizontal Valve , Right Hand Actuation |
| 01040123 | Eyewash with Saf-T-Lok® with Vertical Valve , Right Hand Actuation (shown) |
| 01040125 | Eyewash without Saf-T-Lok® with Vertical Valve , Right Hand Actuation |

NOTE

Other models available without Saf-T-Lok® assembly. Models available with Eye/Facewash. Left-hand models available.

*Varying hydraulic conditions of 30 to 70 psi (206.8 to 482.6 kPa)

U.S. Patent No. 5,530,972

Encon
SAFETY PRODUCTS

1.800.283.6266

FAX 713.466.1703

WWW.ENCONSAFETY.COM



Every model in this section includes 7" x 11" sign (17.8 cm x 27.9 cm)

LABORATORY

RECESSED SHOWER/EYEWASH

PIPING & VALVE

EW – ½" BCP piping; ½" CP bronze stay-open eyewash valve integral to swing down arm in wall cabinet

SHOWER – 1" CP bronze stay-open shower valve with CP ball, SS stem integral to wall cabinet (shower head piping by others)

304 SS; self-adjusting regulator to flow at 20 or 30 gpm (113.6 lpm)*; delivers minimum of 20" (50.8 cm) diameter, dispersed pattern for target area of 60" (152.4 cm) above standing level when installed in a 96" ceiling; actuation through pull down handle in recessed cabinet

MOUNTING

4" deep, wall-recessed unit including actuation valve, arm and eyewash head; 304 SS enclosure

SUPPLY

1¼" NPT connection

**SHOWER ONLY
OPTION AVAILABLE –
Model 01112430**

EYEWASH

Acetal heads mounted on BCP actuation arm and Wye; self-adjusting regulators to flow at 2.4 gpm (9.1 lpm)*; 19" extension allows wheelchair access

EYEWASH WASTE OPTION

1½" slip joint tailpiece

SHIP WEIGHT

45 lbs (20.41 kg)

SHOWER HEAD

MODEL

DESCRIPTION

01112470	Shower/EW with Flush Mount Shower Head, Recessed Cabinet and ABS Return Tray Drain System (<i>shown</i>)
01112473	Shower/EW with Flush Mount Shower Head, Recessed Cabinet and SS Return Tray Drain System
01112428	Shower/EW with Flush Mount Shower Head and Recessed Cabinet
01112429	Shower/EW with Extended Shower Head and Recessed Cabinet
01112430	Shower & Recessed Cabinet Only

CEILING SHOWER

INSTALLATION CHOICES

Horizontal or vertical mount; connects to overhead pipe; trim ring provided for flush mounting to ceiling

SHOWER HEAD WITH TRIM RING

Fully 304 SS shower including both head and dispersion baffle; self-adjusting regulator to flow at 30 gpm (113.6 lpm)*; delivers minimum of 20" (50.8 cm) diameter, dispersed pattern for target area of 60" (152.4 cm) above standing level

PIPING & VALVE

1" schedule 80 hot dip galvanized steel; 1" CP bronze ball valve and CP ball with SS valve stem & galvanized 2-way actuator with separate on/off pull rings and actuation graphic

SUPPLY

1" NPT connection

SHIP WEIGHT

11 lbs (4.98 kg)

CHAIN

304 SS safety chain

MODEL

DESCRIPTION

01052507	30 gpm Shower, Horizontal Valve (<i>shown</i>)
01052518	20 gpm Shower, Horizontal Valve
01052500	30 gpm Shower, Vertical Valve
01052520	20 gpm Shower, Vertical Valve

CEILING SHOWER/RECESSED EYEWASH

Model: 01112473

- Flush Mounted Shower
- Recessed Cabinet
- Return SS Drain Tray System



CEILING SHOWER/RECESSED EYEWASH

Model: 01112470

- Flush Mounted Shower
- Recessed Cabinet
- Return ABS Drain Tray System



CEILING SHOWER

Model: 01052507

- Horizontal Valve
- 30 gpm
- Vertical Valve is Model 01052500



*Varying hydraulic conditions of 30 to 70 psi (206.8 to 482.6 kPa)

LABORATORY

RECESSED WALL-MOUNTED EYEWASH

Model: 01040112

- Recessed Cabinet
- Return Drain Tray System



WHEEL CHAIR ACCESSIBLE RECESSED WALL-MOUNTED EYEWASH

Model: 01040140

- Recessed Cabinet
- Pull Down Actuation
- Wheel Chair Accessible



RECESSED WALL-MOUNTED EYEWASH

PIPING & VALVE

BCP piping and valve

CABINET

SS cabinet; EW shut-off valve strainer and water inlet accessible through maintenance panel

EYEWASH

Return Drain

Acetal heads, recessed cabinet with fluid return tray and drain; self-adjusting regulators to flow at 0.7 gpm (2.6 lpm)*; activate by pulling eyewash handle 90° and return to cabinet to shut off

Without Return Drain

Acetal heads, BCP arm, recessed cabinet; self-adjusting regulators to flow at 2.4 gpm (9.1 lpm)*; activate by pulling eyewash handle 90° and return to cabinet to shut off

RETURN DRAIN OPTION

ABS plastic; directs spent water into cabinet drain assembly; eliminates clean up after use

SUPPLY

1/2" NPT connection

WASTE

1 1/2" slip joint tailpiece

SHIP WEIGHT

30 lbs (13.61 kg)

MODEL DESCRIPTION

- | | |
|-----------------|---|
| 01040106 | Eyewash with Acetal Heads, Recessed Cabinet without Return Drain |
| 01040112 | Eyewash with Acetal Heads, Recessed Cabinet & Return Drain (<i>shown</i>) |

PULL-DOWN EYEWASH

PIPING & VALVE

1/2" BCP piping and valve

at 2.4 gpm (9.1 lpm)*

MOUNTING CHOICES

Recessed Cabinet

304 SS with removable access panel; ABS tray with actuator handle option

SUPPLY SHUT OFF VALVE

Recessed cabinet—1/2" in-line gate valve behind access panel

SUPPLY

1/2" NPT connection

Flush to Wall

On supply pipe with 304 SS backing plate

SHIP WEIGHT

Recessed Cabinet—25 lbs (11.34 kg)

Pipe Mount

On supply pipe without back plate

Flush Mount—14 lbs (6.34 kg)

Pipe Mount—6 lbs (2.72 kg)

EYEWASH

Acetal heads with hinged covers; BCP are; self-adjusting regulators to flow

MODEL DESCRIPTION

- | | |
|-----------------|--|
| 01040139 | Eyewash with Recessed Cabinet & Return Tray Drain System |
| 01040140 | Eyewash with Recessed Cabinet (<i>shown</i>) |
| 01040141 | Eyewash, Flush to Wall Mounted |
| 01040142 | Eyewash, Pipe Mounted |

*Varying hydraulic conditions of 30 to 70 psi (206.8 to 482.6 kPa)

COMBINATIONS

COMBINATION SHOWER/EYEWASH WITH YELLO-BOWL®

PIPING & VALVE

EW/EFW – ½" CP bronze stay-open ball valve with CP ball, SS valve stem, SS push plate with actuation graphic **SHOWER** – Schedule 80 hot dip galvanized steel piping; 1" shower CP bronze stay-open ball valve with CP ball, SS pull rod assembly with actuation graphic; Also available in SS piping

SHOWER HEAD

High visibility ABS plastic; self-adjusting 30 gpm (113.6 lpm)*; delivers minimum of 20" (50.8 cm) diameter, dispersed pattern for target area of 60" (152.4 cm) above standing level; 20 gpm also available

EYE/FACEWASH CHOICES

EYEWASH

- ABS plastic heads, Wye and float off covers secured with SS bead chains; self-adjusting regulator to flow at 3.2 gpm (12.1 lpm)*
- Acetal heads with hinged covers, BCP Wye; self-adjusting regulation to flow at 2.4 gpm (9.1 lpm)*

FACEWASH

ABS plastic heads, Wye and float off covers secured with SS bead chains; Also available with BCP Wye; Self-adjusting regulator to flow at 8.0 gpm (30.3 lpm)*

BOWL

ABS plastic Yello-Bowl®, 10.8" diameter

SUPPLY

1¼" NPT connection

WASTE

1¼" NPT connection

DRENCH HOSE OPTION

Provides partial body flushing

6' (182.9 cm) synthetic rubber hose assembly and mounting bracket

Yellow ABS plastic single-stream head and float off cover secured by SS bead chain; self-closing, lock-open squeeze handle

SHIP WEIGHT

59 lbs (26.76 kg)
61 lbs (27.66 kg) – with FTR
62 lbs (21.12 kg) – with DH

MODEL DESCRIPTION

01050207	30 gpm Shr./EW with ABS Heads & Wye (shown)
01050208	30 gpm Shr./EW with ABS Heads & Wye and Drench Hose
01050216	30 gpm Shr./FW with ABS Heads & Wye
01050217	30 gpm Shr./EW with Acetal Heads & BCP Wye
01050251	20 gpm Shr./EW with ABS Heads & Wye
01050260	20 gpm Shr./FW with ABS Heads & Wye

NOTE

Available on most models: stainless steel piping, strainer and/or drench hose. Plastic Bowl Covers available on all models with BCP Wyes.

COMBINATION SHOWER/EYEWASH

Model: 01050207

- ABS Heads/Wye
- Yello-Bowl®
- ABS Plastic Shower Head



Eyewash Model: 01050207

Facewash Model: 01050216

Drench Hose Option

Model: 01050208



Available with Acetal Eyewash Heads and Strainer – Shown 01050265



Available with Facewash and Strainer – Model 01050266



Foot Treadle available on all models – 01052382



Plastic Bowl Covers available on all models with BCP Wye



Every model in this section includes 7" x 11" sign (17.8 cm x 27.9 cm)

NOTE All Encon facewashes also meet the ANSI Z358.1 requirements of an eyewash.

*Varying hydraulic conditions of 30 to 70 psi (206.8 to 482.6 kPa)

COMBINATION SHOWER/FACEWASH

Model: 01050234

- SS Bowl
- ABS Plastic Shower Head
- Eyewash Model is 01050230



Facewash Model: 01050234

Eyewash Model: 01050230

Drench Hose with Strainer Option

Model: 01050374



Models available with a Stainless Steel Shower Head



Eyewash with Acetal Heads is Model 01050230



Plastic Bowl Covers available on all models – add PBC to the model number



Models available with a Stainless Steel Bowl Cover – add SBC to the model number

*Varying hydraulic conditions of 30 to 70 psi (206.8 to 482.6 kPa)

COMBINATIONS

COMBINATION SHOWER/FACEWASH WITH STAINLESS STEEL BOWL

PIPING & VALVE

EW/EFW – 1/2" CP bronze stay-open ball valve with CP ball, SS valve stem, SS push plate with actuation graphic
SHOWER – Schedule 80 hot dip galvanized steel piping; 1" shower CP bronze stay-open ball valve with CP ball, SS pull rod assembly with actuation graphic; Also available with SS piping

regulator to flow at 8.0 gpm (30.3 lpm)*

BOWL

304 SS, 10.6" diameter

SUPPLY

1 1/4" NPT connection

WASTE

1 1/4" NPT connection

DRENCH HOSE OPTION

Provides partial body flushing
 6' (182.9 cm) synthetic rubber hose assembly and mounting bracket
 Yellow ABS plastic single-stream head and float off cover secured by SS bead chain; self-closing, lock-open squeeze handle

SHIP WEIGHT

59 lbs (26.76 kg)

61 lbs (27.66 kg) – with FTR

62 lbs (21.12 kg) – with DH

SHOWER HEAD

High visibility ABS plastic; self-adjusting 30 gpm (113.6 lpm)*; delivers minimum of 20" (50.8 cm) diameter, dispersed pattern for target area of 60" (152.4 cm) above standing level; 20 gpm also available; Models available with 304 SS shower head

EYE/FACEWASH CHOICES

EYEWASH

Acetal heads with hinged covers, BCP Wye; self-adjusting regulation to flow at 2.4 gpm (9.1 lpm)*

FACEWASH

ABS plastic heads and float off covers secured with SS bead chains; BCP Wye; Self-adjusting

MODEL DESCRIPTION

01050230	30 gpm Shr./EW
01050234	30 gpm Shr./FW (shown)
01050471	30 gpm Shr./EW with SS Shower Head
01050472	30 gpm Shr./FW with SS Shower Head
01050374	30 gpm Shr./FW with Drench Hose and Strainer (shown)

NOTE Available on most models: stainless steel piping, strainer and/or drench hose. Plastic or Stainless Steel Bowl Covers available on models with BCP Wyes.

NOTE All Encon facewashes also meet the ANSI Z358.1 requirements of an eyewash.

Every model in this section includes 7" x 11" sign (17.8 cm x 27.9 cm)



COMBINATIONS

PVC SHOWER/EYEWASH

PIPING & VALVE

Schedule 80 corrosion-resistant PVC piping with socket weld joints;
EYE/FACE WASH – 1/2" Polane® coated bronze valve with CP ball, SS valve stem, SS push plate with actuation graphic

SHOWER – 1" shower Polane® coated bronze stay-open ball valve with CP ball, pull rod assembly with actuation graphic

SHOWER HEAD

High visibility ABS plastic; self-adjusting 20 or 30 gpm (113.6 lpm)*; delivers minimum of 20" (50.8 cm) diameter, dispersed pattern for target area of 60" (152.4 cm) above standing level

SHIP WEIGHT

34 lbs (15.42 kg)

EYE/FACEWASH CHOICES

EWYEWASH

ABS plastic heads, Wye and float off covers secured with SS bead chains; self-adjusting regulator to flow at 3.2 gpm (12.1 lpm)*

FACEWASH

ABS plastic heads, Wye and float off covers secured with SS bead chains; Option for BCP Wye; Self-adjusting regulator to flow at 8.0 gpm (30.3 lpm)*

BOWL

ABS plastic Yello-Bowl®, 10.8" diameter

SUPPLY

1 1/2" NPT connection

WASTE

1 1/2" NPT connection on models with bowls

MODEL DESCRIPTION

01060007	30 gpm Shr./EW, Verticle support flanges, 1 1/2" stanchion (shown)
01060009	30 gpm Shr./FW, Verticle support flanges, 1 1/2" stanchion
01060011	30 gpm Shr./EW, Barrier free, Verticle support flanges, 1 1/2" stanchion
01060021	30 gpm Shr./EW, 2" Self-supporting stanchion (shown)
01060022	20 gpm Shr./EW, 2" Self-supporting stanchion
01060023	20 gpm Shr./EW, Barrier free, 2" Self-supporting stanchion
01060024	30 gpm Shr./EW, Barrier free, 2" Self-supporting stanchion

CORROSION-RESISTANT COATING

PIPING & VALVE

Schedule 80 corrosion-resistant galvanized steel piping;
EYE/FACE WASH – 1/2" CP bronze valve with CP ball, SS valve stem, SS push plate with actuation graphic

SHOWER – 1" shower CP bronze stay-open ball valve with CP ball, SS pull rod assembly with actuation graphic

SHOWER HEAD

High visibility ABS plastic; self-adjusting 30 gpm (113.6 lpm)*; delivers minimum of 20" (50.8 cm) diameter, dispersed pattern for target area of 60" (152.4 cm) above standing level; 20 gpm also available

SHIP WEIGHT

59 lbs (26.7 kg)

EYE/FACEWASH CHOICES

EWYEWASH

ABS plastic heads, Wye and float off covers secured with SS bead chains; self-adjusting regulator to flow at 3.2 gpm (12.1 lpm)*

FACEWASH

ABS plastic heads, Wye and float off covers secured with SS bead chains; Self-adjusting regulator to flow at 8.0 gpm (30.3 lpm)*

BOWL

ABS plastic Yello-Bowl®, 10.8" diameter

SUPPLY

1 1/4" NPT connection

WASTE

1 1/4" NPT connection on models with bowls

MODEL DESCRIPTION

01050210	30 gpm Shr./EW (shown)
01050228	30 gpm Shr./FW (shown)

PVC SHOWER/EYEWASH

Model: 01060021

- ABS Heads/Wye
- Yello-Bowl®
- ABS Plastic Shower Head
- 2" Self-supporting stanchion



Wallmount Option

Model: 01060007


- 1 1/2" stanchion



CORROSION-RESISTANT SHOWER/EYEWASH


Model: 01050228

- ABS Heads/Wye
- Yello-Bowl®
- ABS Plastic Shower Head



Eyewash Option

Model: 01050210



Every model in this section includes 7" x 11" sign (17.8 cm x 27.9 cm)

NOTE All Encon facewashes also meet the ANSI Z358.1 requirements of an eyewash.

*Varying hydraulic conditions of 30 to 70 psi (206.8 to 482.6 kPa)

SHOWERS

FREEZE & SCALD PROTECTION

Model: 01050362

- ABS Yello-Bowl®
- ABS Plastic Shower Head



FREEZE-RESISTANT SHOWERS

PIPING & VALVE

ES/EFW – 1/2" CP bronze stay-open ball valve with CP ball, SS valve stem, SS push plate with actuation graphic
SHOWER – Schedule 80 hot dip galvanized steel piping; 1" shower CP bronze stay-open ball valve with CP ball, SS pull rod assembly with actuation graphic; Option available for SS piping

SHOWER HEAD

High visibility ABS plastic; self-adjusting 30 gpm (113.6 lpm)*; delivers minimum of 20" (50.8 cm) diameter, dispersed pattern for target area of 60" (152.4 cm) above standing level; 20 gpm also available; Models available with 304 SS shower head

EYEWASH CHOICES

ABS heads/Wye; self-adjusting regulation to flow at 3.2 gpm (12.1 lpm)*

BOWL

ABS Yello-Bowl®, 10.8" diameter

FREEZE & SCALD VALVE OPTIONS

Auto Freeze Protection Valve

Opens automatically when internal temperature reaches 35°F (2°C) and closes at 40°F (4.5°C)

Auto Scald Protection Valve

Opens automatically when internal temperature reaches 95°F (35°C) and fully open at 105°F (40.6°C). Closes at 92°F (33°C)

SUPPLY

1/4" NPT connection

WASTE

1/4" NPT connection

SHIP WEIGHT

60 lbs (27.22 kg)

MODEL DESCRIPTION

MODEL	DESCRIPTION
01050317	Shr./EW with Auto Freeze Protection Valve
01050357	Shr./EW with Auto Scald Protection Valve
01050362	30 gpm Shr./EW with Auto Freeze & Scald Protection Valves (shown)

NOTE All above models are 30 gpm.

HORIZONTAL & VERTICAL SHOWERS

PIPING & VALVE

Mounts directly onto overhead pipe; Schedule 80 hot dip galvanized steel piping; 1" CP bronze stay-open ball valve with CP ball; SS valve stem; 29" SS, pull rod assembly with actuation graphic; 1/4" pipe models available

SHOWER HEAD

High visibility ABS plastic; self-adjusting 30 gpm (113.6 lpm)*; delivers minimum of 20" (50.8 cm) diameter, dispersed pattern for target area of 60"

(152.4 cm) above standing level; 20 gpm models also available

SUPPLY

- 1" NPT connection; or
- 1-1/4" NPT connection

SHIP WEIGHT

Horizontal Mounting—1" supply—8 lbs (3.62 kg); 1/4" supply—11 lbs (4.98 kg)

Vertical Mounting—1" supply—6 lbs (2.72 kg); 1/4" supply—11 lbs (4.98 kg)

MODEL DESCRIPTION

MODEL	DESCRIPTION
01052501	30 gpm Horizontal Shower
01052502	30 gpm Vertical Shower (shown)

NOTE Stainless Steel Piping Available
1/4" Pipe Mount Available

FREEZE & SCALD PROTECTION

Model: 01052502

- ABS Plastic Shower Head
- 1" Pipe Mount
- For Horizontal Pipe Mount is Model 01052501



Every model in this section includes 7" x 11" sign (17.8 cm x 27.9 cm)



NOTE All Encon facewashes also meet the ANSI Z358.1 requirements of an eyewash.

*Varying hydraulic conditions of 30 to 70 psi (206.8 to 482.6 kPa)

ACCESSORIES

ALARM SYSTEMS & LIGHTING

STANDARD

Installation For existing or new ESEW stations to alert local and/or remote locations when in use

Remote Capability Spare NO/NC "dry" contacts available on all alarm products; 120V, 3 amp rating on relay for remote signal

OPTIONS

Light & Audible Alarm

Provides intermittent pulsing sound when activated; local reset button to silence the audible alarm

Visual Alarm Displays red flashing alarm light when activated

Area Light Provides constant illumination to emergency station when area vision is compromised; choice of clear, blue or green globe light

ACTIVATION DEVICE OPTIONS


Flow Switch® Detects flow through piping when emergency assembly activated; relay rated @ 3 amps, 120V, 60 Hz; accepts horizontal & vertical positions; suitable for Class 1 Div. 2 Gp. B, C & D areas; 1/4" NPT connection

MAP® Switch (Magnetic Activated Proximity Switch) Senses shower pull rod and/or push plate activation; Yello-Bowl®, SS bowl, or without bowl options available

ALARM & LIGHTING SYSTEMS

Model: 02111000

- Flow Switch
- Audible Alarm
- Visual Alarm



Design Your Own System

- Select the number per column that matches your choice
- Transfer the numbers to bottom line
- Note the model number you have created when ordering

Code			
Activation Device	Audible Alarm	Visual Alarm	Area Light
No	No	No	No
0	0	0	0
Flow Switch	Yes	Yes	Yes Clear Globe
1	1	1	1
MAP® Switch for Yello-Bowl® & No Bowl Models			Yes Blue Globe
2			2
MAP® Switch for Stainless Steel Bowl Models			Yes Green Globe
3			3

Model#

02-

-00

AWARENESS® SIGNAGE

- High visibility graphics
- Chemical Resistant ABS

Mounting Choices

- Top/bottom Entry Showers*
- Midpoint Entry Showers
- Wall Mounting

Language Choices

- English*
- French
- German
- Swedish
- Spanish

Color Choices*

- Green 01112953
- Orange 01112951
- Yellow 01112911



MODESTY CURTAINS

Model: 01052149

- ABS Plastic Blocks
- SS Rod & Support Bracket with SS U-bolts for Corrosion Resistance
- 70" x 145" Water-resistant, PVC Nylon-coated Curtain
- Weighted along Bottom to Maintain Shape during Use
- Clean Room Option available



SHOWER SHELTER™

Model: 01080024

- 3-Side Wind Break
- SS Clamp & Hardware
- Galvanized Steel Pipe Supports & Flange
- Fiberglass Panels & Molded Roof
- 109 1/16" x 45 1/2" x 51 1/2"



SHOWER TEST UNIT

Model: STU1

- Shower Test Unit with Cart
- Portable PVC Nylon Test Chute
- Large Opening with Drawstring
- Yellow Cart with 10" Semi-Pneumatic Back Wheels & 6" Locking Front Casters



PARTS

ABS EYE/FACEWASH ASSEMBLIES

ABS EW Heads/Wye,
3.2 gpm

- 1/2" Inlet is Model 01052123
- 3/8" Inlet is Model 01052185



ABS FW Heads/Wye,
8.0 gpm


- 1/2" Inlet is Model 01052122
- 3/8" Inlet is Model 01052189



BCP EYE/FACEWASH ASSEMBLIES

Acetal EW Heads,
BCP Wye, 2.4 gpm

- 1/2" Inlet is Model 01052132
- 3/8" Inlet is Model 01052129



ABS FW Heads,
BCP Wye, 8.0 gpm

- 1/2" Inlet is Model 01052133
- 3/8" Inlet is Model 01052130



LOW PROFILE ASSEMBLIES

Acetal EW Heads, BCP
Wye, 2.4 gpm

- 1/2" Inlet is Model 01052208
- 3/8" Inlet is Model 01052207



ABS FW Heads, BCP
Wye, 8.0 gpm

- 1/2" Inlet is Model 01052212



LOW FLOW FOR SELF-CONTAINED

ABS EW Heads, BCP
Wye, .4 gpm

- 1/2" Inlet Model 01052111A



SHOWER HEADS

Model: 01054003

- ABS
- 1" Connection
- 30 gpm



Model: 01054005

- ABS
- 1" Connection
- 20 gpm



Model: 01055007

- 304 Stainless Steel
- 30 gpm
- 20 gpm Model is 01055005



BOWLS

Model: 01110096

- 304 SS



Model: 01110462

- ABS Yello-Bowl®



COVERS

Model: 01052113

- EW Float Off Cover
- 8" Chain



Model: 01052020


- FW Float Off Cover
- 10" Chain



HOSE

Model: 00014337

- Pressurized Portable 1/4" Hose
- 8' Red Recoil Hose



DRENCH HOSE SUBASSEMBLY

Model: 01105005

- Pressurized Portable Subassembly
- 8' Red Recoil Hose



DOLLY CART

Model: 01105003

- Tubular Steel Cart
- Velcro® Straps for 13-gallon Units



YELLOW CART

Model: 01103008

- Polyethylene Cart
- Straps for 13-gallon Units



PUSH PLATES

Model: 01052101

- Valve & Push Plate
- Graphic Kit
- 1/2" BCP with Nut
- 1/2" Self-draining BCP with Nut is Model 01052114
- Push Plate Only is 01052018



ACTUATION VALVES

Model: 01052103

- Valve with Actuator Arm, Horizontal
- 1/4" BCP
- SS is Model 01052197



STRAINER TEE

Model: 01052098

- 1/2" BCP
- 16 Mesh
- 100 Mesh is Model 01052083





TF12B4777200

- Self-limiting heat trace cable; 5 watts per foot.
- Closed-cell foam insulation to maximize heat retention.
- 120 or 240 VAC compatible models.
- High-visibility yellow, green or orange UV-inhibited, ABS plastic covers resist chemical and environmental deterioration.
- Completely removable covers with elastomer seals for field maintenance.
- Neoprene coated aluminum trim strips secure covers.
- High-limit thermostat protects against over temperature water.

THERMA-FLOW® FREEZE-PROTECTED EMERGENCY SHOWER/EYEWASH

Encon® freeze protected Therma-Flow® showers are designed and manufactured to resist freezing by keeping the water at or above 50°F (10°C) to external temperatures as low as -40°F (-40°C). The design includes a fixed internal thermostat controlling electrical self limiting heat trace on schedule 80 galvanized pipe and bronze valves, closed cell foam insulation and durable ABS covers as standard materials of construction. The base unit can be combined with options such as alternate electrical supply voltages, varying flow volumes to meet or exceed the ANSI Z358.1 standard, alarms on actuation, mechanical freeze and scald protection back-up devices, freeze protection for the water line connection and voltages for alternate electrical connection requirements. The Therma-Flow® is simple to install, easy to maintain and is highly visible with multiple choices of cover colors.



TF16B2300300

- Remote and local alarm capability with horn, bell, Pulsetone™ and flashing light selection.
- 20 and 30 gpm shower flow regulation for maximum utilization of water and piping schemes.
- CSA approved with UL and FM components for non-hazardous or hazardous areas.
- Optional heat traced, insulated extension protects underground water supply piping.
- Flow switch or proximity (MAP®) switch alarm actuator options available.



LR83818