

## Gear and Bearing Pullers

Cage® guides jaws for fast setup, solid contact and superior safety.

Center bolt threads designed for less effort to apply high torque.



precisely where you set them.

Nut recessed to avoid

Leverage up front for vise-like power and no slippage.

Slim tapered jaws allow for easier gripping and better access to tight spots.

A general purpose puller that eliminates the need for many specialty pullers and accessories.

- One-man operation
- Locks like a vise
- Save time, money and labor



Model Number	Number of Jaws	Capacity Tons	Maximum Reach	Spread Range
202	2	1	2.25 in.	.25 to 3.25 in.
102	3	1	2.25 in.	.25 to 3.25 in.
203	2	2	3 in.	.25 to 4.5 in.
103	3	2	3 in.	.25 to 4.5 in.
204	2	2	4 in.	.5 to 5 in.
104	3	5	4 in.	.5 to 5 in.
206	2	6	6 in.	.5 to 7 in.
106	3	10	6 in.	.5 to 7 in.
208	2	12	8 in.	.75 to 12 in.
108	3	17	8 in.	.75 to 12 in.
210	2	14	9.67 in.	1 to 15 in.
110	3	20	9.67 in.	1 to 15 in.
213	2	25	12 in.	2.5 to 18 in.
113	3	30	12 in.	2.5 to 18 in.
216	2	35	14 in.	3 to 25 in.
116	3	40	14 in.	3 to 25 in.