

*Specialists in
Safety
Identification
Products*

Harris West

5181 Argosy Avenue
Huntington Beach, CA 92649

Phone:
(714) 898-8048
(800) 222-6866

Fax:
(714) 898-7108
(800) 228-1274

Harris East

181 Conant Drive
Pawtucket, RI 02860

Phone:
(401) 727-3160
(800) 443-2821

Fax:
(401) 727-3162

Technical Specifications

PIPE MARKERS

I. GENERAL CHARACTER AND USE:

The product consists of 5.0 mil calendered vinyl coated on one side with a permanent pressure-sensitive adhesive. Adhesive is protected by a silicone release liner. Excellent conformability and good holding on a variety of flat and curved surfaces. Durable and versatile in its applications and uses. Available in a variety of colors. For use as printed labels, decals or pipe markers bearing information, instructions or identification.

II. FACESTOCK:

5.0 mil calendered vinyl

Thickness:	0.005 mm + . 10%
Tensile Strength:	15 lbs./in.
Elongation:	150%

III. ADHESIVE PERFORMANCE:

LS2 Acrylic Adhesive

Thickness:	0.023 mm + . 10%
Dry Weight:	25g/m ² + . 10%
Initial Tack:	15 cm max., 7/32" diameter rolling ball.
Adhesion to Steel:	1 kg/1" min. average
Release Force:	5 to 20 g/1"
Temperature Range:	0°C to 60°C

IV. MISCELLANEOUS:

Shelf Life:	12 months @ 73°F and 65% relative humidity
Chemical Resistance:	Excellent

All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for their intended use, and user assumes all risk and liability whatsoever in connection therewith.