

Specialists in
Safety
Identification
Products

5181 Argosy Avenue
Huntington Beach,
California 92649

181 Conant Street
Pawtucket,
Rhode Island 02860

Telephone Numbers:
(714) 898-8048
(800) 222-6866

Fax Numbers:
(714) 898-7108
(800) 228-1274

Technical Specifications

VM Series Vinyl Marking Tape

Product Description

- Soft PVC or its copolymer film backing, suitably elasticized and stabilized
- Coated with rubber-based pressure sensitive adhesive on one side
- Matte finish with different colors, which conform to OSHA 1910.144.

Applications

- It is used for industrial identification, color-coding, aisle marking and duct wrapping.

Features/Benefits

- Suitable use at not more than 60°C (140°F)
- Excellent anti-abrasion, flexible and resistant to acid, alkalis and oils
- Non-corrosive pressure sensitive adhesive, latex free, easy to apply
- No known hazards

Technical Performance

<u>Description</u>	<u>Unit</u>	<u>Value</u>	<u>Test Method</u>
Tape Thickness	mm/mil	0.130/5.2	PSTC-33
Adhesion to Steel	(kg/cm)/(oz/in)	0.20/18	ASTM D-1000
Adhesion to Backing	(kg/cm)/(oz/in)	0.20/18	ASTM D-1000
Elongation at Break	%	150	PSTC-31
Tensile Strength	(kg/cm)/(lb/in)	2.5/14	PSTC-31

Storage

- Shelf Life: One year recommended from the date of dispatch at the moderate temperature and humidity environment