255 Fastac Natural

REINFORCED WATER ACTIVATED TAPE

INTERTAPE POLYMER GROUP

TECHNICAL DATA SHEET

DESCRIPTION

3-Way fiberglass reinforced natural kraft carton sealing tape, manufactured with water activated adhesive.

PRODUCT APPLICATION

Used for two strip sealing cartons top and bottom. Works well on recycled cartons, and non-unitized loads. Recommended for use on average weight cartons up to 50 pounds.

CONSTRUCTION (PER 3.000 SOUARE FEET):

Top Ply: 25 Lb. Natural Kraft Paper

(virgin fibers)

Bottom Ply: 25 Lb. Natural Kraft Paper

(virgin fibers)

Laminating Adhesive: 14 Lb. High Melt Index

Polypropylene Based Co-

Polymer

Remoistenable Adhesive: 15 Lb. Chemically Grafted

Starch Based Copolymer Adhesive, Designated as

S3911

MD Reinforcement: 2.91 Lb. (2-1-1-1-2) 110

Fiberglass (per 3"), ½"

spacing

CD Reinforcement: 1.34 Lb. (1-1-1) 150

Fiberglass, 1.20" spacing,

37 degree angle

Total Basis Weight: 83.2 Lb.

PHYSICAL PROPERTIES:

Caliper (mils):6.5MD Tensile (Lbs./in.):80CD Tensile (Lbs./in.):31

ADHESION (WATER AT RECOMMENDED 110°F):

Fipago:

 2/0
 41

 2/1
 66

 5/0
 70

 15/0
 88

 McClaurin:
 85



3647 Cortez Road West | Bradenton, FL 34210 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832 www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/10/2012

