

# **Food Grade Grainger SKUS**

## Food Grade Silicone

NSF H1 rated. Stops sticking, squeaking and binding of moving parts. Excellent release agent. Will not gum or form unwanted residue, leaves a clear film that is moistureresistant, long-wearing, odorless, colorless and nontoxic.

SKU 2YKK3, 12 oz. Aerosol

#### FMG<sup>™</sup>

NSF HI rated. Formulated to perform in a wide variety of operating conditions. It is extremely water-resistant and will remain in place even after frequent wash downs. Recommended for the lubrication of roller, needle, ball, journal, and sliding bearings in the food processing and handling industry.

SKU 5CHP4, 14 oz. Cartridge SKU 5CHP5, 5 Gal. SKU 5CHP6, 15 Gal. SKU 5CHP6, 15 Gal. SKU 5CHP7, 50 Gal.



## **CC Lube**

NSF H1 rated. A clear, clean, colorless, nonstaining, nondrying, biodegradable grease. It is unsurpassed in reducing friction, extending machine and equipment life and preventing the formation of rust and corrosion over a broad temperature range. Excellent for use wherever a clear, clean, safe, multi-purpose lubricant is required.

SKU 5CHP8, 14 oz. Cartridge SKU 5CHP9, 1 Gal. SKU 5CHR0, 5 Gal. SKU 5CHR1, 15 Gal. SKU 5CHR2, 50 Gal

# Magic Wrench<sup>™</sup>

NSF H1 rated. Super penetrant attacks rust and corrosion quickly and safely to free corroded parts, loosen nuts and aid in the disassembly of mechanical components. Versatile synthetic formula penetrates, lubricates, removes moisture and protects chains, cables, slides and other moving parts.

SKU 5CHR3, 13 oz. Aerosol SKU 5CHR4, 16 oz. Trigger SKU 5CHR5, 1 Gal. SKU 5CHR36, 5 Gal. SKU 5CHR7, 50 Gal.



## EMS™

NSF HI rated. An emulsified, premium, multipurpose product that lubricates, waterproofs and protects while being odorless, tasteless and nonstaining. Recommended for use in food processing plants on conveyors, guides, roller chains, bakery equipment, racks, cookers and in bottling and packaging applications.

SKU 5CHT1, 16 oz. Trigger SKU 5CHT2, 1 Gal. SKU 5CHT3, 5 Gal. SKU 5CHT4, 50 Gal.



## Oven Chain Lubricant<sup>™</sup>

NSF HI rated. A premium, effective, high viscosity lubricant that penetrates into the chain to provide optimum performance at elevated temperatures. Derived from a carefully evolved blend of high viscosity, nonsmoking [550°F



(288°C)], low odor synthetic fluids and surface tension modifiers. These lower the surface tension of the high viscosity fluids allowing them to move effectively to penetrate into the links and pins of the chain and lubricate the chain roller.

SKU 5CHR8, 5 Gal. SKU 5CHR9, 15 Gal. SKU 5CHT0, 50 Gal.

## White Knight<sup>™</sup>

Food grade anti-seize, NSF registered HI. Protects and lubricates metal parts and threaded fasteners from rust and corrosion up to 1800°F (982°C). Use on threaded fasteners for food processing equipment, threaded bottle filling heads and baking oven chain drives. Effective on stainless steel, iron galvanized fittings a



steel, iron galvanized fittings and plastic/nylon components. -65°F to 1800°F (-54°C to 982°C).

SKU 26W743, ½ Lb. Brush Top SKU 26W744 I Lb. Brush Top SKU 26W745 I Gal.





All Products are made right here in the USA!