

PIG® Outdoor Latching Drum Lid

#DRM1111 - For 55-gal. New & Reconditioned Open-head Steel • Hinged w/ One Hand Latch



Get fast, easy access to outdoor drums and meet closed container regs with the only latching lid that's made to stand up to the elements and resist corrosion.

- Outdoor drum lid is zinc primed for extra protection against rust and corrosion
- Fast-latch ring allows easy installation on new or reconditioned 55-gallon steel drums; no clumsy nut-and-bolt ring
- 3"-wide EVA gasket and locking mechanism seal lid to reduce vapor emissions and help keep drum contents dry and pure
- Large-diameter crowned lid keeps out rainwater and improves appearance
- Latching handle is easy to open or close with one hand
- Removable hinge pin lets you remove lid without loosening band around drum
- Lid stop keeps lid upright when open
- Accepts padlock (not included)



New Pig

By Phone:
1-855-493-HOGS

Online:
newpig.com

Email:
hothogs@newpig.com

One Pork Avenue • Tipton PA 16684-0304

© 2014 New Pig Corporation. All rights reserved.
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: DRM1111 - Pg 1 of 3

DRM1111 Specifications

Style:	Hinged w/ One Hand Latch
Use With:	55-gal. New & Reconditioned Open-head Steel
Padlockable:	Yes with .25" shackle
Sold as:	1 per box
Composition:	Paint - Zinc-Primed, Powder-Coated Enamel Lid - Steel Gasket - Ethylene-Vinyl Acetate
UNSPSC:	24112112

Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

29 CFR 1910.134(a)(1) - Engineering controls should be used as a first step in controlling harmful dusts, fogs, fumes, mists, gases, smokes, sprays, or vapors in the workplace.

29 CFR 1910.106(e)(2)(i) - Flammable liquids need to be stored in closed containers that are sealed by a "lid or other device" that does not allow liquids or vapors to escape.

40 CFR 261.4 - Helps you comply with 40 CFR 261.4 requiring excluded solvent contaminated wipes to be accumulated and stored in closed containers while they are managed onsite.

29 CFR 1910.22(a) - All places of employment "shall be kept clean and dry and in a sanitary condition" and floors shall be kept clean and dry.

40 CFR 264.173 - Containers holding hazardous waste, "must always be closed during storage, except when it is necessary to add or remove waste."

40 CFR 264.1086(c)(1)(ii) - Level one containers must have closure devices that, "form a continuous barrier over the container openings." When these closure devices are in place, there can be, "no visible holes, gaps or other open spaces into the interior of the container."

40 CFR 262.34(c)(1) - Satellite Accumulation Areas allow generators of hazardous waste to accumulate as much as 55 gallons of hazardous waste or one quart of acutely hazardous waste in containers at or near the point of generation. The container must be kept closed when not in use, must be under the control of the operator generating the waste and must be properly labeled.

Technical Documents:

(Available at newpig.com)

Product Data Sheet (PDS)

Chemical Compatibility (CCG)



By Phone:
1-855-493-HOGS

Online:
newpig.com

Email:
hothogs@newpig.com

New Pig

One Pork Avenue • Tipton PA 16684-0304
© 2014 New Pig Corporation. All rights reserved.
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: DRM1111 - Pg 3 of 3