

# PIG® DoorBlocker Dike

#PLR213 - 2" x 4' x 1.5"



Specially designed spill dike seals off doorways to protect against spreading spills, rising water or washdown liquids.

- Unique 45-degree wedge design fits snugly against doorjamb to stop the spread of liquids
- Ideal as a barrier in doorways during washdown operations, as a dam to control or contain spilled liquids or as a diverter to direct rising water or liquid away from equipment or supplies
- Polyurethane material resists water, oils and many chemicals
- High-visibility yellow top color draws attention to spill for increased safety
- Fits any doorway up to 4' wide
- Light-weight dike is easy to handle and deploy
- Reusable dike cleans easily with soap and water



By Phone:  
**1-855-493-HOGS**

Online:  
**newpig.com**

Email:  
**hothogs@newpig.com**

**New Pig**

One Pork Avenue • Tipton PA 16684-0304  
© 2014 New Pig Corporation. All rights reserved.  
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: PLR213 - Pg 1 of 2

## PLR213 Specifications

<b>Style:</b>	Standard
<b>Color:</b>	Yellow
<b>Dimensions:</b>	2" W x 4' L x 1.5" H
<b>Intended For:</b>	Smooth Surface
<b>Max liquid temp exposure:</b>	225°F for up to 30 minutes
<b>Storage Temp Range:</b>	0° — 120°F
<b>Temperature Limit:</b>	0° — 160°F up to 12 months
<b>Sold as:</b>	1 each
<b>Weight:</b>	4 lbs.
<b>New Pig Patent:</b>	5,236,281
<b># per Pallet:</b>	120
<b>Composition:</b>	Polyurethane
<b>UNSPSC:</b>	24101907

## PLR213 Metric Equivalent

<b>Dimensions:</b>	5.1cm W x 121.9cm L x 3.8cm H
<b>Weight:</b>	1.8 kg

## Technical Information

### Warnings & Restrictions:

#### Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.

### Regulations and Compliance:

40 CFR 122.26 - When applying for a National Pollutant Discharge Elimination System (NPDES) permit, facilities must have a plan in place that describes actions, procedures, control techniques, management practices and equipment available to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7 - SPCC planning requirements state that facilities subject to these regulations must have written plans in place discussing the products, countermeasures and procedures that are in place, or will be taken by the facility to prevent discharge of oil into waters of the United States.

### Technical Documents:

(Available at [newpig.com](http://newpig.com))

Product Data Sheet (PDS)

Safety Data Sheet (SDS)

Chemical Compatibility (CCG)



**New Pig**

By Phone:  
**1-855-493-HOGS**

Online:  
**newpig.com**

Email:  
**hothogs@newpig.com**

One Pork Avenue • Tipton PA 16684-0304

© 2014 New Pig Corporation. All rights reserved.  
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: PLR213 - Pg 2 of 2