

# PIG® Original SpillBlocker® Dike

#PLR204 - 4" x 10' x 2.25"



Confine and divert spills up to 2.25" deep with our customer-favorite dike. Others look the same but only PIG delivers durable two-part construction.

- Exclusive New Pig formulation features a tear-resistant top layer and a flexible, tacky bottom layer that seals tight to smooth surfaces and blocks liquids
- Other dikes may look similar, but only PIG SpillBlocker Dikes have two-layer construction for superior performance
- 2.25" height is great for containing smaller spills
- Fast protection for when a spill is heading right for your drain; just place dike in front of spill to contain liquid
- Confines and diverts fluids without absorbing them, making cleanup or reclamation simpler
- Polyurethane material resists water, oils and many chemicals
- Reusable dike cleans easily with soap and water



**New Pig**

By Phone:  
**1-855-493-HOGS**

Online:  
**newpig.com**

Email:  
**hothogs@newpig.com**

One Pork Avenue • Tipton PA 16684-0304  
© 2014 New Pig Corporation. All rights reserved.  
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: PLR204 - Pg 1 of 3

# PLR204 Specifications

<b>Style:</b>	Standard
<b>Intended For:</b>	Smooth Surface
<b>Max liquid temp exposure:</b>	225°F for up to 30 minutes
<b>Storage Temp Range:</b>	0° — 120°F
<b>Temperature Limit:</b>	0° — 160°F up to 12 months
<b>Sold as:</b>	1 each
<b>New Pig Patent:</b>	5,236,281
<b># per Pallet:</b>	32
<b>Composition:</b>	Polyurethane
<b>UNSPSC:</b>	24101907

# Technical Information

## Warnings & Restrictions:

### Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.

## Regulations and Compliance:

40 CFR 122.26 - When applying for a National Pollutant Discharge Elimination System (NPDES) permit, facilities must have a plan in place that describes actions, procedures, control techniques, management practices and equipment available to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7 - SPCC planning requirements state that facilities subject to these regulations must have written plans in place discussing the products, countermeasures and procedures that are in place, or will be taken by the facility to prevent discharge of oil into waters of the United States.

## Technical Documents:

(Available at [newpig.com](http://newpig.com))

Product Data Sheet (PDS)

Safety Data Sheet (SDS)

Chemical Compatibility (CCG)



By Phone:  
**1-855-493-HOGS**

Online:  
**newpig.com**

Email:  
**hothogs@newpig.com**

**New Pig**

One Pork Avenue • Tipton PA 16684-0304  
© 2014 New Pig Corporation. All rights reserved.  
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: PLR204 - Pg 3 of 3