



PIG® LeakBlocker® Dike

#PLR212 - 2.25" x 10' x 1.375"



Don't waste a big blocker on a small leak. This 1.375"H LeakBlocker is just right for leaky machinery until you can make repairs.

- Fast protection for when a leak is starting to spread; just surround machine with dike to contain liquid
- Exclusive New Pig formulation features a flexible, tacky bottom layer that seals tight to smooth surfaces and blocks liquids
- Built-in, interlocking end joints create a liquid-proof seal and allow you to join as many sections as you need without extra parts
- Confines and diverts fluids without absorbing them, making cleanup or reclamation simpler
- Polyurethane material resists water, oils and many chemicals
- High-visibility yellow color draws attention to spill for increased safety
- Reusable dike cleans easily with soap and water



New Pig

By Phone:
1-855-493-HOGS

Online:
newpig.com

Email:
hothogs@newpig.com

One Pork Avenue • Tipton PA 16684-0304

© 2014 New Pig Corporation. All rights reserved.
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: PLR212 - Pg 1 of 2

PLR212 Specifications

Style:	Standard
Color:	Yellow
Dimensions:	2.25" W x 10' L x 1.375" H
Intended For:	Smooth Surface
Max liquid temp exposure:	225°F for up to 30 minutes
Storage Temp Range:	0° — 120°F
Temperature Limit:	0° — 160°F up to 12 months
Sold as:	1 each
Weight:	13 lbs.
New Pig Patent:	5,236,281
National Stock Number (NSN):	7930-01-436-8320
# per Pallet:	108
Composition:	Polyurethane
UNSPSC:	24101907

PLR212 Metric Equivalent

Dimensions:	5.7cm W x 3m L x 3.5cm H
Weight:	5.9 kg

Technical Information

Warnings & Restrictions:

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.

Regulations and Compliance:

40 CFR 122.26 - When applying for a National Pollutant Discharge Elimination System (NPDES) permit, facilities must have a plan in place that describes actions, procedures, control techniques, management practices and equipment available to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7 - SPCC planning requirements state that facilities subject to these regulations must have written plans in place discussing the products, countermeasures and procedures that are in place, or will be taken by the facility to prevent discharge of oil into waters of the United States.

Technical Documents:

(Available at newpig.com)

Product Data Sheet (PDS)

Safety Data Sheet (SDS)

Chemical Compatibility (CCG)



New Pig

By Phone:
1-855-493-HOGS

Online:
newpig.com

Email:
hothogs@newpig.com

One Pork Avenue • Tipton PA 16684-0304

© 2014 New Pig Corporation. All rights reserved.
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: PLR212 - Pg 2 of 2