Corner for PIG® SpillBlocker® Dike

#PLR268 - 4.75" x 5" x 3"



Turn the corner with your SpillBlocker Dikes using this leakproof 90-degree connector.

- Add this handy corner piece to a pair of SpillBlocker Dikes to create a 90º angle
- Built-in dovetail connectors form a liquid-proof seal
- Build any shape or configuration to suit your application or environment



PLR268 Specifications

Style: Standard

Intended For: Smooth Surface

Max liquid temp exposure: 225°F for up to 30 minutes

Storage Temp Range: $0^{\circ} - 120^{\circ} F$

Temperature Limit: 0° — 160°F up to 12 months

 Sold as:
 1 each

 New Pig Patent:
 5,236,281

 # per Pallet:
 882

Composition: 100% polyurethane

UNSPSC: 24101907

Technical Information

Warnings & Restrictions:

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.

Regulations and Compliance:

40 CFR 122.26 - When applying for a National Pollutant Discharge Elimination System (NPDES) permit, facilities must have a plan in place that describes actions, procedures, control techniques, management practices and equipment available to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7 - SPCC planning requirements state that facilities subject to these regulations must have written plans in place discussing the products, countermeasures and procedures that are in place, or will be taken by the facility to prevent discharge of oil into waters of the United States.

Technical Documents:

(Available at newpig.com)
Product Data Sheet (PDS)
Safety Data Sheet (SDS)
Chemical Compatibility (CCG)



