

PIG® WashBlocker® Strip

#PLR500 - 1.25" x 10' x 0.75"



Easily keep washdown liquid from reaching neighboring areas or carpeted floors.

- Use low-profile spill dike for routine containment of washdown and sanitizing liquid
- Block doorways, protect carpeting, and channel liquid to drains
- Tacky urethane construction creates a leakproof seal on dry floors
- Tear-resistant polypropylene top withstands repeated use
- Lightweight strip is easy to handle and store
- Reusable barrier cleans up with soap and water
- Bright-green color is highly visible

Always in stock. Ships within 24 hours.



New Pig

By Phone:
1-855-493-HOGS

Online:
newpig.com

Email:
hothogs@newpig.com

One Pork Avenue • Tipton PA 16684-0304
© 2014 New Pig Corporation. All rights reserved.
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: PLR500 - Pg 1 of 2

PLR500 Specifications

Style:	Standard
Color:	Hi-vis Green
Dimensions:	1.25" W x 10' L x 0.75" H
Intended For:	Smooth Surface
Max liquid temp exposure:	225°F for up to 30 minutes
Storage Temp Range:	0° — 120°F
Temperature Limit:	0° — 160°F up to 12 months
Sold as:	1 each
Weight:	5.8 lbs.
New Pig Patent:	Patent Pending, Patent 5,236,281
Composition:	Top Film - Polypropylene Bottom - Polyurethane
UNSPSC:	24101907

PLR500 Metric Equivalent

Dimensions:	3.2cm W x 3m L x 1.9cm H
Weight:	2.6 kg

Technical Information

Warnings & Restrictions:

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.

Regulations and Compliance:

40 CFR 122.26 - When applying for a National Pollutant Discharge Elimination System (NPDES) permit, facilities must have a plan in place that describes actions, procedures, control techniques, management practices and equipment available to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7 - SPCC planning requirements state that facilities subject to these regulations must have written plans in place discussing the products, countermeasures and procedures that are in place, or will be taken by the facility to prevent discharge of oil into waters of the United States.

Technical Documents:

(Available at newpig.com)

Product Data Sheet (PDS)

Safety Data Sheet (SDS)

Chemical Compatibility (CCG)



By Phone:
1-855-493-HOGS

Online:
newpig.com

Email:
hothogs@newpig.com

New Pig

One Pork Avenue • Tipton PA 16684-0304
© 2014 New Pig Corporation. All rights reserved.
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: PLR500 - Pg 2 of 2