

PIG® DrainBlocker® Curb-Style Drain Cover

#PLR510 - For Rectangular Drains up to 114" x 12"



Thin DrainBlocker Drain Cover molds to seal vertical drains or contain washdown spray.

- Thin, pliable drain cover can form into an S-shape to block liquids from vertical storm drains
- Tear-resistant polypropylene top withstands repeated use
- Super-sealing urethane bottom layer creates a tight seal on curved or face-opening drains
- Reusable cover resists chemicals, oils and detergents
- High-visibility green makes it easy to confirm protection from a distance
- Ideal for power washing and other spill-prone operations
- Cost-effective alternative to inflatable plugs and other specialized equipment
- For drains with vertical and horizontal openings, this cover should be used with a DrainBlocker Drain Cover (sold separately)
- For custom sizes, call 1-800-HOT-HOGS (468-4647)

Always in stock. Ships within 24 hours.



New Pig

By Phone:
1-855-493-HOGS

Online:
newpig.com

Email:
hothogs@newpig.com

One Pork Avenue • Tipton PA 16684-0304
© 2014 New Pig Corporation. All rights reserved.
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: PLR510 - Pg 1 of 2

PLR510 Specifications

Style:	Non-Weight Bearing
Use With:	Rectangular Drains up to 114" x 12"
Color:	Green
Dimensions:	18" W x 120" L x 0.1" H
Intended For:	Smooth Surface
Max liquid temp exposure:	225°F for up to 30 minutes
Storage Temp Range:	0° — 120°F
Temperature Limit:	0° — 160°F up to 12 months
UV Resistant:	No
Sold as:	1 each
Weight:	11.00 lbs.
New Pig Patent:	Patent Pending
# per Pallet:	50
Composition:	Top - Polypropylene Bottom - Polyurethane
UNSPSC:	40141739

PLR510 Metric Equivalent

Dimensions:	45.7cm W x 3m L x 2.5mm H
Weight:	5 kg

Technical Information

Warnings & Restrictions:

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.

Regulations and Compliance:

40 CFR 122.26 - When applying for a National Pollutant Discharge Elimination System (NPDES) permit, facilities must have a plan in place that describes actions, procedures, control techniques, management practices and equipment available to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7 - SPCC planning requirements state that facilities subject to these regulations must have written plans in place discussing the products, countermeasures and procedures that are in place, or will be taken by the facility to prevent discharge of oil into waters of the United States.

Technical Documents:

(Available at newpig.com)

Product Data Sheet (PDS)

Safety Data Sheet (SDS)

Chemical Compatibility (CCG)



New Pig

By Phone:
1-855-493-HOGS

Online:
newpig.com

Email:
hothogs@newpig.com

One Pork Avenue • Tipton PA 16684-0304

© 2014 New Pig Corporation. All rights reserved.
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: PLR510 - Pg 2 of 2