



54123NT	750 kcmil	BLACK/106	3.800	1.575	1.330	1.330	.625	5/8
54123NT05	750 kcmil	BLACK/106	3.000	.781	1.330	1.330	.375	5/16
54123NT08	750 kcmil	BLACK/106	3.475	1.250	1.330	1.330	.500	1/2
54118NT	500 kcmil	BROWN/87	3.250	1.250	1.100	1.100	.500	1/2
58177NT06	925/24	n/a / 80	2.815	.815	1.100	.926	.375	3/8
54915BENTPH	350 kcmil	RED/71	3.500	1.062	.926	.926	.500	1/2
54115NT06	350 kcmil	RED/71	2.500	1.000	.926	.926	.375	3/8
54115NT	350 kcmil	RED/71	2.750	1.250	.926	.926	.500	1/2
58168NT	650/24	WHITE/66	2.512	1.062	.850	.850	.500	1/2
54179NT	300 kcmil	WHITE/66	2.143	.815	.850	.850	.375	3/8
54178NT04	300 kcmil	WHITE/66	2.325	.875	.850	.850	.250	1/4
54174NT	250 kcmil	YELLOW/62	2.165	.815	.766	.766	.375	3/8
54173NT	250 kcmil	YELLOW/62	2.131	.781	.766	.766	.375	5/16
54172NT	250 kcmil	YELLOW/62	2.000	.650	.766	.766	.250	1/4
54112NT	4/0 AWG	PURPLE/54	2.065	.815	.701	.701	.375	3/8
54167NT	4/0 AWG	PURPLE/54	1.900	.650	.701	.701	.250	1/4
54111NT	3/0 AWG	ORANGE/50	1.915	.815	.632	.632	.375	3/8
54162NT	3/0 AWG	ORANGE/50	1.680	.650	.632	.632	.250	1/4
54157NT	2/0 AWG	BLACK/45	1.600	.650	.571	.571	.250	1/4
54152NT	1/0 AWG	PINK/42	1.600	.650	.521	.521	.250	1/4
54108NT	#1 STR	GREEN/37	1.500	.650	.467	.467	.250	1/4
54107NT	#2-3 STR	BROWN/33	1.500	.650	.410	.410	.250	1/4
54138NT	#4 STR	GRAY/29	1.312	.562	.365	.365	.250	#10
CATALOG No.	WIRE SIZE	COLOR/CODE	<b>A</b> ±.093	<b>B</b> ±.062	<b>C</b> ±.015	E O.D.	<b>F</b> ±.030	<b>Bolt Hole</b>

MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER

FINISH: ELECTRO TIN PLATE

UL LISTED AND CSA CERTIFIED

GENERAL NOTES			
1. DIMENSIONS IN PARENTHESES ( ) ARE IN METRIC UNITS.			
REVISIONS		DESCRIPTION:	
<b>5</b> SEE ERN 2010252 FOR APPROVAL SIGNATURES PROJECT NO: CD55420		<b>ONE HOLE NARROW TONGUE LUGS</b>	
ORIGINAL PROJECT NO / ( ERN NO )		SHEET NO:	REV. NO:
CD55420 / (2007073)		1 OF 1	<b>5</b>
DRAWING NO:		<b>WSD-000288</b>	