





Good Better Best Superior

Cushion-Ease® is a resilient rubber anti-fatigue mat with an anti-slip surface texture and multi-nib backing to further enhance the ergonomic support of the mat. A large hole drainage system facilitates the removal of liquid and debris from the work area and its modular design is compatible with NoTrax® M.D. Ramp System for on-site custom configurations.

<u>Test</u>	Test Description	* <u>Results</u>
Compression Deflection	Test specimen is subjected to varying compression load levels and the resulting deflection was measured. The greater the deflection, the better the anti-fatigue properties. (Inches)	.146" (20 lbs/sq. inch) .209" (40 lbs/sq. inch)
Coefficient of Friction ASTM C1028-96	A neolite heel assembly with a predetermined load is pulled horizontally with a dynamometer to measure the force required to cause the assembly to slip.	.74
Abrasion Resistance ASTM D3884-01	Test specimen is subjected to the rubbing action of two abrading wheels under controlled conditions. Results measured in Weight loss (Grams)	10.76 Grams (10.8%)
Elongation ASTM D412	Test specimen is stretched at a specified rate until breaking point. The results are measured in weight needed to break, and % of size increase at breaking point.	59.5 lbs 195.1% (average of 5 specimens)
Hardness ASTM D2240-02	The hardness of a test sample is measured by means of a type A Shore Durometer. It measures the penetration of its specified indentor forced into the material under specified conditions	68

*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.



Anti-Fatique



Food Processing



Anti-Slip



Drainage



Food Service



Welding

Available in two versions:

 Black: NBR (Natural Rubber) - grease resistant w/1 year warranty

 Red: Nitrile Rubber - grease proof w/3 year warranty

• Thickness: 3/4"

• Weight: 3' x 3' (24 lbs), 3' x 5' (39 lbs)

• Stock Sizes: 3' x 3', 3' x 5'

Compatible with patented 551 MD Ramp System

