

Style 1347AF

PTFE Impregnated Syn-Tex™

Product Data

Material: PTFE Impregnated Syn-Tex[™]

Construction: Interwoven[™] braid

pH Range: 2 − 12

Pressure Limit: 1500 psi (103.5 bar)

PV Factor: 335,000

Shaft Speed: 2300 fpm (11.7 m/s)

Temperature Limit: -10°F to 450°F (-23°C to 232°C)



Service

Palmetto Syn-Tex™, style 1347AF, is a cost-effective combination of absorbent synthetic-textile staple yarn. The "thirsty" nature of this proprietary yarn permits a 50 percent pick-up of virgin PTFE suspensoid. This protects fibers from chemical attack, reduces running friction, and enahances sealability. The material's low gland follower squeeze extends packing and sleeve life and decreases motor energy draw. The entire packing is saturated in our proprietary break-in lubricant, improving initial start-up and preventing overheating and glazing.

Style 1347AF is proven in centrifugal pumps, mixers, blenders, agitators and knife gate valves.

Features

- · Soft, flexible and thoroughly lubricated Syn-Tex extends sleeve life and reduces down time.
- · Conformable material accepts difficult environments such as shaft runout, end play or misalignment.
- · Noncontaminating/nonstaining materials prevent product rejections.
- · Low initial cost reduces maintenance overhead profits.
- · Special petroleum-based break-in lubricant reduces the need for adjustments during break-in periods.

How to Order

Specify: style number, size, quantity and packaging desired

Size	in	1/8"	³ /16"	1/4"	⁵ /16"	3/8"	⁷ /16"	1/2"	⁹ /16"	⁵ /8"	¹¹ / ₁₆ "	3/4"	¹³ /16"	⁷ /8"	¹⁵ /16"	1"
	mm	3,20	4,80	6,40	7,90	9,50	11,10	12,70	14,30	15,90	17,50	19,10	20,60	22,20	23,80	25,40
Length	ft/lb	82.00	39.00	25.23	16.61	12.00	9.00	6.40	5.00	4.20	3.97	3.00	2.80	2.10	1.90	1.73
(±10%)	M/kg	54,94	26,13	16,90	11,13	8,04	6,03	4,29	3,35	2,81	2,66	2,01	1,87	1,41	1,27	1,16
Packaging		*Sizes 1	*Sizes 1/8" through 1/2" available in 1 lb. spools. All sizes available in 5 and 10 lb. boxes; 25 and 50 lb. reels.													

Distributed by

A Greene, Tweed Company Denton Industrial Park

25 Engerman Ave., Denton, MD 21629

Phone: +1.410.479.2244, Fax: +1.410.479.0836

E-mail: info@palmettopackings.com Website: www.palmettopackings.com

