

ACRYLIC URETHANE FLOOR PAINT 5600 SYSTEM



Improved aesthetics



5S / organization and safety markings



Easy maintenance



Spruce up your facility floor with low odor roll and go floor paint

- Ready-to-use with no messy measuring or mixing
- Protects against water damage, staining and mildew
- Excellent coverage over new and previously coated surfaces



ACRYLIC URETHANE FLOOR PAINT

5600 SYSTEM

<100 g/l VOC Acrylic Urethane Floor Paint

Less Prep Time • Applies direct-to-concrete or previously coated surfaces with minimal prep (washing and light scuff sanding).

Less Application Time • Easy roller application. Convenient one component formulation eliminates measuring, mixing and thinning.

Less Downtime • Can be applied during regular work hours with low to no solvent odor. Accepts next day foot traffic.

Greater Lifetime Value • Protection against dusting, staining, wear, chemicals and abrasion.

Typical applications

Interior and exterior concrete floors, walkways, decks and patios in mild industrial and commercial environments exposed to heavy and light rubber wheeled cart traffic.

Colors




1 gallon
Safety Yellow
#251286



1 gallon
Safety Red
#261115




1 gallon
Safety Orange
#261116



1 gallon
Safety Blue
#261117



1 gallon
Safety Green
#261118



1 gallon
White
#251289



1 gallon/5 gallon
Silver Gray
#251291/251293

Companion products



**5500 System
Acrylic Dust-Proof
Floor Sealer**

1 gallon Clear
#251282

5 gallon Clear
#251283



**200 Anti-Skid
Additive**
#200504



Ready-to-use



Easy-to-apply



Just roll and go



Protects against water damage,
staining and mildew

APPLICATION:



SUBSTRATES:



CONCRETE

Can be used in USDA-regulated facilities based on FSIS Directive 11,000.4 (Rev. 4), November 24, 1995. Agriculture Canada accepted.