## **TJ-3 Transmission Bearing Puller**

In keeping with Posi Lock's tradition of excellence, the TJ-3 Transmission Bearing Puller has been added to the manual puller line. The TJ-3 features the same unique characteristics as the TJ-1 and TJ-2 transmission bearing pullers such as the patented "Safety Cage®" and jaws that are specially machined to clamp in snap-ring grooves as narrow as .070 inches.

With Posi Lock's uniquely designed puller, jaws lock into snapring grooves and make transmission bearing removal quicker and safer! The smallest puller in the transmission bearing family,

the TJ-3 has a reach of 4 inches and spread range from .5 inch to 5 inches. This versatile 3-jaw puller has optional standard jaws available which give the TJ-3 the same capabilities as the manual model 104 puller.





**TJ-3 Specifications and Accessories** 

Number of Jaws	Reach in. (mm)	Spread in. (mm)	Weight Ibs. (kg)	Тір	Optional Accessories			
					Accessories	Optional Standard Jaws		
						Jaw	Reach	Spread
							in. (mm)	in. (mm)
3	4 in. (102 mm)	.5 to 5.5 in. (13 to 140 mm)	4.1 lbs. (1.9 kg)	P4	TJ-3 Bolt Extender	Standard Jaws	4 in. (102 mm)	.5 to 5 in. (13 to 127 mm)



Posi Lock features manual 2- and 3-jaw pullers ranging from 1 ton to 40 tons and hydraulic 2- and 3-jaw pullers ranging from 50 to 200 tons.