





ternational, Inc

FEATURES & BENEFITS

• Use in front of storm drains, around downspouts, in gullies, and ditches, or anywhere there is potential for harmful stormwater runoff.

CONTRACTOR AND A CONTRACTOR

- Woven polymer casing allows water to pass through quickly while filtration media inside removes pollutants.
- Available in 9-foot lengths. Units can be overlapped for longer coverage.
- Looped ends allow units to be staked in place and also assist in transport.
- · Available with different types of media depending on which pollutant is present.*
- Option for heavy-metal removal available.

Media Descriptions

- Activated Carbon: Excellent "polishing media". Helps remove certain chemicals, hydrocarbons and odors.
- Sorb 44: Used to remove oil and other hydrocarbons.
- Sediment Removal: Recycled rubber media provides weight, keeps unit in place, allows maximum water flow.
- Phos Filter: Excellent for removal of phosphorous.
- Heavy Metal Removal: Custom filter media helps remove zinc, lead, copper and other harmful, heavy metals.

Ultra-Filter Socks®			
Part#	Description	Dimensions in. (mm)	Weight lbs. (kg)
9453	Activated Carbon	108 x 7 x 4 (2,743 x 178 x 102)	40.0 (18.0)
9455	Sorb 44	108 x 7 x 4 (2,743 x 178 x 102)	15.0 (7.0)
9457	Sediment Removal	108 x 7 x 4 (2,743 x 178 x 102)	40.0 (18.0)
9456	Phos Filter	108 x 7 x 4 (2,743 x 178 x 102)	66.0 (30.0)
9454	Heavy Metal Removal	108 x 7 x 4 (2,743 x 178 x 102)	35.0 (16.0)

*Multiple Ultra-Filter Socks can be used in a "treatment train" if the potential for more than one contaminant or a large quantity of a single contaminant is present.