

Our Story

The Ventis Diner is proud to serve up safety all day, every day. Established in 2011, the Diner's already famous Ventis MX4 gas detector perfectly satisfies those cravings for a small, reliable multi-gas instrument to be used in a variety of applications.

At the Diner, we understand that each of our patrons have unique gas detection needs. That's why The Gas Detection People are so pleased to be able to meet those needs with the highly configurable Ventis. When ordering the instrument, select a powerful, yet lightweight pump for easy monitoring in confined spaces; choose a safety or-ange overmold for increased visibility of your fleet; or pick from a wide range of sensors to ensure safety in a variety of environments.

Best of all, you may order the Ventis with iNet™ – Industrial Scientific's software-based service that increases safety by providing visibility into alarms, exposure and usage. With iNet, patrons are delighted to find that they do not have to buy the Ventis and instead can subscribe to Gas Detection as a Service for a monthly fee.

We invite you to stop in to view our menu which includes the many ways the Ventis and iNet can meet your specific gas detection needs. Need a faster way to curb your appetite?

Build your instrument today at www.indsci.com/ventisbuilder.

**INDUSTRIAL
SCIENTIFIC**



NUTRITIONAL INFORMATION

Case Material:
Polycarbonate with Protective Rubber Overmold

Dimensions:
103 mm x 58 mm x 30 mm (4.1" x 2.3" x 1.2") - Ventis, Lithium-ion Battery Version (typical)
172 mm x 67 mm x 66 mm (6.8" x 2.6" x 2.6") - Ventis with Pump, Lithium-ion Battery Version (typical)

Weight:
182 g (6.4 oz) - Ventis, Lithium-ion Battery Version (typical)
380 g (13.4 oz) - Ventis with Pump, Lithium-ion Battery Version (typical)

Operating Temperature Range:
-20°C - 50°C (-4°F - 122°F) typical

Operating Humidity Range:
15%-95% Non-condensing (continuous) typical

Display/Readout:
Backlit Liquid Crystal Display (LCD)

Power Source/Run Time:
Rechargeable Lithium-ion Battery Pack (12 hours typical @ 20°C) - Ventis
Rechargeable Extended-Range Lithium-ion Battery Pack (20 hours typical @ 20°C) - Ventis
(12 hours typical @ 20°C) - Ventis with Pump
Replaceable AAA Alkaline Battery Pack (8 hours typical @ 20°C) - Ventis
(4 hours typical @ 20°C) - Ventis with Pump

Alarms:
Ultra-bright LEDs, loud audible alarm (95 dB at 30 cm) and vibrating alarm

Sensors:
Combustible gases/methane - Catalytic Diffusion
O₂, CO, H₂S, NO₂, SO₂ - Electrochemical

Measuring Ranges:
Combustible Gases:
0-100% LEL in 1% increments
Methane (CH₄):
0-5% of vol. in 0.01% increments
Oxygen (O₂):
0-30% of vol. in 0.1% increments
Carbon Monoxide (CO):
0-1,000 ppm in 1 ppm increments
Hydrogen Sulfide (H₂S):
0-500 ppm in 0.1 ppm increments
Nitrogen Dioxide (NO₂):
0-150 ppm in 0.1 ppm increments
Sulfur Dioxide (SO₂):
0-150 ppm in 0.1 ppm increments

Certifications:
UL
Class I, Division 1, Groups A B C D, T4
Class II, Groups F G (Carbonaceous & Grain Dust)
Class I, Zone 1, AEx ia d IIC
IP66; IP67
ATEX
Ex d ia I Mb / Ex d ia IIC T4 Gb;
Equipment Group and Category I M2 and II 2G
IP66; IP67
IECEx
Ex d ia IIC T4 Gb
IP66; IP67
CSA
Class I, Division 1, Groups A B C D, T4
C22.2 No. 152
Ex d ia IIC T4
ANZEx
Ex ia s Zone 0 I
Ex ia s Zone 0 IIC T4
IP66; IP67
INMETRO
Ex d ia IIC T4 Gb
IP66; IP67

**INDUSTRIAL
SCIENTIFIC**

www.indsci.com

ISO 9001:2008
CERTIFIED

ISO 14001:2004
CERTIFIED

AMERICAS
Phone: +1-412-788-4353
Fax: +1-412-788-8353
info@indsci.com

ASIA PACIFIC
Phone: +65-6561-7377
Fax: +65-6561-7787
info@ap.indsci.com

EUROPE
Phone: +33-3-21-60-80-80
Fax: +33-3-21-60-80-00
info@eu.indsci.com

The **VENTIS™**
DINER

Served by The Gas Detection People



**INDUSTRIAL
SCIENTIFIC**

www.indsci.com

GETTING STARTED

Versions

Ventis..... Served with a calibration cup, calibration tubing, service tool and reference guide



Ventis with a pump Served with sample tubing, calibration tubing, service tool and reference guide



Sensors

Combustible gases (Select one).....LEL (Pentane),
LEL (Methane), CH₄ (0-5%)

Toxic gases (Select two)..... CO, H₂S, SO₂, NO₂

Oxygen O₂



Batteries

Rechargeable lithium-ion battery..... Up to 12 hours
of run time without pump



Rechargeable extended-range lithium-ion battery..... Up to 12 hours
of run time with pump or 20 hours without pump



Replaceable AAA Alkaline battery pack..... Up to 4 hours
of run time with pump or 8 hours without pump



Colors

Black.....



Safety orange.....



Reference Guide Languages

Language (Select one) English, French, Spanish, German, Italian,
Dutch, Portuguese, Russian,
Polish, Czech, Chinese,
Danish, Norwegian,
Finnish, Swedish



A LA CARTE

Docking Station

Optimize nearly any size gas detector fleet using a Docking Station that provides consistent and automated calibration, record keeping, diagnostics and battery recharging.



Calibration Stations

Calibrate and bump test the Ventis with or without the pump using the stand-alone station designed for use with the respective configuration.

Chargers

Prepare your Ventis and/or gas detector fleet for operation by choosing from a number of charger options which range from a simple single-unit charger to a robust six-unit charger.

Cases

Select a soft or leather carrying case to ensure protection of your instrument no matter the environment.

Confined Space Kits

Simplify confined space monitoring using a kit which includes the Ventis with a pump, universal charger, soft carrying case, service tool, reference guide, calibration tubing, dust filter/water stop, calibration fitting, sample tubing, calibration gas (appropriate mix) with regulator and rugged case.



DINER CLASSICS

Perfect for personal or confined space entry monitoring, the Ventis is useful in a variety of industries. The Ventis Diner offers classic diner selections that can be commonly used in the following industries and applications.

Construction

- Confined space entry (trenching, tank entry)..... O₂, LEL, CO, H₂S or NO₂
- Personal monitoring..... O₂, LEL, CO, H₂S or NO₂

Electrical / Gas Utilities

- Coal storage (coal loading, bin inspection) CO, CH₄
- Boiler operations (confined spaces, boiler startup, maintenance)..... O₂, LEL, CO, SO₂ or NO₂
- Confined space entry (transmission, distribution, maintenance, turnaround, transformer vaults, manholes)..... O₂, LEL, CO, H₂S
- Pipeline construction (trenching) O₂, LEL, CO, H₂S

Steel Production

- Blast furnace (operations and maintenance)..... O₂, LEL, CO, SO₂ or NO₂
- Pits (pit inspection, maintenance)..... CO, O₂
- Confined space entry (maintenance, turnaround)..... O₂, LEL, CO, H₂S
- Personal monitoring..... O₂, LEL, CO, H₂S, NO₂ or SO₂

Oil and Gas Production

- Drilling (spudding, drilling, flaring) O₂, LEL, H₂S, SO₂
- Transportation, storage and distribution (pipelines, tanker truck, tank farms, pipeline monitoring)..... O₂, LEL, H₂S, SO₂
- Confined space entry (maintenance, turnaround) O₂, LEL, CO, H₂S

Chemical

- Hot work ("live" pipes, tank work) O₂, LEL, CO, H₂S
- Confined space entry (tank/vessel entry) O₂, LEL, CO, H₂S, SO₂ or NO₂
- Personal monitoring..... O₂, LEL, CO, H₂S or SO₂

Fire Services

- Confined space entry (confined space rescue) O₂, LEL, CO, H₂S
- Carbon monoxide response CO
- Hazmat O₂, LEL, CO, H₂S, SO₂ or NO₂
- Gas leak response..... O₂, LEL

Water / Waste Water Treatment

- Storm and waste water collection (dry/wet wells, manholes, sumps WWT plants)..... O₂, LEL, CO, H₂S or SO₂
- Confined space entry (meter pits, vaults, underground tunnels, access ways, dry/wet wells)..... O₂, LEL, CO, H₂S

ASK ABOUT OUR CHEF'S SPECIAL



iNet eliminates costly and time-consuming maintenance while keeping your Ventis, and other iNet-Ready instruments, working. Don't buy gas detectors. Instead, subscribe to Gas Detection as a Service.

