

NOTES:

- 1. FINISH: Unpainted
 2. MAX. TORQUE: 50.0 in.-lb.
- 3. LUBRICATION: Grease Filled
- 4. BRUSHES: Externally Replaceable 5. GEAR MATERIAL: Acetyl / Steel

- 6. SEALS: O-Ring Type on Output Shaft
 7. GEARMOTOR MOUNTING POSITION: All Angle 8. SHAFT TYPE / ORIENTATION: Single / Parallel
- 9. GEARMOTOR ENCLOSURE: Totally Enclosed Nonventilated
- 10. BEARINGS: Porous Bronze Sleeve on Case, Ball on Motor
- 11. GEAR CASE / HOUSING MATERIAL: Die Cast Zinc / Die Cast Zinc



100 Grainger Parkway, Lake Forest, Illinois 60045-5201 1-(800) GRAINGER, 1-(800) 472-4643, (847) 535-1000 www.grainger.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. Grainger makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file. information or specifications.

This drawing is the property of GRAINGER. It contains confidential, proprietary information that is GRAINGER property. Do not disclose to or duplicate for others except as authorized by GRAINGER.

SCALE

0.15

COMPONENT

DC Gearmotor

1LPV7

DC Gearmotor, 5 RPM, 90 V, TENV

INCH

UNIT

SHEET

1 of 1