



NOTES:

1. WEIGHT: 0.44 Lbs.
2. STIFFNESS: 10000
3. MAXIMUM RPM: 6000
4. COMPONENT WR2: 0.0066 bs-ft²
5. TORQUE RATING: 1800 in-lb
6. MATERIAL: Hytrel
7. MAX. ANGULAR MISALIGNMENT: 1° in.
8. MAX. PARALLEL MISALIGNMENT: 0.016 in.
9. MAX. ANGULAR GAP MISALIGNMENT: 0.01 in.
10. OPERATING TEMPERATURE: -65°F to +250°F

COMPONENT		Sleeve Coupling Insert	
32ZP98		UNIT	INCH
		SHEET	1 of 1
Sleeve Coupling Insert, 6H, Hytrel		SCALE	0.87



100 Grainger Parkway, Lake Forest, Illinois 60045-5201
 1-(800) GRAINGER, 1-(800) 472-4643, (847) 535-1000
 www.grainger.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. Grainger makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

This drawing is the property of GRAINGER. It contains confidential, proprietary information that is GRAINGER property. Do not disclose to or duplicate for others except as authorized by GRAINGER.