



**NOTES:**

1. WEIGHT: 1.4 Lbs.
2. MAXIMUM RPM: 6,000
3. MATERIAL: High Strength Cast Iron
4. COMPONENT WR2: 0.0091 lbs-ft<sup>2</sup>
5. SET SCREW TORQUE REQUIREMENT: 13 ft-lb
6. MAXIMUM PARALLEL MISALIGNMENT: 0.015 -> EPDM/Neoprene Sleeves, 0.010 in.-> Hytrel Sleeves in.
7. MAXIMUM ANGULAR GAP MISALIGNMENT: .0070 -> EPDM/Neoprene Sleeves, 0.016 in.-> Hytrel Sleeves in.
8. CAPSCREW SPECS: Hex Head, Qty 4, Size 1/4 x 1-3/4" Lg., 9 ft-lb Torque Req., (Furnished)
9. TORQUE RATING: 585 in-lb -> EPDM or Neoprene Sleeves, 1800 in-lb -> Hytrel Sleeves
10. MAXIMUM ANGULAR MISALIGNMENT: 1° -> EPDM & Neoprene Sleeves, 0.25 ° -> Hytrel Sleeves

<b>COMPONENT</b>		Spacer Coupling Hub	
<h1>32ZR94</h1>		<b>UNIT</b>	INCH
		<b>SHEET</b>	1 of 1
<b>SCALE</b>		1.25	
Sure-Flex® Plus Coupling Hub			



100 Grainger Parkway, Lake Forest, Illinois 60045-5201  
 1-(800) GRAINGER, 1-(800) 472-4643, (847) 535-1000  
 www.grainger.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. Grainger makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

This drawing is the property of GRAINGER. It contains confidential, proprietary information that is GRAINGER property. Do not disclose to or duplicate for others except as authorized by GRAINGER.