



| Force Rating | 160 lb. | Max. Pressure | 80 psi |
|---------------------|------------|----------------|------------|
| Bin Weight Capacity | 1600 lb. | Max. Temp. | 350 °F |
| Speed @ 80 psi | 12,000 VPM | Speed @ 60 psi | 10,000 VPM |
| dB @ 80 psi | 70 | dB @ 60 psi | - |
| CFM @ 80 psi | 2.5 | CFM @ 60 psi | 2.3 |





NOTES:

MOUNTING: Foot
 MUFFLER: Included
 DUTY: Continuous

VIBRATOR TYPE: Turbine
 HOUSING MATERIAL: Cast Iron

6. MOUNTING PLATE: Sold Separately

7. STANDARDS: CE Certified, ATEX Certified

| CD | 75 T | | | |
|----|------|------------|---|----|
| GR | AI | LA! | 5 | SR |
| | A | 10. 10.251 | | |

100 Grainger Parkway, Lake Forest, Illinois 60045-5201 1-(800) GRAINGER, 1-(800) 472-4643, (847) 535-1000 www.grainger.com This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. Grainger makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

This drawing is the property of GRAINGER. It contains confidential, proprietary information that is GRAINGER property. Do not disclose to or duplicate for others except as authorized by GRAINGER.

SCALE

0.667

COMPONENT

Pneumatic Vibrator

4HV36

PNEUMATIC VIBRATOR, 160 LB, 10,000 VPM, 80 PSI

UNIT
INCH [MM]

SHEET

1 of 1